



Advanced Manufacturing Services Ltd

80 Biddulph Road

Congleton

Cheshire

CW12 3LG

Email: sales@ams-electronics.co.uk

Tel: +44 (0) 1260 270 950

■ Dual Rail Conveyor

Features

- Modular design, PLC controlled
- Stability enhanced by heavy design
- Ergonomic design arm rest
- Smooth and parallel width adjustment (stainless steel screws)
- Different lengths available upon request
- Multi-segment concept available upon request
- Automatic/Manual modes
- Independent variable speed controls for each rail
- Independent inspection buttons
- SEMA compatible
- Conveyor height 950±30mm

Options


- Covers for operator protection
- High-clearance on request
- Cooling fans on top for after-reflow
- Light system for better inspection
- Shelf with ESD component boxes
- Motorized width adjustment
- Chain transport system



Technical Parameters

Description	This unit is used as a visual inspection station for operators between SMT machines or board handling unit to link the machines. Dual rail version.
Belt Type	Antistatic Flat Belt of 3mm width
Conveyor Speed	0.5-20m/min or specify
Power Source	AC 220V, 50/60Hz, 1 phase
Power Consumption	100W Max.

Schematic



Specifications

Units in mm

Size	Model	Machine Dimensions (LxWxH)	Effective PCB Size	Weight (Kg)
M	LS-C050SD3BM-Y	500x843x950	50x50 - 470x250	92
L	LS-C050SD3BL-Y	500x1003x950	50x50 - 470x300	97
M	LS-C100SD3BM-Y	1000x843x950	50x50 - 530x250	102
L	LS-C100SD3BL-Y	1000x1003x950	50x50 - 530x300	107