


Specification

【 Electronic Component Mounting System 】



Model ID : **NPM-W2**

Model No. : NM-EJM7D (Mount)
NM-EJM7D-MD (Mount + Dispense)
NM-EJM7D-MA (Mount + AOI)
NM-EJM7D-D (Dispense)
NM-EJM7D-A (AOI)

Cautions Regarding These Specifications

Please note the following points.

1. This document may not be copied or reproduced in part or in total, without permission.
2. Due to improvements to the machine and software, the specifications may change without notice.
3. If there are any questions regarding the content of this document, please contact us.
4. Please use the machinery and software with full understanding of its specifications and limitations. We do not assume responsibility for damages resulting from improper use.
5. Some of our products fall under the export control items (or technologies) established in the Foreign Exchange and Foreign Trade Act.
When exporting (or providing technologies overseas), please check its legal restrictions and be sure to take necessary procedures such as to obtain the export permission.
6. This machinery may come under U.S. government re-export regulations.
When moving the machinery outside of Japan, apply for the necessary export permission from the U.S. government in advance.
7. Products without complying with Machinery Directive or EMC Directive are not allowed to carry into or sell in EU countries.
8. Technical information in this document is provided only as a guide for the major operation and applications of the products.
No responsibility is assumed by our company for any infringements of intellectual property or other rights of ours or any third parties which may result from its use.
No license is granted by implication or otherwise under any patent or patent rights of our company or others.
We reserve any industrial property rights such as patents, copyrights, and other intangible property rights relating to our products, which are developed and manufactured by customers' request or information.
9. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
10. As the manufacturer of this system, we do not assume responsibility for defective products or costs incurred as a result of improper operation (errors in writing data to memory).
11. When reselling or moving this equipment, please make sure to contact us, our sales subsidiaries or agents.
12. The contents of this document are valid as of August 8, 2023.

 Precautions for Safe Use	
● Thoroughly read the instruction manual and use the machine only as directed.	● The machine described in this Specification is an industrial machine. Confirm the operation requirements described in the separate instruction manuals. Regarding machine installation, operation and maintenance, and handling of necessary materials, the local laws and requirements may be applied. ● Before carrying out the operation and maintenance of this machine, confirm the descriptions in the separate instruction manuals and warning information attached on this machine regardless of the operating condition of this machine. Ignoring safety functions might cause injury, electric shock or machine trouble.

Revision History

This document content is based on the version of the last date printed below.

Revision date	Version	Revised page	Revisions
Dec. 10, 2014	Ver. 2014.1210	---	First edition
Dec. 16, 2014	Ver. 2014.1216	P. 5, 12, 39, 84, 89, 95, 98	Addition of 4 mm thin type single tape feeder and its associated options
Apr. 1, 2015	Ver. 2015.0401	P. 39, 52 ~ 56, 65, 66, 76, 85, 89, 96, 100, 109 ~ 113	• Addition of maintain the thin type single tape feeder by IFCU • PanaCIM (support “Material Control module” and “Production Monitoring module”) • Feeder Setup Navigator(support mobile terminal, others) • Addition of Head maintenance unit and its associated options • “4.7 Recognition Unit Configuration” :Addition of explanation • Addition of Win8.1 support. For the PC (NIP) which is using interface software from other companies.
Apr. 28, 2015	Ver. 2015.0428	P. 86, 112, 113	Addition of Automatic Tape Splicing Unit (ATSU)
Jun. 15, 2015	Ver. 2015.0615	P. 69, 87, 115, 116, 128	Addition of Component Supply Navigator Addition of Feeder Maintenance Unit (IFMU).
Jul. 24, 2015	Ver. 2015.0724	P. 69, 85, 98, 112, 113	• Revision of Component Supply Navigator • Revision of Head maintenance unit
Aug. 20, 2015	Ver. 2015.0820	P. 61	• Change of the product name of wireless scanner(PDA). MC75 ⇒ MC55
Jan. 22, 2016	Ver. 2016.0122	P. 101	• Correction of typo On-site ⇒ Factory
Feb. 19, 2016	Ver. 2016.0219	P. 11	• “3.2 Standard Functions” :Addition of explanation
May. 25, 2016	Ver. 2016.0525	P. 79 ~ 81, 132	Function addition : • Automatic recovery function for pickup error • Component inspection before pickup (Polarity) • Message board • Head diagnosis
Oct. 18, 2016	Ver. 2016.1018	P. 3 ~ 5, 39 ~ 41, 90, 96, 97, 122, 124, 126	• Addition of 8mm Auto Load Feeder and its associated options
Nov. 18, 2016	Ver. 2016.1118	P. 62, 72	• Revision of Component Verification
May. 22, 2017	Ver. 2017.0522	P. 12, 26, 31, 42, 60, 80, 83, 92, 93, 100, 105, 107, 118 ~ 125, 145	• Deletion of the reference on 32 mm adhesive tape feeder • Addition of Nozzle changer large type for 8-nozzle head • Change to Nozzle 1599/1599N • Microsoft® Windows® 10 Pro Addition of (32-bit/ 64-bit version) • Revision of Component inspection before pickup (Polarity) Function addition : • 16-nozzle head constant mount load control (Lightweight type) • 16-nozzle head transfer (Lightweight type) • Load checker • Pre-pickup Inspection (Char/2D) • Multi-recognition camera PIP lighting • AOI info display function

Jul. 28, 2017	Ver. 2017.0728	P. 94, 130 ~ 135, 138	- Revision of Automatic Tape Splicing Unit (ATSU) - Revision of Feeder Maintenance Unit (IFMU)
Aug. 31, 2017	Ver. 2017.0831	P. 12, 42, 44 ~ 46, 49, 76, 96, 104, 105, 116, 149 ~ 151	<u>Function addition</u> - Stackable stick feeder - Single stick feeder
Oct. 13, 2017	Ver. 2017.1013	P. 140	Addition of Microsoft® Windows® 10 Pro for IFMU
Nov. 07, 2017	Ver. 2017.1107	P. 50, 56, 72, 78, 83, 123, 140, 142	Change of software OS specifications, etc.
Feb. 23, 2018	Ver. 2018.0223	P. 46	Addition of explanation about management of stackable stick feeder
Apr.16, 2018	Ver. 2018.0416	P. 26, 87, 88, 98, 122, 126 ~ 129	- Addition of tape feeder components in "Polarity recognition" and "Character/2D code recognition" in component inspection before pickup - Addition of supplementary explanation about lightweight 8-nozzle head - Modification of applicable component dimensions of multi-functional transfer unit
Sep. 05, 2018	Ver. 2018.0905	P. 60, 141, 158	- Addition of the size of applicable components of Multi-recognition camera (Type 2) - Addition of specification to the PC requirements about IFMU - Addition of "Important Notes"
Oct. 12, 2018	Ver. 2018.1012	P. 7, 45, 73, 80 ~ 83, 85 ~ 87, 89, 102, 103, 110, 125 ~ 127, 129 ~ 136, 161	- Revision of APC System - Addition of APC-MFB2 - Modification of the "Constraint condition" about Feeder Setup Navigator - Addition of the descriptions for the use of stackable stick feeders
Nov. 1, 2018	Ver. 2018.1101	P. 34, 49, 94, 103, 122, 123, 161	- Addition of iLNB ready - Addition of a dedicated jig(nozzle) list for head diagnosis - Corrected errors, added descriptions, revised descriptions
Dec. 21, 2018	Ver. 2018.1221	P. 6, 7, 45, 73, 79 ~ 83, 85 ~ 90, 104, 126, 149	- Revision of descriptions about APC ready - Addition of "Note" on auto load feeder - Corrected errors, added descriptions, revised descriptions
Oct. 15, 2019	Ver. 2019.1015	P. 96 ~ 104, 113 ~ 115, 140 ~ 149, 160, 172	- Deleted explanations about IFCU - Standardized the following options: - Remote operation - Biometric authentication - Mount complete position recognition - LCR checker (Feeder shape type)
Nov. 1, 2019	Ver. 2019.1101	P. 1, 11 52	Revised the descriptions on connection to DX, D3/ D2/ D
Jan. 17, 2020	Ver. 2020.0117	----	Deleted "Note" given at the beginning
Feb. 2, 2020	Ver. 2020.0207	P. 87	Added APC-MFB, AOI recognition level and the range where MFB could be applied
Apr. 27, 2020	Ver. 2020.0427	P. 51, 79	- Quality information viewer, Support station (operating system compatibility updated) - Other
Jun. 25, 2020	Ver. 2020.0625	P. 73	Modification of the "System Requirements" about Feeder Setup Navigator
Sep. 28, 2020	Ver. 2020.0928	P. 66 ~ 68, 153, 156, 162 ~ 164	- Added LCR checker(Built-in type) - Revised Feeder Maintenance Unit(IFMU) - Added an additional explanation to Head Maintenance Unit
Oct 30, 2020	Ver. 2020.1030	P. 121	Specified the fact that multi-recognition camera Type3 comes with side lighting
Jan 5, 2021	Ver. 2021.0105	P. 118, 154, 168	- Added Primary air hose to the options (illustration changed) - Added separators to options

[illegible]

Contents

1.	General Description.....	1
2.	Features	1
3.	Specification	9
3.1	Standard Specifications	9
3.2	Standard Functions.....	10
3.3	Placement mode	15
3.4	Description of Inspections.....	18
3.5	Dispense Capability	21
4.	Machine Configuration	24
4.1	Head Configuration	27
4.2	Nozzle Configuration.....	29
4.3	Dispense Nozzle Configuration.....	39
4.4	Feeder Carriage Configuration	43
4.5	Line Configuration.....	54
4.6	Line configuration that includes a machine equipped with an inspection head.....	57
4.7	Recognition Unit Configuration	62
4.8	LCR checker(Built-in type)	70
5.	System software.....	73
5.1	Component Verification* ¹	73
5.2	Automatic Changeover	76
5.3	Feeder Setup Navigator.....	79
5.4	Upper Communication	81
5.5	Component Supply Navigator	83
5.6	Support station	84
5.7	APC system	87
5.7.1	APC-FF	89
5.7.1.1	When you use SPI of inspection machine from other companies	90
5.7.1.2	When you use inspection heads	92
5.7.2	APC-MFB	93
5.8	PCB information communication function (standard feature)	99
5.8.1	When Receiving Bad Marks from Other Company Inspection Machines.....	100
5.9	Automatic recovery function for pickup error	101
5.10	Component inspection before pickup (Polarity)	102
5.11	Pre-pickup Inspection(Char · 2D Recognition)	104
5.12	Message board	108
5.13	Head diagnosis	108
5.14	Remote operation	109
5.15	Biometric authentication.....	113
5.16	Mount complete position recognition	114
5.16.1	Mount complete position recognition function	114
5.16.2	Shield case warping inspection function before mounting	115
5.17	Tray 1 Pallet 10 Kind.....	116
5.18	LCR checker(Feeder shaped type).....	118
5.19	Tray Pickup Positions Offset (Standard Specification)	120
6.	Other Standard Functions	122
6.1	Programming Functions.....	122
6.2	Signal Tower	122
7.	PCB Design Standard	123
7.1	PCB Specifications	123
7.2	Recognition Mark	126
7.3	PCB waiting condition	126
8.	Standard Machine Configuration	127
9.	Options	128
10.	Paint Color.....	182
11.	Safety Devices	182
12.	Electric / Pneumatic.....	183
12.1	Electric Source Unit	183
12.2	Pneumatic Source Unit	184
13.	Dimensions.....	185
14.	Regarding Licenses.....	193

1. General Description

■ High Productivity

Simultaneously materialized the further improved area productivity and the high accuracy placement through Lightweight 16-nozzle head V3A, multi-recognition camera and high rigid frame.

■ Versatility

It is possible to combine “Lightweight 16-nozzle head V3A”, “12-nozzle head” suitable for super-high speed placement of microchips, “Lightweight 8-nozzle head” suitable for high speed placement of microchips to medium-size components, and “3-nozzle head V2” that supports various kinds of odd-shaped components. Moreover, it is possible to support various processes by combination of the “2D inspection head” that performs various inspections of produced PCBs and the “Dispensing head” that applies adhesives in order to temporarily joint electric components.

Its standard compatibility with large-sized PCBs of up to L 750 × W 550 mm* has further enhanced its general versatility.

Possible to upgrade from 2D measurement specification to 3D (Thickness, 3D measurement) by employing “Multi-recognition camera” consolidated 3 functions (2D, Thickness and 3D measurement).

* For single conveyor specifications

■ Efficient Changeover

In the independent mode*, you can conduct a changeover on one lane while production continues on the other lane. It supports automatic support pin replacement (option) and an automatic changeover (option) so that it provides the best changeover for your production type.

* For dual conveyor specifications

■ High-Quality Placement


High-quality placement is possible carrying over various unit and functions of NPM series.

2. Features

High Productivity

Support for machine coupling (modularizing)

NPM-W2 supports coupling (modularizing); up to 15 machines* can be coupled.




Conceptual illustration of data distribution for a total of four NPM-W2 machines

* When the number of machines coupled exceeds 15 machines, please consult us.

* Connecting to NPM-DX/ D3A/ D3/ D2/ D requires a traverser between them. The machine cannot be connected to NPM-TT or NPM.


Placement tact time



0.043 s/chip

With Lightweight 16-nozzle head V3A specifications
(When high production mode is "ON")
(In the dual lane specification)

Dispense tact time



Dot dispense

0.16 s/dot

- XY movement: within 10 mm
- Without θ rotation
- Blow-off time: within 20 ms
- During continuous operation under optimum conditions

Draw dispense^{*1}

4.25 s/part^{*2}

- Drawing size: within 30 × 30 mm
- Corner dispensing,
Under optimum conditions

^{*1} For drawing dispense (non-contact dispense), the height sensor (option) is required.

^{*2} PCB height measurement time (0.5 s) is included. (30 × 30 mm, with 4-point measurement)

**** Remarks ****

- Optimum conditions mean the placement conditions defined by our original standards.

PCB exchange time

Two PCBs can be clamped when PCB length is up to 350 mm.

Even when the NPM-W2 is dual conveyor specification, clamping two PCBs per lane is also available.*1

When two PCBs are clamped, after the placement of the PCB on the downstream side is complete, that on the upstream side is carried out continuously.

In the case of PCBs of 350mm or less in length (L), one PCB is replaced by another within 2.3 seconds*2.


(That is attainable if no components are placed on the back side, and support pins are not used.)

The others are based on our measurement conditions.)

*1 The two PCBs clamping is not done when share mode is selected in dual lane mode.

*2 Transfer time varies depending on such conditions as a PCB size and whether the support pins are used or not.

For further information, please contact us.



When you use the dual conveyor (option), it is possible for you to exchange PCBs in one lane while you are placing components in another lane, resulting in actual PCB exchange time of 0 s.

(It can't be 0 s, when the cycle time is less than PCB exchange time.)


Feature of components supply during operation

NPM-W2 has a tape splicing function, which allows components to be supplied without stopping the placement process during operation.

If the number of components is pre-registered, a warning will be issued before they run out.

Tape splicing can be done in manual by hand or automatic by ATSU.

However, by using an auto load feeder, tape splicing will not be needed and a continuous components supply can be provided.



Versatility

Auto Load Feeder (8 mm) *

This is a thin type feeder materialized automatic component tape setup.

The off-line setup time can be drastically reduced by the simple work of inserting a tape, then pressing the “Send” button. (Approx. 30s/reel ⇒ Approx. 15s/reel)

If insert a following component in advance, this feeder can detect the tape end of preceding component and automatically supply the following component during production.

Because you don't need a tape splicing work, the error stop of splice mistake can be prevented.

This auto load feeder can also use a short cut tape (longer than 120mm).

* Not available for emboss tape.

* Available for 0402, 0603, 1005 and 1608 paper tape components. If want to use 2012 or 3216, please contact us.

Compatibility with large-sized PCBs or components

NPM-W2 is standard compatible with large-sized PCBs of up to L 750 × W 550 mm^{*1}.

3-nozzle head V2 is compatible with odd-shaped large components up to 150 × 25 mm(or 120 × 90 mm) ^{*2}, and compatible component height has extended to 30 mm^{*3}.

*1 For single conveyor specifications

*2 When you choose Large heavy component mount (option), it is up to 135 × 135 mm.

*3 When you choose Tall Component mount (option), it is over 30 mm.

Flexible location of the tape feeder*

The tape feeder can be located flexibly within the same table.

You can locate components alternately and the feeder for the next product at an empty slot.

* Using the “Support station: Component verification type”, you need to write data to tape feeders in advance.
“Component verification (license)” is also needed.

Head exchange function

In NPM-W2, you can select any head from among the different types (placement, dispensing and inspection heads^{*1}) for each table. ^{*2}

*1 Inspection head can be selected for front side only.

*2 Please select the Head for each table. It is possible to set different types of Heads to the front and the rear table.
For the table of tray feeder, however, only the lightweight 8-nozzle head and the 3-nozzle head V2 are available.


Number of setting feeder and tray

Up to 60 double tape feeders can be set on NPM-W2.
At this time, 120 reels can be set. (for the small reel)

$30 \text{ feeders} \times 2 \text{ reels} \times 2 \text{ tables} = 120$ of 8 mm tape reels can be set.

The single tray feeder connection table, equipped with 13-slot feeder base, allows you to set up 20 types of trays and 13 double tape feeders at the maximum.

Up to 40 types of trays can be set to the twin tray feeder connection table.




Compatibility with the CM series

Compatibility of feeders, nozzle and others are secured for NPM series with CM series (CM602, CM402, CM401, CM400, DT401, CM232, CM212 and CM101) having good track record.

Versatility of feeders

The feeders, which are compatible with the AM100 and CM series, support 4-mm up to 104-mm paper/ embossed tape.

Tape feeding is driven by the servomotor; feed pitch and feed speed are set according to the components. These parameters are set by the data sent from the main body.



*Thin type tape feeders cannot be used in CM series.

Efficient Changeover


Independent changeover

In the independent mode*¹, you can perform a changeover (product data change and feeder cart replacement) on one lane while production continues on the other lane.*²

*1 For dual conveyor specifications

*2 It is not possible to do works by opening safety covers (such as manual replacement of support pins). The “independent changeover support unit (option)” is necessary for feeder cart exchange.

Production example of the different types of products in the independent mode




Automatic replacement of support pins

A function to automatically set up the support pins using the placement head.

This does not need to access an operator inside the machine, contributing manpower saving for changeover and prevention of human errors.

It also realizes non-stop changeover during production in dual lane mode.



Automatic Changeover

This supports changeovers (production data change and rail width change), minimizing the time loss of operation caused by product changes. In accordance with each customer's operation, selection can be made from following two types, “External scanner read type”, and “Head read type”.

Multi job production

Per NPM-W2, 120 types of components (on an 8 mm tape basis) can be set. Even while the machine is running, it is possible to set the taped components for another model to vacant slots in advance, increasing the efficiency of changeovers. The data creating system NPM-DGS can sort the placement data for each stage, taking this multi-job production system into consideration.

High-Quality Placement


■ Component thickness measurement function (Multi-recognition camera: Type 2/ Type 3)

Two functions provide high quality placement. These are applicable for each Placement head.

- Measurement function of component thickness:
Component thickness is measured, and the results are reflected on placement height, making the placement more stable. Standing/tilted standing of micro components at the time of their pickup can also be checked simultaneously.
- Check function of nozzle tips:
Placement quality can be enhanced by periodical nozzle height checks.

■ 3D-measurement function (Multi-recognition camera: Type 3)

Detects coplanarity(flatness) of all the leads in QFP/SOP and other packages, and presence or absence of all the balls, and partially broken balls in its shape in BGA/CSP and other packages.



■ Calibration feature

Our unique calibration program realizes high accuracy placement. An automatic calibration feature maintains initial high precision even during operation.

(Each parameter is automatically corrected by periodically recognizing the gauge mark during operation.)

■ High speed low vibration control

High speed low vibration control has been introduced to the XY unit operation.

■ 2D inspection function (solder inspection and component inspection)

Using color CCD camera and its own unique lighting, it executes inspection based on color processing.

- Items of solder inspection: Oozing, blurring, displacement, abnormal shape, bridging
- Items of component inspection: Component presence, misalignment, polarity difference, reversed, foreign object inspection (flying chips etc.)

There are two inspection types; resolution of 9μm can inspect component size of 0402 or more, and resolution of 18μm can inspect component size of 0603 or more.

■ APC (Advanced Process Control) System

APC-FF (Feed Forward)

APC-FF is our unique in-line process control system to improve the quality of mounting; it feedforwards deviation of the mounting position to mounters based on the position data of soldering inspection.

APC-FB (Feed Back)

APC-FB is our unique in-line process control system to improve the quality of mounting; it feedbacks deviation of the mounting position to printers based on the position data of soldering inspection.

APC-MFB (Mounter Feed Back)

APC-MFB is a control system to maintain the quality of mounting; it feedbacks the position data of mounted parts measured with inspection machines (AOI) to mounters after the parts were mounted.

■ Dispense of Pre-bonding adhesives

Quality enhancements can be made by dispense of pre-bonding adhesives to avoid movement of large components during material handling as well as to avoid large components dropping during reflow.

■ Corner Bonding

Panasonic's Patented "Corner Bonding" is a process. Prior to placement of BGA/ CSPs, dispensing of adhesives which do not interfere with the self-alignment effect will mitigate the risk of cracks in the interconnect which is induced by warpage of substrates. Dispensing is performed prior to placement where solder connection and curing of the adhesive is done simultaneously. ^{*1}

Point dispense or straight line drawing dispense is used for the corner bonding. ^{*2}

^{*1} Underfill process requires dispense > cure after reflow requiring 2 cycles of heat.

^{* 2} Advance proof must be necessary.

■ Height Sensor

It controls the placement/dispensing height of the nozzle by measuring the height (warpage) of PCB.

If a measurement result exceeds the acceptable value, a warning is issued prior to placement or dispensing to prevent the occurrence of quality defects.

There are two independent functions; PCB warpage correction (for placement head) and local PCB height correction (for dispensing head)

- PCB warpage correction (for placement head)

Controls the placement height by measuring the height (warpage) of the whole PCB.

- Local PCB height correction (for dispensing head)

Adjusts to the optimal nozzle height by measuring several PCB heights (warps) near the draw dispensing (non-contact dispensing) positions.

3. Specification

3.1 Standard Specifications



Item	Specifications	
Electric source	- Rated voltage - Frequency - Rated capacity - Feeding specification - Peak current value during operation	3-phase, AC 200/ 220 V $\pm$ 10 V, AC 380/ 400/ 420/ 480 V $\pm$ 20 V 50/ 60 Hz 2.8 kVA For the case of AC 290 V or more (380 V or more tap), make sure that the feeding side is in star (Y) connection and the voltage between the PE (protective earth) terminal and each phase is AC 290 V or less. 40 A (Rated voltage: AC 200 V) *Please take this into account when choosing the capacity of the primary power supply AVR (the stabilized power supply), etc. *Please be careful of a voltage drop due to the primary power cable length and the wire diameter.
Pneumatic source	- Supply air pressure - Supply air amount	0.5 MPa ~ 0.8 MPa (Working air pressure: 0.5 MPa ~ 0.505 MPa) 200 L/min (A.N.R.)
Dimensions	- Feeder cart connected: - Tray feeder connected:	W 1 280 × D 2 465 × H 1 444 mm W 1 280 × D 2 570 × H 1 444 mm (without Signal Tower and Touch Panel)
Mass	- Main body - Feeder cart - Single tray feeder - Twin tray feeder - Inspection box - Standard structure mass	2 470 kg 190 kg 200 kg 360 kg 70 kg 2 850 kg (Main body and two feeder carts)
Environment	- Temperature - Humidity - Altitude	10 °C ~ 35 °C (Placement head) 22 °C ~ 28 °C (Dispensing head) 10 °C ~ 28 °C (Inspection head) 25 %RH ~ 75 %RH (No condensation) 1 000 m or less, above sea level
Operating unit	Interactive operation with LCD color touch panels (Standard equipment)	One touch changeover between English, Japanese and Chinese Recognition screen display (Chip/PCB recognition screen is displayed in superimpose screen* with one touch of a button.) Hierarchical operation (Operator/Engineer) * Recognition screen is displayed on operating screen.
Paint color	Standard color	White: W-13 (G50) * The paint color cannot be designated.
Control System	Microcomputer system (VxWORKS)	
Command System	Designation of X, Y, Z and θ coordinates	
Production data	- No. of placement points: - No. of Patterns (Blocks): - No. of Mark settings*:	
Others	- Program Functions - Data creation	

*1 In the dual lane mode production, it is the total of placement points in both front and rear lanes.
 When you choose the option of Extend Mount points, the max mounting point is 50 000 points, and the max pattern is 8 000 patterns.
 If the line is made up with the CM and NPM series coupled, please contact us.

3.2 Standard Functions

Item	Specifications			
	Lightweight 16-nozzle head V3A	12-nozzle head	Lightweight 8-nozzle head	3-nozzle head V2
Placement tact time (Under optimum conditions)	84 000 CPH* ¹ (Chip: 0.043 s/chip) 70 000 CPH* ² (Chip: 0.051 s/chip)	64 500 CPH* ¹ (Chip: 0.056 s/chip) 62 500 CPH* ² (Chip: 0.058 s/chip)	41 600 CPH (Chip: 0.087 s/chip)	16 640 CPH (Chip: 0.217 s/chip) 13 000 CPH (QFP: 0.277 s/QFP)
	IPC9850 (1608C): 61 200 CPH* ¹ 56 000 CPH* ²			
	* This may vary depending on components. *1 When high production mode is "ON." *2 When high production mode is "OFF."			
Placement accuracy (Under optimum conditions)	<u>0402(01005"),</u> <u>0603(0201"), 1005</u> <u>placement</u> ±0.04 mm* ¹ : Cpk ≥ 1	0402 (01005"), 0603 (0201"), 1005 placement ±0.04 mm* ¹ : Cpk ≥ 1 ±0.03 mm* ³ : Cpk ≥ 1	0402 (01005"), 0603 (0201"), 1005 placement ±0.03 mm: Cpk ≥ 1	QFP placement ±0.03 mm: Cpk ≥ 1
	<u>03015*², 0402(01005"),</u> <u>0603(0201"), 1005</u> <u>placement</u> ±0.03 mm* ³ : Cpk ≥ 1		QFP placement ±0.05 mm: Cpk ≥ 1 (12 × 12 mm or less) ±0.03 mm: Cpk ≥ 1 (12 × 12 mm over to 45 × 45 mm or less)	
	±0.025 mm* ⁴ : Cpk ≥ 1			
	* This may vary depending on components. * This data is applicable when the placement angle is 0°, 90°, 180°, or 270°. For the other angles, the data changes. * Sudden ambient temperature changes may affect the accuracy. *1 When high production mode is "ON." *2 When "03015 placement support" is selected. (Panasonic specified requirements) *3 When high production mode is "OFF." *4 When "±0.025 mm placement support" is selected. (Panasonic specified requirements)			

Item	Specifications			
	Lightweight 16-nozzle head V3A	12-nozzle head	Lightweight 8-nozzle head	3-nozzle head V2
Applicable component				
Component dimensions	03015* ¹ chip ~ 8.5 × 8.5 mm (There are pickup limitations on components over 6 × 6 mm)	0402 (01005") chip ~ 12 × 12 mm (There are pickup limitations on components over 6 × 6 mm.)	0402 (01005") chip ~ 45 × 45 mm or 100 × 40 mm* ² (There are pickup limitations on components over 12 × 12 mm.)	0603 (0201") chip ~ 120 × 90 mm or 150 × 25 mm* ^{2*3*4}
	*1 When "03015 placement support" is selected. (Panasonic specified requirements) *2 Component dimensions may be subject to constraints under either of two conditions; the placement of a large-sized connector and the relation between the pickup position and the recognition range. For more information, please contact us. *3 When the short side of component outer dimension is longer than 45 mm, it is split recognition. *4 You can add an option to extend up to 135 mm × 135 mm. For the details, see the optional "Large Heavy Component Mount".			
	Max. 6 mm* ^{1*2}	Max. 6.5 mm* ^{1*2}	Max. 12 mm* ²	Max. 30 mm* ^{3*4}
Component height	*1 When component size is over 3 mm, it is limited to 6.5 mm x 6.5 mm. At mounting of components over 3 mm, short nozzle(101GS, 101GSN, 102GS, 102GSN) is necessary. *2 Applies to components with a pickup depth (the distance between the top surface of an embossed tape and the pickup surface) of 2 mm or less. (Mechanical constraints of tape feeder and nozzles). *3 For component height mounted on the back of PCB, See "Conditions of PCB before placement" in the "7.1 PCB Specifications". *4 You can add an option to extend up to Max. 48 mm(Component height + PCB thickness + Carrier thickness). For the details, see the optional "Tall Component mount".			
Mass	---	---	---	Max. 30 g* ¹
	*1 You can add an option to extend up to Max. 300g. For the details, see "Large Heavy Component Mount".			
Placement load control	Constant load control 1.0 N* ¹	---	---	0.5 N ~ 100 N (In increments of 0.01 N)
	*1 Constant load control is optional.			
Placement Angle	-180° ~ 180° (In increments of 0.01°)			
Recognition	<u>Head camera</u> - Offset of PCB position and orientation by using recognition mark. <u>Multi-recognition camera: Type 1</u> - Recognition and offset of all applicable components. <u>Multi-recognition camera: Type 2 (Type 1 + Component thickness measurement)</u> - Measurement of component thickness (chip data registration, placement height control), detection of standing/tilted standing of components at the time of pickup, nozzle tip check. <u>Multi-recognition camera: Type 3 (Type 2 + 3D-measurement function)</u> - Detects coplanarity(flatness) of all the leads and XY-direction positions in QFP/SOP and other packages. - Detects presence or absence of all the balls, and partially broken balls in its shape in BGA/CSP and other packages.			
PIP lighting (Applicable heads)	3-nozzle head V2			

Item	Specifications
PCB exchange time	
Single conveyor	2.3 s (L 350 mm or less) 4.4 s (L 350 mm over to L 450 mm or less) 5.2 s (L 450 mm over to L 750 mm or less)* ¹ * ¹ It can be 4.4s, with the extension conveyor between equipment but without the backside mounting.
Dual conveyor	- Dual lane mode: 0 s (It cannot be 0 s, when the cycle time is less than PCB exchange time.) - Single lane mode*¹: 2.3 s (L 350 mm or less) 4.4 s (L 350 mm over to L 450 mm or less) 5.2 s (L 450 mm over to L 750 mm or less)*² * ¹ When production is implemented in a single lane mode, the optional PCB support block that supports single lane mode is needed. * ² It can be 4.4s, with the extension conveyor between equipment but without the backside mounting.
Applicable PCB	
Single conveyor	- Dimension 50 × 50 mm ~ 750 × 550 mm - Placement area 50 × 44 mm ~ 750 × 544 mm - Thickness 0.3 mm ~ 8.0 mm - Mass 3.0 kg or less (After mounting, including the carrier mass.) - Flow direction Left → Right, Left ← Right (Selectable) - Reference Front reference, Rear reference (Selectable) * Connecting to NPM-DX/ D3A/ D3/ D2/ D requires a traverser between them. The machine cannot be connected to NPM-TT or NPM.
Dual conveyor	- Dimension Dual lane mode : 50 × 50 mm ~ 750 × 260 mm Single lane mode*¹ : 50 × 50 mm ~ 750 × 510 mm - Placement area Dual lane mode : 50 × 44 mm ~ 750 × 254 mm Single lane mode*¹ : 50 × 44 mm ~ 750 × 504 mm - Thickness 0.3 mm ~ 8.0 mm - Mass 3.0 kg or less (After mounting, including the carrier mass.) - Flow direction Left → Right, Left ← Right (Selectable) - Reference [Dual lane mode]  [Single lane mode*¹]  *¹ When production is implemented in a single lane mode, the optional PCB support block that supports single lane mode is needed. * The rear reference is available when the machine is reversed. (For single lane mode production only) * Connecting to NPM-DX/ D3A/ D3/ D2/ D requires a traverser between them. The machine cannot be connected to NPM-TT or NPM.
PCB transfer height	900 mm ~ 920 mm

Item	Specifications
Component Supply Unit	Taping 4 mm Max. 120 inputs*¹: Thin type tape feeder 8 mm Max. 120 inputs*¹: Double/ Thin type tape feeder (Small reel) Max. 60 inputs*¹ : Double/ Thin type tape feeder (Large reel) 12/ 16 mm Max. 60 inputs*¹ 24/ 32 mm Max. 30 inputs*¹ 44/ 56 mm Max. 20 inputs*¹ 72 mm Max. 14 inputs*¹ : Only Lightweight 8-nozzle head and 3-nozzle head V2 88 mm Max. 12 inputs*¹ : Only 3-nozzle head V2 104 mm Max. 10 inputs*¹ : Only 3-nozzle head V2 ▪ Single stick feeder Max. 30 inputs*¹ : Only Lightweight 8-nozzle head and 3-nozzle head V2 ▪ 3-lot stick feeder Max. 14 inputs*¹ : Only Lightweight 8-nozzle head and 3-nozzle head V2 ▪ Stackable stick feeder (S) *² Max. 8 inputs *¹ : Only Lightweight 8-nozzle head and 3-nozzle head V2 ▪ Stackable stick feeder (L) *² Max. 8 inputs*¹ : Only Lightweight 8-nozzle head and 3-nozzle head ▪ Single tray feeder Max. 20 pieces : Only Lightweight 8-nozzle head and 3-nozzle head V2 ▪ Twin tray feeder Max. 40 pieces : Only Lightweight 8-nozzle head and 3-nozzle head V2 ▪ Auto load feeder Max. 120 inputs*¹: When attachments for auto load feeder are used *¹ When both front and rear units are the feeder carts. *² "Air supply unit for feeder" is necessary.

Item	Specifications	
2D Inspection Head	2D inspection head A	2D inspection head B
Field	44.4 × 37.2 mm (Resolution 18 μm)	21.1 × 17.6 mm (Resolution 9 μm)
Inspection processing time	Solder inspection: 0.35 s/field Component inspection: 0.5 s/field	
	* This varies depending on inspection conditions. The following is the measurement conditions.	
Object for Inspection*	Solder inspection Chip component: 0.1 × 0.15 mm or more (0603 [0201"] or more) Package component: φ0.15 mm or more	Solder inspection Chip component: 0.08 × 0.12 mm or more (0402 [01005"] or more) Package component: φ0.12 mm or more
	Component inspection Square chip (0603 [0201"] or more), SOP, QFP (0.4 mm pitch or more), BGA, CSP, Aluminum electrolytic capacitor, Volume, Trimmer, Coil, Connector, Network resistor, Transistor, Diode, Inductor, Tantalum capacitor, Cylindrical chip	Component inspection Square chip (0402 [01005"] or more), SOP, QFP (0.3 mm pitch or more), BGA, CSP, Aluminum electrolytic capacitor, Volume, Trimmer, Coil, Connector, Network resistor, Transistor, Diode, Inductor, Tantalum capacitor, Cylindrical chip
Items of Inspection	Solder inspection: Oozing, blurring, displacement, abnormal shape, bridging Component inspection: Component presence, misalignment, reversed, polarity difference, foreign material inspection	
The number of inspection	Solder inspection: Solder points: Max. 30 000 points/machine (Component points: Max. 10 000 points/machine) Component inspection: Component points: Max. 10 000 points/machine	
Inspection accuracy (Under optimum conditions)	±0.02 mm: Cpk≥1.0	±0.01 mm: Cpk≥1.0
	* This is the solder position inspection accuracy measured with our reference using our glass PCB for plane calibration. It may also be affected by sudden change of ambient temperature.	

* 03015R are not eligible.

Dispensing Head	Dot dispense	Draw dispense
Dispensing tact time* ¹	0.16 s/dot • XY movement: within 10 mm • Without θ rotation • Blow-off time: within 20 ms • Without trial dispensing • During continuous operation under optimum conditions	4.25 s/part* ² • Drawing size: within 30 × 30 mm • 10mm long L-shape corner dispensing • Without trial dispensing • Under optimum conditions
Dispensing Accuracy* ¹	±0.075 mm: Cpk ≥ 1.0 • Dispensing for 1608 at the condition of φ0.7 ± 0.1 mm • Under optimum conditions	±0.1 mm: Cpk ≥ 1.0 • Dispensing for BGA at the condition of 30 × 30 mm shape • Under optimum conditions
	*1 The values such as tact time and accuracy are varied depending on conditions (e.g. adhesive). *2 PCB height measurement time (0.5 s) is included. (30 × 30 mm, with 4-point measurement)	
No. of nozzles loaded	Max. 2 types	
Applicable Components	1608 chip to SOP, PLCC, QFP, Connector, BGA and CSP	BGA and CSP
Supply vessel (barrel)	30 mL (general: PS30S manufactured by Iwashita engineering, Inc.) * Syringe of HDP series cannot use.	
The Number of dispensing	Max. 10 000 points/machine	

3.3 Placement mode

■ Single lane

	Share mode
Pattern	
Motion	Heads move in an alternating pattern during production.

■ Dual lane

Dual lane allows for 3 different placement modes with the movement of the front and rear heads.


	Share mode	Share mode (front/rear)* ¹	Independent mode* ¹
Pattern			
Motion	Each head works on boards in both lanes. The heads, moving alternately, handle boards in one lane once completing production in the other lane.	< Share mode (front) > The front and rear heads are used to handle boards in the front lane while those in the rear lane just pass through. < Share mode (rear) > The front and rear heads are used to handle boards in the rear lane while those in the front lane just pass through.	Each head independently handles production boards in each lane. Front head: handling front lane Rear head: handling rear lane
Feature	PCB transport losses are minimized.	Production can be initiated or stopped according to lane.	Production can be initiated or stopped according to lane. The elimination of the heads' standby time (waiting for the opposed head's movement) associated with their alternating movement contributes to increased productivity.* * Some PCB board sizes bring the heads into a standby state.
Changeover	Changeover can be conducted in each lane after stopping the machine.	Changeover (production data change, feeder cart replacement, and tray magazine replacement) can be conducted in a suspended lane while boards are passing through the other lane.* ²	Changeover (production data change, feeder cart replacement) can be conducted in a suspended lane while producing boards in the opposite lane. * ²

*¹ Independent mode and Share mode (front/rear) are available for placement head specifications only.

*² It is not possible to do works by opening safety covers (such as manual replacement of support pins). The "independent changeover support unit (option)" is necessary for feeder cart exchange.


The combination of placement modes allows NPM-W2 to respond to the needs of your various production patterns.

■ Large size PCB mounting line Share mode (Single lane)




- Specifically designed for large size boards that cannot make use of dual transport.

■ High-efficiency mounting line Share mode



- Minimizes board transport losses.
- Realizes highly efficient production through the smallest number of feeder locations.


■ Fastest mounting line Independent mode



- Realizes the fastest placement of PCBs of a pattern at the fastest rate.

■ Non-stop changeover line

Independent mode




- You can keep producing in one lane while conducting a changeover in the other lane.* (Independent changeover)

* It is not possible to do works by opening safety covers (such as manual replacement of support pins).


* The "independent changeover support unit (option)" is necessary for feeder cart exchange.

Independent mode plus Share mode (front/ rear)



■ High-speed/High-efficiency mounting line


Independent mode plus Share mode



- Line configuration that utilizes the merits of Independent and Alternate modes.
- Chip parts can be mounted faster, and atypical or tray components, more efficiently.

■ Imbalanced mounting line

Independent mode plus Share mode (front/ rear)










- You may configure the mounting line shown in the left figure if unable to achieve a production balance between the front and rear lanes.

e.g.) Board A: 300 placement points (chip parts only)
Board B: 600 placement points (chip parts plus atypical components)

3.4 Description of Inspections

■ Items of inspection

Inspection kind*1		Detected defect	Inspection method	OK	NG
Solder inspection	Oozing 	Solder is oozing out (too much)	Solder area is measured, and it is good if the margin of error is within tolerance value against mask design area.		
	Blurring 	Solder is blurring (too less)			
	Displacement 	Solder position is displaced.			
	Abnormal shape 	Solder shape differs from the setting.	Solder outer shape is measured and it is good if the margin of error is within tolerance against mask design value.		
	Bridging 	Bridging occurs.	Search frame is created close to the target solder. It is good if the solder is not present to the length on the frame exceeding the tolerance value.		
Component inspection	Missing 	There are no components in the placement position.	It is good, if there is no PCB color or if there is a component color.		
	Shift 	- The placement position of the component shifts. - The placement angle of the component shifts.	Positions of terminals or components are measured. It is good if the shift amount is within the set value.		
	Flipping 	- The placement components flip. - The placement components turn sideways.	It is defective if there are colors of the back and side of the component.		
	Polarity 	The direction of the placement component is wrong. (Applicable: components with polarity)	It is good if there are the colors of polarity.		
	Foreign object *2 	- There are falling components under the components that try to be placed. - There are foreign objects under the components that try to be placed. (The side of placement of the components (related components *2) placed by NPM with the inspection Head installed is inspected.) - Foreign objects before the shields are placed are inspected. - Foreign objects before the BGAs are placed are inspected.	It is good if there are no colors other than PCB color.		

*1 The color or inspection area for each inspection is set using previously obtained images.

For the color of PCB, colors of solder, land, silk or others are set in advance.

*2 Lower limit of foreign objects that can be detected

2D inspection head A (Resolution: 18 μm): over thickness of 0603 (0.2 mm)

2D inspection head B (Resolution: 9 μm): over thickness of 0402 (0.15 mm)

■ Object for Inspection

• Items of solder inspection object

Solder shape	2D inspection head A (Resolution: 18 μm)	2D inspection head B (Resolution: 9 μm)
	φ0.15 mm or more	φ0.12 mm or more
	0.1 × 0.15 mm or more	0.08 × 0.12 mm or more

* As solder is the mixture of solder ball and flux, surface condition is not always even depending on content rate of flux or composition of metal. Therefore, difference of color or brightness may not exist between solder and land. Also, color or brightness might vary due to material of PCB or component, or wave or deformation of PCB. In such cases, inspection might not be executed. In order to operate the optical system normally, please avoid setting it in a place where exposed to direct sunlight or near a strong light.

■ Object for Inspection

• Items of component inspection object

Representative kind of applicable components for inspection	Shape	Inspection kind				
		Missing	Shift	Flipping	Polarity	
Square chip resistor		○	○	○*1		
Square chip capacitor						
Cylindrical chip						
Tantalum capacitor				○*2		
Aluminum electrolytic capacitor						
Volume						
Trimmer						
Coil						
Connector				○*2		
Network resistor						
Transistor						
Diode						
Inductor						
SOP						
QFP						
BGA/CSP						

* As for the placed components, if their colors are missing by being shaded by their adjacent ones, the inspection processes may not be possible. And If there are no difference of color and brightness between the PCB and the components (or the printed solder), if there are color and brightness change by the material of PCB and components, or the undulating and transforming of the PCB, the inspection processes may not be possible.

Similarly to solder inspection, please do not install it where direct sunshine strikes or near a strong lighting.

*1 As for such a square chip resistor as has different colors on its front and back, the flipping inspection can be set.

*2 Not only the contrast of the polarity mark is clear, the polarity marks shall not be contaminated and blurred. In addition, variations in color and brightness shall be minimum. As for ICs, the polarity shapes shall be identifiable on the image and they shall not be subject to change. These are the conditions to carry out normal inspection.

■ Inspection time


• Standard case examples of solder inspection tact time

[Accuracy priority mode]

Unless all solder inspections are complete, it does not allow proceeding to placement operation.

This is advantageous operation mode for accuracy as the opposed axis is stopped.


It takes approximately 0.35 sec. to move and capture image.



[Tact priority mode]

Solder inspection and placement operations are executed alternately. This operation mode is advantageous for tact time.

It takes approximately 0.35 sec. to move and capture image.




* In case of solder inspection for components such as 0402 which requires accuracy, please use "Accuracy priority mode."

• Standard case example of component inspection tact time

It is possible to inspect multiple visual fields in single turn. It takes approximately 0.35 sec. to move and capture image.




When inspection time such as foreign object inspection is longer than component pickup and recognition time, placement operation is executed after the inspection completes with results.

In the last turn, only inspection is operated.



3.5 Dispense Capability

■ Dispense Applications/Types

(1) Avoiding movement of large components during material handling	(2) Avoid fall-off of bottom side components during reflow.	(3) Reinforcements for BGA, CSPs*
 Adhesive	 Adhesive	 * Advance proof must be necessary. Adhesive

■ Applicable components and dispense size examples

(Content may vary depending on adhesive manufacturer and model number. Please change volume per your shear force requirements)

Component	Appearance	Dimensions*1 (mm)			Nozzle VS = 1 point Dispense S = 2 point dispense L = 4 point dispense	Dot Size*2 (mm)
		X	Y	T		
1608R, C		1.6	0.8	0.4 ~ 0.8	S or VS × 2 (for 1608)	φ0.6 ~ φ0.7
2012R, C		2.0	1.25	0.4 ~ 0.8	S	φ0.65 ~ φ0.75
3216R, C		3.2	1.6	0.4 ~ 0.8		φ0.7 ~ φ0.8
Mini Mold Tr		2.8	2.8	1.1	S × 2	φ0.8
Mini Power Tr		4.3	4.5	1.5		φ0.85
Cylindrical Component		2.0	φ1.0	—	S (0° or 90°)	φ0.8
		3.6	φ1.4	—		φ1.0
Tantalum Capacitor Y		3.2	1.6	1.6	S	φ0.8
Tantalum Capacitor X		3.5	2.8	1.9		φ1.0
Tantalum Capacitor C		6.0	3.2	2.5	L	φ1.2
Tantalum Capacitor D		7.3	4.3	2.8		
Aluminum Electrolytic Capacitor S		4.3	4.3	5.4		φ0.8
Aluminum Electrolytic Capacitor L		6.6	6.6	5.4		φ1.2
Trimmer Potentiometer		4.5	3.8	1.5		
Trimmer Potentiometer (Center Opening)		3.7	3.1	2.0		
Trimmer Potentiometer (Tapered Opening)		4.8	4.0	3.0		
Trimmer Capacitor (Flat Upper Surface)		4.5	4.0	2.6		
Trimmer Capacitor		4.5	4.0	2.6		
IFT Coil		5.8	5.8	4.2		
Film Capacitor		4.8	3.3	1.4		
Light-Touch Switch		6.2	6.2	2.0		

Component	Appearance	Dimensions* ¹ (mm)			Nozzle L = 4 point dispense	Dot Size* ² (mm)
		X	Y	T		
SOP 8 P		5.0	4.2	1.5	L	φ1.4
SOP 16 P		10.1	4.2	1.5	L × 2	
SOP 28 P		21.25	9.5	2.0	L × 3	
QFP 7 × 7		7.0	7.0	2.5	L	
QFP 14 × 14		14.0	14.0	2.8	L × 3	
QFP 18 × 18		18.0	18.0	3.3	L × 4	
BGA, CSP		33.0	33.0	2.15	Drawing nozzle* ³	Line width 1.0

*1 Component dimensions above are given for reference purposes only.

Be sure to check dimensions and shapes of all components, which may differ per manufacturer.

*2 Specifications of some components may differ from those listed above.

*3 Advance proof must be necessary.


■ Dispense Time (Dot dispense and draw dispense*¹)

• Standard case examples of dispensing tact time

[Accuracy priority mode]*²

Operation moves to the placement process after all dispensing actions are finished.

This is advantageous operation mode for accuracy as the opposed axis is stopped.



*¹ For drawing dispense (non-contact dispense), the height sensor (option) is required.


*² When correction is performed by the height sensor (option), only the accuracy priority mode is available.

*³ For drawing dispense (non-contact dispense), the PCB height measurement time (approx. 0.5 s) is included.

[Tact priority mode]


Dispensing and placement operations are executed alternately.

This operation mode is advantageous for tact time.



* Demonstration is necessary for possible placement misalignment to be introduced depending on the placed component.

4. Machine Configuration



Rear side Front side	Placement head	Dispensing head	No head
	Placement head	Dispensing head	No head
Placement head	NM-EJM7D	NM-EJM7D-MD	NM-EJM7D
Dispensing head	NM-EJM7D-MD		NM-EJM7D-D
Inspection head	NM-EJM7D-MA		NM-EJM7D-A
No head	NM-EJM7D	NM-EJM7D-D	


Model numbers are different depending on the location of where each Head is configured.

■ Placement specification

• Feeder cart specification (tray feeder cannot be installed on the rear side)

Head: Front/ Rear side


- Lightweight 16-nozzle head 3A
- 12-nozzle head
- Lightweight 8-nozzle head
- 3-nozzle head V2
- No head*1



• Tray feeder specification (feeder cart cannot be installed on the rear side)

Single tray feeder specification

Twin tray feeder specification



*1 For "No head", both front and rear cannot be selected together.

*2 It is option for the dual conveyor specification. (It cannot select the rear side only.)
Please refer to "9. Options: Independent changeover support unit" for details.

*3 The safety cover is not required when "Feeder cart" is attached.

■ Data creation


All data are created on NPM-DGS, the data creation system. (NPM-DGS is a separate product.)
The hardware for NPM-DGS should be prepared by yourself.

** Remarks **

- The special specifications may potentially not comply with the CE mark specifications.
- The floor slope in the feeder cart installation area needs to be 6 mm or less in the right/left direction and 11 mm or less in the forward/backward direction. If the floor slope is beyond the above limit, the feeder cart cannot be taken in and out.


■ Inspection specification

- **Feeder cart specification** (tray feeder cannot be installed on the rear side)




- **Tray feeder specification** (feeder cart cannot be installed on the rear side)

Single tray feeder specification



Twin tray feeder specification



- *1 Inspection head can be selected for front side only.
One inspection head cannot handle solder inspection and component inspection at the same time.
- * In case of solder inspection, set it at the upmost stream of NPM-W2 line.
- * Please consult us separately for replacement of inspection head after delivery.

■ Data creation


All data are created on NPM-DGS, the data creation system. (NPM-DGS is a separate product.)
The hardware for NPM-DGS should be prepared by yourself.

** Remarks **


- The special specifications may potentially not comply with the CE mark specifications.
- The floor slope in the feeder cart installation area needs to be 6 mm or less in the right/left direction and 11 mm or less in the forward/backward direction. If the floor slope is beyond the above limit, the feeder cart cannot be taken in and out.

■ Dispense specification

• Feeder cart specification (tray feeder cannot be installed on the rear side)



• Tray feeder specification (feeder cart cannot be installed on the rear side)



*¹ For Dispensing head, both front and rear cannot be selected together.

*² For "No head", both front and rear cannot be selected together.

*³ It is option for the dual conveyor specification. (It cannot select the rear side only.) Please refer to "9. Options: Independent changeover support unit" for details.

*⁴ The safety cover is not required when "Feeder cart" is attached.

* Only a single dispensing head can be selected per line.

If you have to select 2 or more dispensing heads for a line, consult us, separately.

* Please set at the upmost stream of NPM-W2 line when executing dot dispensing.

* For dot dispensing, it is recommended to place components after dispensing (configurable by NPM-DGS).

■ Data creation

All data are created on NPM-DGS, the data creation system. (NPM-DGS is a separate product.)





The hardware for NPM-DGS should be prepared by yourself.

** Remarks **

- The special specifications may potentially not comply with the CE mark specifications.
- The floor slope in the feeder cart installation area needs to be 6 mm or less in the right/left direction and 11 mm or less in the forward/backward direction. If the floor slope is beyond the above limit, the feeder cart cannot be taken in and out.

4.1 Head Configuration



■ Placement head

Lightweight 16-nozzle head V3A		12-nozzle head	
 Motor for vertical motion (Z-axis) (Inside the cover) Motor for rotary motion (θ-axis)		 Motor for vertical motion (Z-axis) (Inside the cover) Motor for rotary motion (θ-axis)	
Accessories	Nozzle changer (For 16-/ 12-nozzle head) • Nozzle changer Expansion type (For 16-/ 12- nozzle head) *Either of the above accessories included.	Accessories	Nozzle changer (For 16-/ 12-nozzle head) • Nozzle changer Expansion type (For 16-/ 12- nozzle head) *Either of the above accessories included.
Lightweight 8-nozzle head *1		3-nozzle head V2	
 Motor for vertical motion (Z-axis) (Inside the cover) Motor for rotary motion (θ-axis)		 Motor for vertical motion (Z-axis) (Inside the cover) Motor for rotary motion (θ-axis)	
Accessories	• Nozzle changer (For 8-nozzle head) • Nozzle changer (Large type) (For 8-nozzle head) *One of the above nozzle changers comes with the 8-nozzle head (Lightweight type).	Accessories	• Nozzle changer (For 3-nozzle head) • Nozzle changer/Shield nozzle ready (For 3-nozzle head) *Either of the above accessories included.

* Nozzle changer is compatible with NPM series heads and NPM-X series heads.

*1 Lightweight 8-nozzle head nozzle holder is a dedicated holder.

■ **Process head**

2D inspection head (A/ B)		Dispensing head	
A: Resolution 18 μm B: Resolution 9 μm  CCD camera (Inside the cover) LED lighting (Inside the cover)		 Motor for vertical motion (Z-axis) Motor for rotary motion (θ, SC-axis)	
Accessories	Inspection head support unit (Inspection BOX, Calibration jig)	Accessories	• Dummy dispensing unit • Wiping station
Please be sure to select the safety cover.		Please be sure to select the safety cover. (Not required when Feeder cart is attached.)	

**** Remarks ****

• The above accessories do not come together with spare head. When you select spare head, be sure to select options according to each head as well. Please refer to “9. Options” for details.

4.2 Nozzle Configuration

All nozzles are available as options so that you will be able to select an optimal combination that suits your production style.

- All the shapes of holes shown here are maximized. Therefore the actual shapes are different.
- The tips of nozzles which include "C" in their No. are made from the ceramic.
- Nozzle No. including "N"
is nozzles that 2D code is on their nozzle flange and that are for NPM series and NPM-X series only.
Wrong nozzle setup can be detected by verification of nozzle No. for the nozzles with the code.
- The nozzles which do not include "N" in their No. are common with CM series (CM602, CM402, CM401, CM400, DT401, CM232, CM212, and CM101).
- The recognition method depends on components.


■ Nozzles for Lightweight 16-nozzle head V3A and 12-nozzle head

No.	Shape (Unit: mm)	Applicable component (Typical examples)	No.	Shape (Unit: mm)	Applicable component (Typical examples)
276CS 276CSN	 Exclusive to Lightweight 16-nozzle head	03015R	230CS 230CSN	 Exclusive to Lightweight 16-nozzle head	1005R/C (0402" R/C) 1608R/C (0603" R/C)
256CS 256CSN	 Exclusive to Lightweight 16-nozzle head	0402R/C (01005" R/C)	235CS 235CSN	 Exclusive to Lightweight 16-nozzle head	1608R/C (0603" R/C) 2012R/C 3216R/C SS-Mini Tr/Di S-Mini Tr/Di
225CS 225CSN	 Exclusive to Lightweight 16-nozzle head	0603R/C (0201" R/C)	240CS 240CSN	 Exclusive to Lightweight 16-nozzle head	3216R/C 4532R/C TAN-X
226CS 226CSN	 Exclusive to Lightweight 16-nozzle head	0603R/C (0201" R/C) 1005R/C (0402" R/C)	140S 140SN	 Exclusive to Lightweight 16-nozzle head	Al electrolysis SOP
101GS 101GSN *1	 Exclusive to Lightweight 16-nozzle head	Inductor 4532R/C 5848R/C Al electrolysis	102GS 102GSN *1	 Exclusive to Lightweight 16-nozzle head	Inductor 4532R/C 5848R/C Al electrolysis


*1 101GS/GSN and 102GS/GSN are for Lightweight 16-nozzle head and are short nozzles.

When you use a short nozzle, there are restrictions, including the following (1) to (7). For the details, see the Chapter, Options.

- (1) Measurement by nozzle recognition is not available, Unable to check for deposits.
- (2) Pickup on concave surface is not allowed
- (3) Short nozzle length is fixed to 11.3 mm
- (4) Pressing force is ≤ 0.3 mm when components are picked up.
- (5) Transmission recognition does not work(Transmission recognition components are not available)
- (6) LCR checker does not work.
- (7) It is not compatible with Lightweight 16-nozzle head constant load control (License).



■ Nozzle layout for Lightweight 16-nozzle head V3A



The layout and the maximum number of attachable nozzles for Lightweight 16-nozzle head V3A (The figures are seen from above.)

- * Standard Lightweight 16-nozzle head V3A nozzles are 10 types described in the previous page.
You can also use NPM series, NPM-X series 16/ 12 nozzle head nozzle or CM series 12-nozzle head nozzle.
- * You cannot use NPM series, NPM-X series Lightweight 8/ 8 nozzle head nozzle or CM series 8-nozzle head nozzle.
- * Nozzles for AM100 cannot be used.

■ Pickup-ready component size and nozzle arrangement


Component size(A) that Lightweight 16-nozzle head V3A can pick up is as follows.

(●: Can pick up, ○: Cannot pick up)

Component size compatible with pickup at transparent recognition is limited to 6 × 6 mm or smaller.

Components of 6 × 6 mm or less


($A \times A \leq 6 \times 6$)




6 × 6 mm ~ 8.5 × 8.5 mm

($6 \times 6 < A \times A \leq 8.5 \times 8.5$)

- Vacuums up to eight components of larger than 6 x 6 mm in a same turn and there are two staggered arrangements as below.
- Nozzles next to a nozzle vacuuming components of larger than 6 x 6 mm can vacuum components of 3 x 3 mm or smaller.




3 x 3 mm or smaller Larger than 6 x 6 mm




Larger than 6 x 6 mm 3 x 3 mm or smaller

(e.g.) When ③, ⑩ or ⑫ nozzle vacuums components over 6 x 6 mm as below, neighbouring ②④⑨⑪⑬ nozzles can vacuum components of 3 x 3 mm or smaller. Other nozzles can vacuum components of 6 x 6 mm or smaller.



3 x 3 mm or smaller Larger than 6 x 6 mm 6 x 6 mm or smaller

■ Nozzle layout for 12-nozzle head



The layout and the maximum number of attachable nozzles for 12-nozzle head
(The figures are seen from above.)

* Standard 12-nozzle head nozzles are 11 types described in the previous page.

You can also use NPM series, NPM-X series 16/ 12 nozzle head nozzle or CM series 12-nozzle head nozzle.

* You cannot use NPM series, NPM-X series Lightweight 8/ 8 nozzle head nozzle or CM series 8-nozzle head nozzle.


* Nozzles for AM100 cannot be used.

■ Pickup-ready component size and nozzle arrangement


The sizes of components that 12-nozzle head can pick up are as follows.

(●: Can pick up, ○: Cannot pick up)

Components of 6×6 mm or less



(Reflecting recognition only)
Exceeding 6×6 mm ~ 12×12 mm
($6 \times 6 < A \times A \leq 12 \times 12$)




■ Nozzles for Lightweight 8-nozzle head

No.	Shape (Unit: mm)	Applicable component (Typical examples)	No.	Shape (Unit: mm)	Applicable component (Typical examples)
256C 256CN		0402R/C (01005" R/C)	240C 240CN		3216R/C 4532R/C TAN-X/B/C/D Al Electrolytic -A/B/C
225C 225CN		0603R/C (0201" R/C)	140 140N		TAN-D Al Electrolytic-D SOP, SOJ PLCC, CSP
226C 226CN		0603R/C (0201" R/C) 1005R/C (0402" R/C)	185 185N		SOP, QFP PLCC, BGA } 18 × 18 mm
230C 230CN		1005R/C (0402" R/C) 1608R/C (0603" R/C)	199 199N		SOP, QFP PLCC, BGA } 32 × 32 mm
235C 235CN		1608R/C (0603" R/C) 2012R/C 3216R/C SS-Mini Tr/Di S-Mini Tr/Di			

■ Nozzle layout for Lightweight 8-nozzle head

Small nozzles (all nozzles listed in the above chart) which support within □12mm components can be attached to all positions.



The layout and the maximum number of attachable nozzles for Lightweight 8-nozzle head
(The figures are seen from above.)

* Standard Lightweight 8-nozzle head nozzles are the above 9 types.

You can also use NPM series, NPM-X series 8-nozzle head nozzle or CM series 8-nozzle head nozzle.
(#450 nozzle and #460 nozzle cannot be used.)

* You cannot use NPM series, NPM-X series Lightweight 16/ 16/ 12 nozzle head nozzle.

* Nozzles for AM100 cannot be used.

■ Pickup-ready component size and nozzle arrangement


The sizes of components that Lightweight 8-nozzle head can pick up are as follows.

(●: Can pick up, ○: Cannot pick up)

Pickup-ready component size for transmission recognition is 12×12 mm or less.


Components of 12×12 mm or less

($A \times A \leq 12 \times 12$)




Exceeding 12×12 mm ~ 18×18 mm

($12 \times 12 < A \times A \leq 18 \times 18$)



Exceeding 18×18 mm ~ 24×24 mm


($18 \times 18 < A \times A \leq 24 \times 24$)



(5) and (7) can be picked up a component of less than 12×12 mm


Exceeding 24×24 mm to 28×28 mm

($24 \times 24 < A \times A \leq 28 \times 28$)



Exceeding 28×28 mm to 45×45 mm or 45×100 mm








($28 \times 28 < A \times A \leq 45 \times 45$)



Component dimension is up to 12×12 mm at (4) and (8).


■ Nozzles for 3-nozzle head V2

The special nozzles can support the components whose vacuum pick up surface's shape is special such as irregular shaped chips. For details, please consult us.

No.	Shape (Unit: mm)	Applicable component (Typical examples)	Max. component mass	No.	Shape (Unit: mm)	Applicable component (Typical ex- amples)	Max. component mass
1582 1582N		0603R/C (0201" R/C)	0.007 g	1004 1004N		SOP, SOJ QFP, PLCC BGA	23.4 g
1001 1001N		1005R/C (0402" R/C) 1608R/C (0603" R/C) 2012R/C (0805" R/C) SS-Mini Tr/Di S-Mini Tr/Di Mini Tr/Di	0.021 g	1005 1005N		SOJ QFP, PLCC BGA	36.6 g
1002 1002N		3216R/C (1206" R/C) 4532R/C (1812" R/C) TAN-X/B/C/D Al electroly- sis- A/B/C	0.192 g	1006 1006N		This is a nozzle (reflector) to be at- tached to the head that will not pick up owing to the combination of pick up components. That will enhance the stability of recog- nition for the head that picks up. * For the details, see Pickup-ready component size and nozzle arrangement.	
1003 1003N		Al electroly- sis- D/E/F SOP, SOJ PLCC BGA, CSP	0.768 g				

* From a productivity viewpoint, we recommend that 0603 chip mounting be with Lightweight 16-nozzle head V3A, 12-nozzle head or Lightweight 8-nozzle head.

■ Nozzle layout for 3-nozzle head V2









The layout and the maximum number of attachable nozzles for 3-nozzle head V2
(The figures are seen from above.)

* Nozzles for AM100 cannot be used.

■ Nozzles for 3-nozzle head V2(For odd-shaped components)




* The product number should be used for order placements.



Nozzle No.	1551 / 1551N	1479 / 1479N	2405 / 2405N
Product number	KXFX05J7A00 N610127747AA (With 2D code)	KXFX05ASA00 N610117226AA (With 2D code)	KXFX05BVA00 N610117223AA (With 2D code)
Shape (Unit: mm)			
Max. component mass	0.12 g	3.5 g	1.5 g
Max. component height	30 mm	27.5 mm	30 mm
Remarks	Nozzle length: 22.5 mm	With a urethane rubber Nozzle length: 27.5 mm	With a urethane rubber Nozzle length: 22.5 mm

Nozzle No.	1404 / 1404N	1421 / 1421N	2467 / 2467N
Product number	KXFX0558A00 N610117224AA (With 2D code)	KXFX056AA00 N610117225AA (With 2D code)	KXFX05F9A00 N610128174AA (With 2D code)
Shape (Unit: mm)			
Max. component mass	3.0 g	8.0 g	2.5 g
Max. component height	30 mm	30 mm	30 mm
Remarks	With a urethane rubber Nozzle length: 22.5 mm	With a urethane rubber Nozzle length: 22.5 mm	With a urethane rubber Nozzle length: 22.5 mm

■ **Nozzles for 3-nozzle head V2(For odd-shaped components)**



* The product number should be used for order placements.

Nozzle No.	1115 / 1115N	2418 / 2418N	1424 / 1424N
Product number	KXFX04PJA00 N610117221AA (With 2D code)	KXFX05CMA00 N610117211AA (With 2D code)	KXFX056PA00 N610127619AA (With 2D code)
Shape (Unit: mm)			
Max. component mass	2.0 g	6.5 g	4.8 g
Max. component height	30 mm	30 mm	30 mm
Remarks	Nozzle length: 22.5 mm	With a urethane rubber Nozzle length: 22.5 mm	With NBR pad Nozzle length: 22.5 mm

Nozzle No.	1427 / 1427N	2421 / 2421N
Product number	KXFX0570A00 N610127623AA (With 2D code)	KXFX05CTA00 N610117212AA (With 2D code)
Shape (Unit: mm)		
Max. component mass	9.7 g	14.5 g
Max. component height	30 mm	30 mm
Remarks	With NBR pad Nozzle length: 22.5 mm	With NBR pad Nozzle length: 22.5 mm


■ Nozzles for 3-nozzle head V2(For odd-shaped components)

* The product number should be used for order placements.

Nozzle No.	3451 / 3451N	6617 / 6617N
Product number	MTKU001354AB MTKU003487AA(With 2D code)	MTKU005517AA MTKU005446AA(With 2D code)
Shape (Unit: mm)		
Max. component mass	80 g	300 g
Max. component height	30 mm	27 mm
Remarks	With NBR pad Nozzle length: 22.5 mm (+Pad allowance : 0.3 mm)	With NBR pad Nozzle length: 25.5 mm (+Pad allowance : 0.5 mm)

■ Correspondence between the pickup depth of electronic component and the nozzle length

The necessary nozzle length varies according to the pickup depth (distance from top of embossed tape to pickup surface) of electronic component to be placed.



Pickup depth B	0 mm to below 3 mm	3 mm to below 8 mm	8 mm to below 13 mm
Nozzle length A	22.5 mm	27.5 mm	32.5 mm


* The list above is limited to at 3 nozzle head V2.

■ Pickup-ready component size and nozzle arrangement


The sizes of components that 3-nozzle head V2 can pick up are as follows.

(●: Can pick up, ○: Cannot pick up)

- Component of diagonal 41 mm (29 × 29 mm)^{*1} or less and Length (L) is 35 mm or less.
- Component of 47 mm (33 × 33 mm)^{*1} or less, L is 38 mm or less and $t \leq 18.5$ mm.




- Component of diagonal 76 mm (54 × 54 mm)^{*1} or less and L is 65 mm or less.



#1006 nozzle (reflector)^{*2}

- Component of diagonal 152.1 mm or less, and L is 150mm or less and W is 90 mm or less.
- Components over 90 mm × 90 mm ~ 135 mm × 135 mm^{*3}



#1006 nozzle (reflector)^{*4}

^{*1} The numerical value inside () is an example of L=W. Component dimensions are subject to constraints if the pickup position is offset from the center of a component. For details, please contact us.

^{*2} At transparent recognition, when component diagonal size at NP1/NP3 is over 50 mm, attach #1006 nozzle(reflector) at NP2.

^{*3} It is optional. For the details, see "Large Heavy Component Mount".



^{*4} At transparent recognition, when component diagonal size at NP2 is over 50 mm, attach #1006 nozzle(reflector) at NP1 and NP3.

4.3 Dispense Nozzle Configuration




Mainly three types of nozzles are prepared based on the component.

Nozzles are for intended for use on NPM series only. Please consult with Panasonic for special nozzles.

■ Dispense Nozzle

Nozzle Type	1 point nozzle (VS)	
Nozzle No.	7030*	7001*
Product number	N610107177AA	N610105001AA
Shape (Unit: mm)		
Dot size	φ0.6 mm ~ φ1.0 mm	φ0.7 mm ~ φ1.1 mm
Applicable components	1608, Dispense near railing	1608, Dispense near railing

A: Outer Diameter
B: Inner Diameter

Nozzle Type	2 point nozzle (S)		
Nozzle No.	7201	7204*	7236*
Product number	N610105003AA	N610104651AA	N610107179AA
Shape (Unit: mm)			
Dot size	φ0.6 mm ~ φ1.0 mm	φ0.7 mm ~ φ1.1 mm	φ0.7 mm ~ φ1.1 mm
Applicable components	1608 ~ 3216	1608 ~ 3216	2125 ~ 3216

* Advance proof may be necessary. Please ask us for details.

Dispense Nozzle




Nozzle Type	2 point nozzle (S)		
Nozzle No.	7222*	7223*	7224*
Product number	N610107149AA	N610107150AA	N610107151AA
Shape (Unit: mm)			
Dot size	$\phi 0.7 \text{ mm} \sim \phi 1.1 \text{ mm}$	$\phi 0.7 \text{ mm} \sim \phi 1.1 \text{ mm}$	$\phi 0.7 \text{ mm} \sim \phi 1.1 \text{ mm}$
Applicable components	2125 ~ 3216	3216 ~ 4 × 4 mm	2 × 2 mm ~ 4 × 4 mm


Nozzle Type	4 point nozzle (L)	
Nozzle No.	7606*	7601
Product number	N610107148AA	N610105004AA
Shape (Unit: mm)		
Dot size	$\phi 0.8 \text{ mm} \sim \phi 1.2 \text{ mm}$	$\phi 0.8 \text{ mm} \sim \phi 1.2 \text{ mm}$
Applicable components	Large Components	Large Components

A: Outer Diameter
B: Inner Diameter

* Advance proof may be necessary. Please ask us for details.

■ Drawing Nozzle (Custom specification)*

Nozzle Type	Drawing nozzle (1 point)		
Nozzle No.	7023	7021	7026
Product number	N610107153AA	N610107145AA	N610107161AA
Shape (Unit: mm)			
Line width	0.4 mm ~ 0.8 mm	0.6 mm ~ 1.0 mm	0.7 mm ~ 1.1 mm
Applicable components	BGA, CSP corner dispensing	BGA, CSP corner dispensing	BGA, CSP corner dispensing

Nozzle Type	Drawing nozzle (1 point)
Nozzle No.	7015
Product number	N610104668AA
Shape (Unit: mm)	
Line width	0.8 mm ~ 1.2 mm
Applicable components	BGA, CSP corner dispensing

A: Outer Diameter
B: Inner Diameter

* The above drawing nozzle is an example.

For the drawing nozzle, individual discussion is required according to dispensing materials and shapes. Please ask us for details.
For drawing dispense (non-contact dispense), the height sensor (option) is required.

■ Dispensing area limitations

Areas not available for dispense (From PCB edge, measured from far end, Y axis)



Orientation	0°	-90°	90°
1 point nozzle Drawing nozzle *1	4.9 mm	5.65 mm	4.1 mm
2 point nozzle	4.9 mm (some at 5.4 mm)	5.65 mm	5.65 mm
4 point nozzle	4.9 mm	5.9 mm	5.9 mm

(Note) The front side stopper is inverted, and above figures for -90° and 90° should be inverted.





*1 The drawing nozzle is identical with "0°" of 1 point nozzle.

1) 1 point nozzle/ Drawing nozzle *1



(Unit: mm)



2) 2 point nozzle



3) 4 point nozzle



* KOZ : Keep Out Zone – Area not possible for dispense

* Above Dispense KOZ is when the correction with recognition as well as the nozzle offset is "0"

* KOZ may increase with correction with recognition as well as offset values.

4.4 Feeder Carriage Configuration

■ Intelligent Tape Feeder

There are two groups of tape feeders: with or without the joint detection sensor, which detects splicing positions for the purpose of managing the component verification and etc. According to the tape width, each group is classified as shown below.

The feed pitch is automatically set according to the production data.

Feeder type		Type	Setting pitch	Maximum depth of Boss	Reel*1 diameter	Maximum Setting reel	Feed pitch (1 pitch = 4 mm)																		
							0.25	0.5	1	2	3	4	5	6	7	8	9	10	11	12	13	14			
4 mm thin type single*2*3 (No detection sensor)		Emboss	10.5 mm	0.5 mm	Small	120	○ 1 mm																		
8 mm thin type single*2*3		Paper/ Emboss			21 mm	3 mm	Small	120	○ 1 mm	○	○														
8 mm double*4			Large	60			○ 1 mm		○	○															
8 mm double for 0402 (01005")*4			Small	120			○ 1 mm		○	○															
8 mm double *4 (For thin embossed tape)			Large	60			○ 1 mm			○	○														
12/ 16 mm			Emboss	21 mm			15 mm	Large	60	○ 1 mm	○	○													
12 mm	16 mm							Small	60			○	○	○	○										
24/ 32 mm								Large	60*5				○	○	○	○	○	○	○						
44/ 56 mm				42 mm			26 mm*6	Large	30				○	○	○	○	○	○	○	○					
72 mm		63 mm		20							○	○	○	○	○	○	○	○	○	○	○	○			
88 mm (With detection sensor)		84 mm		15 mm 21 mm	14						○	○	○	○	○	○	○	○	○	○	○	○			
104 mm (With detection sensor)		105 mm		21 mm	12						○	○	○	○	○	○	○	○	○	○	○	○			
		126 mm			10						○	○	○	○	○	○	○	○	○	○	○	○			

*1 Small reel: $\phi 178$ mm, Large reel: $\phi 178$ mm ~ $\phi 382$ mm

*2 When thin type tape feeders are installed, "Attachment for thin type tape feeder" is required for each feeder slot.
It is not possible to set a small reel and a large reel to the reel holder in the same slot.

*3 For thin feeder inspection with IFCU, contact us.

*4 The 8 mm double tape feeder holds two small reels.

It is not possible to set a small reel and a large reel to the reel holder in the same slot.

*5 Depending on the width of reel, the maximum setting count may be reduced.

*6 When emboss depth of components is over 21 mm, you need to make modifications to the feeder cart (or 13-slot feeder base).
(Custom specifications)

Applicable emboss depth after modification: Max. 26 mm

** Remarks **

- In the case of 8 mm emboss tape, the emboss depth is possible to up to 3 mm.
If you want to use the "paper/ embossing shared block" which is included with the feeder, the emboss depth is limited to 1.2 mm or less.
- In the case of 12 mm/ 16 mm emboss tape, the emboss depth is possible to up to 15 mm.
If the tape width is narrow, you need to adjust the feeder groove width for restraining the tape.
In this case, the emboss depth is limited to 13 mm or less. For further information, please contact us.

■ Auto Load Feeder*

This is a thin type feeder materialized automatic component tape setup.

The off-line setup time can be drastically reduced by the simple work of inserting a tape, then pressing the “Send” button. (Approx. 30s/reel ⇒ Approx. 15s/reel)

If insert a following component in advance, this feeder can detect the tape end of preceding component and automatically supply the following component during production.

Because you don't need a tape splicing work, the error stop of splice mistake can be prevented.

This auto load feeder can also use a short cut tape (longer than 120mm).

* Not available for emboss tape.

Feeder type	Tape	Setting pitch	Reel diameter	Maximum Setting reel	Feed pitch (1 pitch = 4 mm)															
					0.25	0.5	1	2	3	4	5	6	7	8	9	10	11	12	13	14
8 mm thin type auto load feeder ^{*1*2*3}	Paper	10.5 mm	Small	120	●															
			Large	60	1 mm	●	●													

*1 When auto load feeders are installed, “Attachment for thin type tape feeder” is required for each feeder slot.

*2 If you want use IFCU to check auto load feeder, please contact us for details.

*3 To make good use of it, we suggest setting two reels on one auto load feeder.

One preceding component reel and one following component reel.

In this case, the maximum setting reel of auto load feeder is

Small reel: 60 reels (preceding component 60 reels, following component 60 reels)

Large reel: 30 reels (preceding component 30 reels, following component 30 reels)


If you want more reels, please contact us.

Restrictions

The auto load feeder is not available for the reels or utilizations below.

- The tape end is fixed on the reel by adhesive tape etc. (Taping spec.)
(If reel and tape are hard to be separated, by cutting the end of tape will be available.)
- The tape which is be spliced.
- Availability by taping spec. from the last component to the tape end:
280 mm or below: Available without restrictions
Over 280 up to 680 mm: Available depending on the machine setting
Over 680 mm: Component exhaustion error will result.
- When either of the following requirements for the cover tape sticking specification is not satisfied:

Tape guide type	Target components	L (mm)
Tape guide S	0402	5.85mm or over
Tape guide A	0603	5.85mm or over
Tape guide B	1005	6.00mm or over
Tape guide C	1608	6.30mm or over



When the dimension L does not satisfy (shorter than) the above requirement, peeling mistake would happen.

*If need the tape guide for 2012 or 3216, please contact us.

- The tape end is cut obliquely. New and old tape may not be replaced automatically.
- Tape length.
Usable tape length is 120 mm or more.
Insertion slot to be used and available functions differ with the tape length as follows:
 - Tape of 120 or more but less than 500 mm in length should be inserted through the slot dedicated to short tape.
In this case, the automatic sending/replacement function and the component verification function cannot be used.
 - When 500 mm is exceeded, insert the tape through the tape slot on the rear of the feeder.
In this case, the automatic sending and replacement are available. A reel is required to use the component verification function.
- Conditions of automatic replacement.
The following condition is not available for automatic replacement.
 - When “pickup error stop” is setting in “one time” and component remaining number has not been input or wrong number, automatic replacement is not available.


Top portion (Lead portion) processing

The lead portion processing of auto load feeder should satisfy the following conditions.


(The cutting position of lead portion)

Before you insert tape to the auto load feeder, please cut the lead portion with a scissors as the picture below. (To prevent a peeling mistake and tape replacement mistake, please cut perpendicularly.)

<New Tape>



<Half used tape>




End portion (Trailer portion) processing

Please cut the empty tape less than 30mm.

The replacement time will be longer if over 30mm.

When the length of empty pocket positions is between 280 and 680 mm, machine setting is required.


However, when it is longer than 680mm, a shortage error will happen.



■ **Intelligent Stick Feeder**



The stick feeder supplies components through the stick by vibration.
The intelligent stick feeder has improved its ability to support large-sized components, in addition to the traditional merits such as high versatility*1, quick delivery*2, and maintenance-free*3.
(Supporting only Lightweight 8-nozzle head and 3-nozzle head V2)

- *1 It supports not only SOP, SOJ, and PLCC but also odd-shaped components such as the connector.
- *2 With the feeding method that cuts out stick tips (see below), it can feed components as soon as you get them.
- *3 It needs no particular maintenance except for such cleaning as dust removing.




	Single stick feeder	3-lot stick feeder
Setting pitch	42 mm	84 mm
Maximum number of setting feeders	30 inputs	14inputs


Component feeding methods

Feeding with stick tips cut out	Feeding with a guide block (Option)
When components in sticks are level and stable while the sticks are placed in a horizontal position, cut out the stick tips so that the components will be picked up directly from inside the sticks. PICKUP directly from inside sticks  Tips cut	When components in sticks are not level and not stable while the sticks are placed in a horizontal position, attach a block (called a guide block) to solve those problems so that the components will be picked up from the guide block. The guide block is created separately according to the component dimensions to be used. How to design the guide blocks is open to the public, so the users can make them. PICKUP from a guide block  Guide block

Applicable components

Standard				Special			
SOP, SOJ, PLCC				Except for the standard component types and dimension range, depending on the component and stick shapes, components of up to the following dimensions may also be used. If using such components, you need to flow them actually to check of feeding conditions or consult us.			
(All dimensions in mm)							
	W	L	H				
Min	8	9	2.5				
Max	31	31	6				

(All dimensions in mm)			
	W	L	H
Min	-	-	-
Max	31	60	25



Applicable sticks

(All dimensions in mm)			
	Ws	Ls	Hs
Min	-	300	-
Max	34	600	28

The image shows five types of sticks with their respective dimension labels: Ws (width), Ls (length), and Hs (height). The first diagram shows a stick with a central component and two side components. The second diagram shows a long stick with a central component and two side components. The third diagram shows a stick with a central component and two side components. The fourth diagram shows a stick with a central component and two side components. The fifth diagram shows a stick with a central component and two side components.

Number of attachable sticks

Feeding with stick tips cut out	Feeding with a guide block
See Table 1 for the number of attachable sticks.	See either Table 1 or 2, whichever has less number, for the number of attachable sticks.

Table 1

	Stick width W_s (mm)	Number of attachable sticks
Single Stick Feeder	$W_s \leq 34$	1
3-lot Stick Feeder	$W_s \leq 19$	3
	$19 < W_s \leq 28$	2
	$28 < W_s \leq 34$	1

Table 2

	Component width W (mm)	Number of attachable sticks
Single Stick Feeder	$W \leq 31$	1
3-lot Stick Feeder	$W \leq 16$	3
	$16 < W \leq 25$	2
	$25 < W \leq 31$	1

* In principle, production must be limited only for one type product when you attach multiple sticks on 3-lot stick feeder..
 Production for different type products is available with limitations of the shape and dimension of the stick. For details, please consult us.

■ Stackable Stick Feeder

There are two types of stackable stick feeders: S size and L size, each are equipped with unique adjustment mechanisms which makes them flexible and enables them to be adjustable according to stick size and component dimensions.

In addition to common type, there is another type applying to component verification.

Therefore, with the combination of above 2 types of specification, there are total 4 types which can be selected.

Feeder type	Type		Feeding pitch	Max load *1	Component dimension	Max component mass	Packing Dimension	
Stackable Stick Feeder *2	S	Standard	No step (adjustable)	8pcs	W 4mm~20mm	2kg (Total mass of components set in feeder,)	Stick length 380 mm~700 mm	Stick width 8~24mm
		Traceability			L 5mm~70 mm			Stick height 10~29mm
	L	Standard		8pcs	W 4mm~60mm			Stick length 8~64mm
		Traceability			L 5mm~70 mm H 12mm~30 mm			Stick height 21~39mm


*1 When front and rear side is feeder cart (Excluding when tray is attached)

*2 Depending on the size and shape of the components, guide rail, special pushers or other special parts may be required. This will be classified as customized spec.

For parts with leads protruding from the side of the part body and parts with steps and protrusions on the bottom and sides of the body, please consult us separately.

In addition, when pushing components in the stick, the components that overlap or ride up will not be applicable.

* When both sides of length between the side surface of a component and the side surface of stick is 3mm or larger than 3mm, special support is needed. Contact us for the details.



When both length are 3mm or larger than 3mm, special support is needed..

* The use of stackable stick feeders requires "Air Supply Unit for Feeder".

*We design to make the component feeding unit or the stick of the feeder adjustable to improve the versatility. However, depending on the shape of parts and sticks, there are cases where it cannot fully correspond with the standard adjustment range. At that time customization is required. We recommend to confirm the components and stick used in advance.

*We do not recommend daily changeover work. We recommend stackable stick feeder changeover for per component

* Full length : 1 325.5 mm ~ 1 560 mm

The maximum length changes with stick length. When the stick you are using reaches to a certain length (about 460 mm or longer), full length gets long enough for the stick to be put inside.

Height : 699.5 mm

*The stackable height is 216mm + H (H : stick height.)

Below is an indication of attachable sticks.

S type 22 pcs (When stick height is minimum of 10mm)

L type 11pcs (When stick height is minimum of 21mm)

*In traceability type, with parameter, it is possible to select individual verification which collates sticks one by one to replenish sticks or group-verification which collates sticks in a group to replenish.


Stackable stick feeder is used in individual verification, it can attach up to 4 sticks.


*Components to be set in the stick should be the quantity that can be pushed from the rear where 10N or less is applied with the stick held horizontally.

*Be sure to attach and detach stackable stick feeder to and from the cart only when the machine is equipped with the cart.

Operation is impossible in the following situations.

1. Attach and detach the cart to and from the machine while it is attached to the cart
2. Move the stick feeder with it attached to the cart.
3. Store the stackable stick feeder on the cart.







- * Mounting stackable stick feeder on a feeder requires to add reinforcing plate in order to prevent deformation of a clamp part of a feeder.
(Deformation may cause attaching/detaching defect)
(Reinforcing plate is packed with stackable stick feeder)
When reinforcing plate runs short, arrange them individually.
(Model No. : MTKP009217AA (one set consists of six plates))

■ Pusher for Stackable Stick Feeder

Pushers for stackable stick feeder are available in the 5 types shown below.

Pusher type	Shape	Dimensions	Max. component width (Reference value)	Stackable Stick feeder	
				S	L
S size *		W 4×H 4×L25mm	10mm	Standard	Standard
M size		W10×H10×L25mm	15mm	Option	Option
L size		W15×H10×L30 mm	30mm (20mm for stick feeder S)	Option	Option
LL size		W30×H10×L30 mm	50mm	—	Option
LLL size		W50×H10×L30 mm	60mm	—	Option

- * S size pusher is included as standard with S size stackable stick feeder.
If S size pusher is purchased as spare, it will come in a set with the feeding wire because the pusher is glue-fixed to the wire.
For M~LLL size pushers, they are designed such that they can be used by slotting into the S size pusher.
- * Depending on the size and shape of the components, special pushers or other special parts may be required.
This will be classified as customized spec.


■ Tray Feeder

When the NPM-W2 main unit is for tray feeder specification, it can be connected to the rear side. It cannot be installed to the front side.


- Single tray feeder (Max. 20 product types)*
- Twin tray feeder (Max. 40 product types)

Applicable head: Lightweight 8-nozzle head, 3-nozzle head V2

* 13-slot feeder base is included with the single tray feeder.







Single tray feeder



Twin tray feeder

Tray Conditions

Item	Specification							
Tray dimensions	Tray dimensions	L 85 × W 100 mm ~ L 230 × W 335 mm						
	Tray height	2 mm ~ 56 mm (3-nozzle head V2) 2 mm ~ 17 mm (Lightweight 8-nozzle head) * When there is a tray higher than 30 mm, you cannot use tray supply side.						
								
Component position error	<table><tr><th>Pick up face of components</th><th>Position error</th></tr><tr><td>Under 10 × 10 mm</td><td>±1.0 mm or less</td></tr><tr><td>10 × 10 mm or over</td><td>±1.5 mm or less</td></tr></table>  * The pick-up face of a component must be flat.	Pick up face of components	Position error	Under 10 × 10 mm	±1.0 mm or less	10 × 10 mm or over	±1.5 mm or less	
Pick up face of components	Position error							
Under 10 × 10 mm	±1.0 mm or less							
10 × 10 mm or over	±1.5 mm or less							
Permissible tray warpage (Gap)	Warpage (Gap): Max. 0.5 mm 							
Type	• Use an injection molded tray of sufficient strength and dimension accuracy. • If you use any tray other than the above, consult us, separately.							
Mass	• Mass of the tray: 1 kg or less Tray + components = Max. 1 kg/ pallet (Excluding the mass of pallet) • Total mass of the tray magazine: 20 kg or less Magazine + pallets + trays + components = Max. 20 kg/ magazine							
Pallet insertion limitations	• There must be a space of minimum 4mm between tray pallets. Which slot to occupy and insert will be determined based on that.  (Example)							

4.5 Line Configuration

Regardless of stand-alone installment or line connection, PC designed for FA is always needed to set up NPM-W2.

FA PC & HUB:

A set is required for each line in the case of FA PC equipped with line server function.
LNB will be installed.

Basic specifications of FA PC:

Type	FC-E27B-GL2CP7 (made by NEC)
Auxiliary storage	Internal HDD: 500 GB × 2 as standard (Mirroring supported)
OS	Miracle Linux (Version 6)
Outside dimension	W 100 × D 360 × H 310 mm
Mass	10.0 kg

* Please prepare the power supply cable by yourself.

Basic specifications of HUB:

Standard	IEEE802.3 standard
Data rate	10BASE-T/ 100BASE-TX/ 1000BASE-T(Auto-Negotiation)
Recommended type	DGS-1016L (made by D-Link)

* Please prepare the LAN cable by yourself.

LNB

LNB (Line Network Box) is a relay system connecting the machine and NPM-DGS (Data Creation System), being installed on the FA PC.

It handles multiple machines as a line; thereby centrally managing information, downloading production data, and compiling production management information.

(This software is included in the NPM-W2 system software DVD-ROM.)

Main functions:


- ① Downloading production data to machines
- ② Retaining production data and managing differences
- ③ Retaining/Compiling production management information
- ④ Retaining event information

LWS (Line Work Station)

LWS can display the result data retained in LNB by accessing to LNB through the use of PC*.

* A PC is to be prepared by the customer. Google Chrome(the latest version recommended) is required for access.
Please refer to "NPM-DGS Specification booklet" for details.

Examples of system configuration (Line configuration of NPM-W2 only)



*1 When the number of machines coupled exceeds 15 machines, please consult us.

*2 Please prepare the LAN cable by yourself.

(Because the required cable varies in length depending on where you install the FA PC and the HUB)
Basic specification: UTP cable of enhanced category 5 or later


- Quality information viewer

Comprehension of changing points and analysis of defect factors are supported by displaying the information on quality (the position of the feeder used, recognition compensation value, parts data and others) per PCB and per mounting point.

Main features:

- Gathers/Stores weekly quality information

- Displays quality information to LWS



* Please prepare PC on your own. It cannot be shared with the NPM-DGS.
This software is included in the NPM-W2 system software DVD-ROM.

Operating environment of quality information viewer

- Hardware Specifications

Item	Specification	Required or Recommended
Main body	IBM PC/AT compatible machine (A desktop PC is strongly recommended.)	Required
CPU	Intel® Core™2 Duo E6700 equivalent or greater	
Mother board	IBM-fully-compatible machine	
Serial I/O	1 IBM-fully-compatible machine	
Graphic board	SXGA or higher Desk top region: 1 280 × 1 024 dot or more	
Memory	4 GB or more	
HDD	500 GB or more of available space (NTFS file system)	
Optical drive	DVD drive To be used in installation	
Keyboard	English version: 101English keyboard Japanese version: 106 Japanese keyboard	
Mouse	Supported by your OS as standard	
Monitor	SXGA-compliant	Recommended
Network card	For 100/1000BASE-T	
Uninterruptible power supply (UPS)	Supported by your OS as standard	Recommended

- Software Specifications


Item	Specification	Required or Recommended
OS	Microsoft® Windows® 11 Pro Microsoft® Windows® 10 Pro (64-bit version)	Required
Support language	English, Chinese, Japanese	
Framework	Microsoft® .Net Framework 3.5	
Virus check	Virus Buster™ Program version 7.0	Recommended

- Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Intel and Intel Core are registered trademarks or trademarks of Intel Corporation in the United States.
- Virus Buster is a registered trademark or trademark of Trend Micro Incorporated.

Examples of line configuration (Transfer direction: left to right flow sample).


The line configuration of NPM-W2 and the location of the extension conveyors and others are as follows. It is required for the first and last equipment of the NPM-W2 to ensure the safety of the transfer opening. When the extension conveyor is installed between the NPM-W2s please select the conveyor for upstream side.

1. For the line of NPM-W2 alone (Coupled machines: 15 or less)



2. For the line of NPM-W2/ W combined with other systems

Make sure to select an extension conveyor at the point where NPM-W2/ W lies next to another system.



* The above line configuration is a sample.

It may differ depending on your system configuration and the like. For details, please contact us.


* Connecting to NPM-DX/ D3A/ D3/ D2/ D requires a traverser between them. The machine cannot be connected to NPM-TT or NPM.

PCB transfer height

The standard NPM-W2 PCB transfer height is 900 mm to 920 mm.


The PCB transfer height of the production line may differ based on the condition of the floor in the customer's factory. The figure below shows an example in which the feeder cart for #3 and #15 cannot connect with the equipment as usual.

Please contact us if all of the NPM-W2 transfer heights in a production line are not 900 mm to 920 mm.




Height difference between PCB transfer units

The difference in height between the machines when transferring PCBs should be 0.5 mm or less.



4.6 Line configuration that includes a machine equipped with an inspection head

■ Standard line configuration




■ Other line configurations

Position of inspection head or conveyor can be allocated flexibly depending on purpose.


1) To shorten length of line

Allow all NG PCBs from Solder Inspection (SPI) and Component Inspection (AOI) to stop altogether at Ejection conveyor which is located at the end of a line. Placement points or patterns judged as NG at Solder Inspection shall be automatically skipped through placement and Component Inspection.



2) To execute foreign object inspection for two types of components in Reel and on Tray.

Foreign object inspection is carried out to inspect presence of such object under specified components. When an object is found, the specified components are not mounted. Therefore, the components need to be placed on the table opposite from inspection head or in a downstream process. When Reel and Tray types are mixed, please arrange as follows. However, please note that it is not possible to execute component inspection after placement of components in a downstream process.






* The above line configuration is a sample.

It may differ depending on your system configuration and the like. For details, please contact us.




■ List of optional functions and required peripheral equipment

When using the following options, it is required to prepare peripheral equipment according to each function.

Optional function	Description	Peripheral equipment
Solder inspection NG ejection function	Based on inspection results of PCBs that are ejected from NPM-W2, OK/NG signals are output so that NG PCBs are stopped on the ejection conveyor and OK PCBs are passed through.	(1) Extension conveyor (2) Ejection conveyor (Customer)
Component inspection NG ejection function	Also once a PCB is removed from conveyor to repair or to re-check, a function is needed to output a request signal to eject the next PCB to NPM-W2.	(1) Extension conveyor (3) Ejection conveyor (Customer)
Re-putting function	It operates together with "Component inspection NG ejection function" as a set. This function allows you to put a repaired NG PCB, inspect, and mount again which failed to mount with the opposed head. In addition, the PCB removed with NG is managed by the barcode. Reading the barcode during the re-putting enables tracking management.	(1) Extension conveyor (4) Re-putting conveyor (Customer) (5) Wired scanner
NG map display function	Although NG position can be confirmed on equipment screen, this function enables to display it on a PC screen also for component inspection.	(6) Display (Customer) (7) Connection cable (Customer) (8) Mouse (Customer)
Pattern information communication function	When a defect is found during solder inspection, skip placement to the defective pattern to minimize cost of component loss. <u>Defective pattern</u> Skip all component placement in the patterns where printing failure occurred.  Also, when a defect is found during land inspection, skip the defective patterns can minimize cost of component loss similarly. <u>Defective pattern</u> Skip all component placement in the patterns where land failure occurred.   Foreign object	

* You are kindly requested to prepare the peripheral equipment noted as (Customer).

Function	Peipheral equipment	Specifications																																													
Re-putting function	(4) Re-putting conveyor (Customer)	- When the re-putting switch is pressed, PCB transfer is stopped by receiving an order from NPM-W2. The PCB ejection stop signal is transmitted to the NPM-W2 in the upstream via FA PC (LNB). - Required information of PCBs is scanned by the barcode reader ,and then the PCBs are placed on the conveyor prompting them to be sensed to implement their loading to NPM-W2. - The following transfer operating specifications must be satisfied. (1) <u>PCB loading wait operation</u> During stand-by status without NG PCB in stock, transmit Board Available (BA) status signal from pre-process to post-process and Ready status signal from post-process to pre-process. (2) <u>PCB stock operation</u> Placing PCB at stand-by position brings the machine to PCB stock status, turning OFF Ready signal to pre-process and BA signal to post-process. Other than the above, at the start of PCB loading, turn OFF Ready signal to pre-process and unload the PCB as it is without stopping. (3) <u>Transfer restart operation after stocking PCB</u> As it became unloading stand-by status by input of foot switch etc., turn ON BA signal to post-process. After confirming Ready signal of post-process is ON, unload PCB to post-process. After completing the unloading (confirm Ready signal of post-process is turned from ON to OFF), return to operation # (1). Connector pin layout of the conveyor control [XP connector] <table><tr><th>Pin No.</th><th>Signal</th><th>Signal direction</th></tr><tr><td>1</td><td>Ready1 (loading request)</td><td>from NPM-W2 to conveyor</td></tr><tr><td>2</td><td>Ready1 Return</td><td>from NPM-W2 to conveyor</td></tr><tr><td>3</td><td>Board Available1+ (unloading available)</td><td>from conveyor to NPM-W2</td></tr><tr><td>4</td><td>Board Available1- (input common)</td><td>from conveyor to NPM-W2</td></tr><tr><td>5</td><td>N.C.</td><td></td></tr><tr><td>6</td><td>N.C.</td><td></td></tr><tr><td>7</td><td>N.C.</td><td></td></tr><tr><td>8</td><td>N.C.</td><td></td></tr><tr><td>9</td><td>Ready2 (loading request)</td><td>from NPM-W2 to conveyor</td></tr><tr><td>10</td><td>Ready2 Return</td><td>from NPM-W2 to conveyor</td></tr><tr><td>11</td><td>Board Available2+ (unloading available)</td><td>from conveyor to NPM-W2</td></tr><tr><td>12</td><td>Board Available2- (input common)</td><td>from conveyor to NPM-W2</td></tr><tr><td>13</td><td>N.C.</td><td></td></tr><tr><td>14</td><td>N.C.</td><td></td></tr></table> * Please do not make connection to “N.C.”. * This is used with the XL connector of the main body of NPM-W2 being connected. * For further details, such as connector model numbers and control inside the conveyor, please consult us. * When the re-putting conveyor is connected, the extension conveyor must be installed between NPM-W2’s main body and the ejection conveyor.	Pin No.	Signal	Signal direction	1	Ready1 (loading request)	from NPM-W2 to conveyor	2	Ready1 Return	from NPM-W2 to conveyor	3	Board Available1+ (unloading available)	from conveyor to NPM-W2	4	Board Available1- (input common)	from conveyor to NPM-W2	5	N.C.		6	N.C.		7	N.C.		8	N.C.		9	Ready2 (loading request)	from NPM-W2 to conveyor	10	Ready2 Return	from NPM-W2 to conveyor	11	Board Available2+ (unloading available)	from conveyor to NPM-W2	12	Board Available2- (input common)	from conveyor to NPM-W2	13	N.C.		14	N.C.	
	Pin No.	Signal	Signal direction																																												
1	Ready1 (loading request)	from NPM-W2 to conveyor																																													
2	Ready1 Return	from NPM-W2 to conveyor																																													
3	Board Available1+ (unloading available)	from conveyor to NPM-W2																																													
4	Board Available1- (input common)	from conveyor to NPM-W2																																													
5	N.C.																																														
6	N.C.																																														
7	N.C.																																														
8	N.C.																																														
9	Ready2 (loading request)	from NPM-W2 to conveyor																																													
10	Ready2 Return	from NPM-W2 to conveyor																																													
11	Board Available2+ (unloading available)	from conveyor to NPM-W2																																													
12	Board Available2- (input common)	from conveyor to NPM-W2																																													
13	N.C.																																														
14	N.C.																																														
	(5) Wired scanner	- Please purchase the optional wired scanner. - Please prepare the barcode for re-putting by yourself. Any numbers are available if they are corresponding codes with our wired scanner. It is recommended that you attach the barcode to the box or rack, in which PCBs are stored, not directly to PCBs, and scan the barcode on the box or rack. As for the PCBs that have the barcode, which corresponds with our wired scanner, already being attached, it is possible to scan the attached barcode.																																													

Function	Peipheral equipment	Specifications																																		
NG map display	(6) Display (Customer)	This displays NG part image on PCBs that are judged as NG by inspection and NG maps which show at where on PCBs NG occurred. - Resolution: 1 024 × 768 or higher - Display colors: about 16.77 million or more - Image input signal: Analog RGB																																		
	(7) Connection cable (Customer)	A cable that connects the display, which shows the NG map, and the inspection box. For each signal wire, R, G, and B, we recommend the 75 Ω coaxial cable. Cable length: 5 m or less We show below the shape and pin layout of “MONITOR”, which is a connector for the inspection box. [Connector: Mini D-sub 15 pin (Female)] <table><tr><th>Terminal No.</th><th>Signal name</th><th>Pin connection</th></tr><tr><td>1</td><td>GRED</td><td rowspan="15"></td></tr><tr><td>2</td><td>GREEN</td></tr><tr><td>3</td><td>GBLUE</td></tr><tr><td>4</td><td>NC</td></tr><tr><td>5</td><td>GND</td></tr><tr><td>6</td><td>GND</td></tr><tr><td>7</td><td>GND</td></tr><tr><td>8</td><td>GND</td></tr><tr><td>9</td><td>VP50</td></tr><tr><td>10</td><td>GND</td></tr><tr><td>11</td><td>NC</td></tr><tr><td>12</td><td>SDA-10</td></tr><tr><td>13</td><td>GHSYNC+10</td></tr><tr><td>14</td><td>GVSYNC+10</td></tr><tr><td>15</td><td>SCL-10</td></tr></table>	Terminal No.	Signal name	Pin connection	1	GRED		2	GREEN	3	GBLUE	4	NC	5	GND	6	GND	7	GND	8	GND	9	VP50	10	GND	11	NC	12	SDA-10	13	GHSYNC+10	14	GVSYNC+10	15	SCL-10
	Terminal No.	Signal name	Pin connection																																	
1	GRED																																			
2	GREEN																																			
3	GBLUE																																			
4	NC																																			
5	GND																																			
6	GND																																			
7	GND																																			
8	GND																																			
9	VP50																																			
10	GND																																			
11	NC																																			
12	SDA-10																																			
13	GHSYNC+10																																			
14	GVSYNC+10																																			
15	SCL-10																																			
(8) Mouse (Customer)	This is used for displaying enlarged NG maps, clicking the completion button after checking NG maps, and etc. - Required OS: Windows XP Windows Embedded Standard 7 - Connection interface: USB 1.1/ 2.0 - Connection cable: Ones that are certified for USB specification of the mouse which is used by you. Length 5 m or less - Connection terminal: Type A * Maximum electric source/current which we can take out from the USB connector of the inspection box is 500 mA (DC + 5 V).																																			

4.7 Recognition Unit Configuration

■ Head camera

- Field of view: 7.68 × 7.68 mm

(For information about the PCB recognition mark dimensions, please refer to “7. PCB Design Standard.”)

■ Multi-recognition camera: [Type 1](#)

The position and the angle deviation in picking up the chip are corrected.

In addition, the presence of solder balls can be detected * for BGA/ CSP through the side lighting (option).

Recognition method	Recognition speed	Applicable Component
Batch recognition	High	General chip components including the square chips measuring 03015* or over. BGA, CSP, QFP, SOP, and connector etc. * When "03015 placement support" is selected.

* There are limitations on the components for which the ball detecting is available.

Please refer to the item describing the recognition condition of BGA/ CSP.

* The multi-recognition camera on NPM-D3, NPM-W2 or later, some parts cannot be shared with the conventional line camera.
(Such as using the option of the brightness check function etc.)

QFP/ SOP Recognition Conditions ([Type 1](#))

Placement conditions of QFP / SOP are as follows.

(Basically, in QFP/SOP mounting, we will receive samples and then decide whether it is mountable after going through consideration and experiments)

	Lightweight 16-nozzle head V3A	12-nozzle head	Lightweight 8-nozzle head	3-nozzle head V2
Outside dimensions	See “3.2 Standard Functions” *1			
Thickness				
Lead pitch	0.4 mm or over			
Lead width	0.2 mm or over			
Lead shape	Leads must be protruding out of the mold area by 1 mm or over.			

- Feeding type: Taping and tray

*1 When the short side of component outer dimensions exceeds 45 mm × 45 mm, it is split recognition.

* For information about the components that are not conforming to the above specifications, please consult us.

Recognition conditions of BGA/ CSP (Type 1)

Placement conditions of BGA / CSP are as follows.

(Basically, in BGA/CSP mounting, we will receive samples and then decide whether it is mountable after going through consideration and experiments)

	Lightweight 16-nozzle head V3A	12-nozzle head	Lightweight 8-nozzle head	3-nozzle head V2
Outside dimensions	See “3.2 Standard Functions” *1			
Thickness				
Ball pitch	0.075*2*3 ~ 1.5 mm			
Ball diameter	$\phi 0.045 \text{ mm}^{*3} \sim \phi 0.9 \text{ mm}$ (Ball diameter should be uniform)			
Ball shape	Globular or cylindroid*4			
Materials of ball	High temperature solder, eutectic solder			
Balls	Lattice arrangement : $2 \times 2 \sim 64 \times 64$ (Rows $\times$ Columns) (Staggering arrangement : $2 \times 2 \sim 32 \times 32$ (Rows $\times$ Columns) *Ball pitch and ball dimensions should be uniform. At arrangement that is not lattice : $2 \sim 15\,000$ balls			

- To enable the simultaneous recognition of BGA/ CSP appearance and solder balls, the body shall be made of the glass epoxy. There are some cases in which the recognition is difficult depending on conditions (pattern, with or without through hall, luster, etc.) of placement surfaces of solder balls.
- BGA/ CSP which is made of ceramic or has the gold body is placed with only the contour recognition.
- Surface of ball
The surface of ball should be free from the blur due to oxidation.
(Effect extent of oxidation for the recognition needs to be checked by an experiment.)
- Feeding type: Taping and tray

*1 When the short side of component outer dimensions exceeds 45 mm $\times$ 45 mm, it is split recognition.

*2 Consult us regarding large-sized, minimal pitch components.

*3 At split recognition, the minimum ball pitch is 0.15 mm, and the minimum ball diameter is 0.09 mm.

*4 Placement may fail depending on the combinations of ball pitches or ball diameters.

Recognition conditions of connector (Type 1)

The general conditions of placement connectors are as follows.

(Basically, in connector mounting, we will receive samples and then decide whether it is mountable after going through consideration and experiments)

	Lightweight 16-nozzle head V3A	12-nozzle head	Lightweight 8-nozzle head	3-nozzle head V2
Outside dimensions	See “3.2 Standard Functions” *1			
Thickness				
Lead pitch	0.5 mm or over			
Lead width	0.2 mm or over			
Lead shape	Leads must be protruding out of the body by 1 mm or over.			
Other shape	No through holes around contact pins shall exist in a vertical direction. Contact pins shall not be exposed to the underside.			

- Feeding type: Taping, tray and stick

* In the case of the placement of large sized connectors, in addition to those, some limitations may be imposed on the dimensions depending on the relation between the pick up position and the recognition range.
For further information, please contact us.

*1 When the short side of component outer dimensions exceeds 45 mm × 45 mm, it is split recognition.

■ Component thickness measurement function (Multi-recognition camera: Type 2)

In addition to Type 1 features, Type 2 has the component thickness measuring feature and the top/bottom detecting feature and improves mounting quality.

Item	Description		
Applicable component	03015R*1 ~ Mini Tr/ Di (Max: 6 × 6 mm)		
	Minimum component thickness: 0.1 mm (For standing/tilted standing detection at the time of pickup, 50 μm or more is required as difference between any two of thickness, width, or length of components.)		
Functions	Measurement function of component thickness	Every time	Component thickness is measured every time, reflecting the result on placement height. Micro components' standing/tilted standing and flip of Tr/ Di at the time of their pickup can also be checked simultaneously.
		First time of parts exchange	The part detection will be done at the first part after the following operations: "Automatic operation starts", "Parts replenishment", "Tape splicing detection", "Chip data correction".
		Component teaching	Thickness measurement and chip data registration are possible for respective components.
	Check function of nozzle tip	A check is done for nozzle tip height's abnormality (break or nozzle holder sliding defect).	
	Ejection detecting function	After component ejection following recognition errors or etc., a check is done to make sure there's no adhesive material on the nozzle tip.	

* This detection is not applicable when you use the nozzle with pad or the nozzle with steps on its tip. ([e.g.] 205A)

* Measurement with short nozzle is not included.

* Please make purchase for each table at the front/ rear sides.

* The multi-recognition camera on NPM-D3, NPM-W2 or later, some parts cannot be shared with the conventional line camera.
(Such as using the option of the brightness check function etc.)

*1 When "03015 placement support" is selected.

■ 3D-measurement function (Multi-recognition camera: Type 3)

In addition to Type2 features, Type 3

- Detects coplanarity(flatness) of all the leads and XY-direction positions at high speed in QFP/ SOP and other packages.
- Detects presence or absence of all the balls, and partially broken balls in its shape in BGA/ CSP and other packages.

Recognition method	Recognition speed	Typical example of components	Min. lead/ Min. ball pitch	Min. lead width/ Min. ball diameter	Min. ball height
Batch recognition	3D high speed	QFP, SOP	0.4 mm ^{*1}	0.2 mm	—
		BGA, CSP	0.4 mm ^{*2}	0.25 mm	0.25 mm


* The multi-recognition camera on NPM-D3, NPM-W2 or later, some parts cannot be shared with the conventional line camera. (Such as using the option of the brightness check function etc.)

* Coplanarity(Flatness) measuring range is ± 0.5 mm.

* Depending on recognition speed and/or the number of electrodes, there may be recognition waiting time at mounting.

* BGA/ CSP is limited to the ones that electrode shape is circle and that the bottom surface has ball-shape terminals.

* When it is QFP/ SOP, there must be at least 0.2mm flat surface at the bottom surface of a lead.



*1 For QFP/ SOP of a lead pitch less than 0.4 mm, please consult us.


*2 For BGA/CSP whose ball pitch is less than 0.4, consult us.

■ Height sensor

It controls the placement/dispensing height of the nozzle by measuring the height (warpage) of PCB.

If a measurement result exceeds the acceptable value, a warning is issued prior to placement or dispensing to prevent the occurrence of quality defects.

There are two independent functions; local PCB height correction (for the dispensing head) and PCB warpage correction (for the placement head).



Height sensor



Local PCB height correction (for the dispensing head)

Adjusts to the optimal nozzle height by measuring several PCB heights (warps) near the draw dispensing (non-contact dispensing) positions.

The measurement is before dispensing.

Item		Description
Applicable PCB	Thickness	0.3 mm ~ 8.0 mm
	Material	Glass epoxy, Paper Phenolic
	Measuring surface material	The area of 1.5 × 1.5 mm or larger on the copper foil + the resist surface, the copper foil surface or the silk surface. Transparent and translucent area are excluded. (e.g., glass epoxy material face)
Functions	Height control	Adjusts to the optimal nozzle height by measuring several PCB heights (warps) near the draw dispensing (non-contact dispensing) positions.
	PCB warpage acceptable value detecting	If the difference equal to the measurement results of plural points exceeds the acceptable value, the occurrence of defects in quality is prevented by detecting the error before drawing.
Measurement condition	Measurement height	PCB upper surface ±4 mm (A measurable range but not a PCB warpage acceptable range.)
	Measurement area	You need to set a measurement point at 5 mm inside from a slit in the edge of a PCB.
Measurement time		0.5 s (30 × 30 mm in an optimal condition, with 4-point measurement)

* Install to the beam mounted with the dispensing head.



* Measurement information is not communicated between machines.

* Only the dispensing height of the dispensing head can be corrected.

PCB warpage correction (for the placement head)

Controls the placement height by measuring the height (warpage) of the whole PCB.

The measurement is after PCB recognition.

Item		Description
Applicable PCB*1	Thickness	0.3 mm ~ 8.0 mm*3
	Material	Glass epoxy
	Measuring surface material	The area of 1.5 × 1.5 mm or larger on the copper foil + the resist surface, the copper foil surface or the silk surface. Transparent and translucent area are excluded. (e.g., glass epoxy material face)
	Warpage	Upward warp: 2 mm or less, downward warp: 2 mm or less, a warping gradient of 0.5 % or less, and a ridge line (in the transfer direction) with a height difference less than 1 mm. 
Functions	PCB warpage acceptable value detecting	If a measurement result exceeds the acceptable value, a warning is issued prior to placement to prevent the occurrence of quality defects. Acceptable warping gradient (%) can also be checked.
	Height control	Controls the placement height by measuring the height (warpage) of the whole PCB.
	Measurement data passing	The data measured by the first NPM-W2S/ W2 in line is passed to the downstream NPM-W2S/ W2*.  * If any machine other than NPM-W2S/ W2 is coupled together, no data passing is allowed. * For any PCB whose warp shape changes each time it is clamped, please consult us separately.
Measurement condition	Measurement height	PCB upper surface ±4 mm (A measurable range but not a PCB warpage acceptable range.)
	Measurement area	You need to set a measurement point at 5 mm inside from a slit in the edge of a PCB.
	Measurement points*4	Whole warp correction: more than 9 points (Up to 25 points/PCB) Pattern warp correction: more than 9 points/pattern (Up to 25 points/pattern)
Measurement time		3.0 s (750 × 510 mm in an optimal condition, with 9-point measurement)

*1 PCB warpage correction can correct only simple curved surfaces with a U-shaped cross-section.

Complicated warp geometry can be corrected as a combination of simple curved surfaces with the use of the pattern warp correction. You are recommended to use the pattern warp correction for PCBs with a slit or thin PCBs since they tend to have a complicated warp shape. (See the next page)

*2 Select the height sensor for the first NPM-W2 in line.


Select only the front side for single conveyor specifications and, both the front and rear side, for dual conveyor specification. The head configuration except for [placement head + placement head], PCB warpage correction does not function.

*3 When PCB thickness is 0.3 mm - 1.6 mm, prior verification is necessary.

*4 For the maximum number (total number of settings) of measurement points that can be set, please refer to "3.1 Basic specifications Production data."


■ PCB with a slit

It is unlikely that PCBs with a slit have smooth (even) curved surfaces because of their complicated warp geometries. In such a case, you are recommended to use the pattern warp correction. Pattern warp correction: corrects a warp at the measurement per pattern. (see the following figure)



■ Uncorrectable warp shape

e.g.) PCB with an undulating surface



4.8 LCR checker(Built-in type)


LCR checker (Built-in type) measures electrical properties of chip components to prevent error mounting caused by erroneous picking up of chip components.

FA PC receives component electrical properties measured with LCR checker and checks whether machine is within the acceptable range.

■ Standard configuration

FA PC keeps operation history on it.

When you use LCR checkers, you need to enter settings with DGS.



* LCR head is the target of calibration.

■ Overviews

Check

- Measures electrical properties of chip components and checks whether the values are within the set range.

Production stop

- When judged as NG, i.e. when electrical properties of chip components are out of the set range, productions will go in to error stop.

■ Standard specifications (1)

Items	Descriptions
Applicable heads	- Lightweight 16-nozzle head V3A, V2 12-nozzle head - Lightweight 8-nozzle head
Components	L:0.4 mm x W:0.2 mm ~ L:6.0 mm x W:6.0 mm, H:5.0 mm or lower • The conditions must be: In Dimension "L", chip components have electrodes on both sides and both sides have electrodes underside.
Measurable parameter range	Resistance(R : 0 Ω ~ 100 M Ω Condenser(C) : 1 pF ~ 100 μ F (Polar capacitor are not included) Inductor(L) : 4.7 nH ~ 1 mH Diode/Zener diode : 0 V ~ 3.4 V * Polarity evaluation only
Measurement accuracy	Resistance(R) : 0 Ω ~ 0.999 Ω $\pm$ 0.05 Ω 1 Ω ~ 9.999 M Ω $\pm$ 3 % 10 M Ω ~ 100 M Ω $\pm$ 5 % Condenser(C): 1 pF ~ 99.99 pF $\pm$ 5 % 100 pF ~ 4.699 μ F $\pm$ 10 % 4.7 μ F ~ 100 μ F $\pm$ 40 % ($\pm$ 10 % *) Inductor(L) : 4.7 nH ~ 1 mH $\pm$ 20 % ($\pm$ 10 % *) Diode/Zener diode : 0 V ~ 3.4 V $\pm$ 10 % * The values (in brackets) are the accuracy range of electrical capacitance, frequency response considered. (For details on how to calculate the percentage, refer to operational manuals)
Measurement tact	Less than 5 seconds / points (Picking up and collecting chip components are included)

■ Standard specifications (2)

Item	Description
Eligible nozzles	Standard-specification nozzles that match targeted measurement component size. * Nozzles that are used for LCR Checker Electrical Correction Lightweight 16-nozzle head V3A, V2, 12-nozzle head : 230CS nozzle Lightweight 8-nozzle head : 230C nozzle
Supply unit rules	Applies to tape feeder. When the rear of the supply unit is single tray feeder + 13-slot feeder base, only 13-slot feeder base is subject to LCR checks. LCR checks do not work when the rear of the supply unit is twin tray feeder specifications.
Placement mode	• Share mode • Independent mode * When a measurement unit is only on one table, chip components on the other table that does not have a measurement unit are NOT subject to LCR checks.
Determine electrical property constants (Resistance, Capacitance, Inductance, Forward voltage, Zener voltage)	This is a function that checks electrical property constants with LCR checkers in the process of production and that the constant values will be showed on the machine's screen or LNB. (constant check timing is as follows) • When picking up is for the first time after production start* • When picking up is for the first time after splicing is detected to go to a next tape • When picking up is for the first time after feeders are disconnected • When picking up is for the first time after chip components run short and production restarted • When teaching is ongoing and you are manually measuring values * When chip components are the same before and after changeover and went through electrical property checks at the previous production, the tests at this time are not performed.
Judge the measurement values	• This is a function to detect whether the values are not in acceptable range when the values are exceeded "Value Maximum Limit" or when the values are lower than "Value Minimum Limit", based on the values you defined for each chip component with DGS. • When the values are not in acceptable range, detection will be repeated until the maximum number of trials is reached to the entered "the number of attempts to retry". When the re-tried values are in acceptable range, measuring continues. • When all of the retrials are not in acceptable range, measuring will go in to error stop.
LCR checker Calibration features	• Placement position calibrations The NPM-W2 machine corrects coordinate axes of LCR checkers in X-direction and Y-direction with its head camera recognition functions, and coordinate axes in Z-direction with its nozzle height measuring functions. • Electrical Corrections There are two corrections to maintain measurement accuracy; Short Corrections and Open Corrections.
Storing measurement values	The values measured in the process of productions will be kept on LNB for 7 days; you can see the data and output them in a CSV format.

■ Preparations on your end

Items	Descriptions	Specifications
USB cables	USB cables are used for LAN settings of LCR meters.	USB 2.0 A-A Type A  Type A
0 Ω Resistance	0 Ω Resistance is used for LCR Checker Electrical Corrections.	Dimensions : $L \times W = 1.6 \text{ mm} \times 0.8 \text{ mm}$, $t = 0.5 \text{ mm}$ Resistance : 50 m Ω or lower *Recommended resistance Manufacturer model number : TLRZ1JTDD Manufacturer : KOA Speer (Model number : D0YBR0000045)

5. System software

5.1 Component Verification*1

This prevents components from being put wrongly. If you set components that are inconsistent with production data that are downloaded to the machine, interlock function of the machine operates to create automatically the mode where production cannot be continued. It is possible to customize order of barcode scanning and/or barcode definition, according to customers' operation.

Regarding the main body of the scanner, please choose between the wired scanner and the wireless scanner (PDA).

(We ask you to prepare a wireless scanner on your end)

Purchase of this option is required for the optional "Feeder Anywhere" feature.

*1 This is an option list of Component Verification.


When NPM-DX is in production line, please select "Material Verification" from "PanaCIM-EE Gen2"

Option		Hardware	Floor level control*2
Equipment	Component Verification : Wired scanner type	Wired scanner	Unsupported
PanaCIM-EE Gen2*3	Material verification : wireless scanner type	Wireless scanner (PDA) , Access point iLNB PC	Available

*2 It is impossible to control multiple lines in the floor and use modules like Material Control Module, Traceability Module etc.

*3 See PanaCIM-EE Gen2 Specifications for details.

■ System Configuration



* It is impossible to implement operation where the wired and wireless scanners (PDA) are used in combination.

■ Function List


Item		Description
Feeder Verification*1	Component verification at the time of preparation	Components are verified at the time of preparation.
	Component verification at the time of component exhaustion	Components are verified when they are replenished at the time of component exhaustion
	Component verification at the time of splicing	Components are verified at the time of splicing.
Periodic check		Components are checked at random time, such as time of shift change, etc. There's no need for stopping production while the periodic check is done.
Re-check	Re-check for feeder jam releasing	Re-check is done at the time of feeder jam releasing.
	Re-check for releasing splicing error detection	Re-check is done at the time of releasing splicing error detection.
	Re-check function for In-setting/removing of feeder	Re-check is done in the case where feeder insertion/removal is done due to some reasons while single stop occurs.
Automatic line selection		When you prepared a wireless scanner(PDA) on your end, you can choose a line in the GUI. The wireless scanners (PDA) on other lines can also be used.
Setting function	Defining verification flow (*This is a function that optionally defines scanning order of some 1D/ 2D codes which are attached to reels.)	Verification flow can be defined according to customers' operation. By entering code, which indicates type, into barcode, you can make setting for two modes: random mode which does not specify scanning order or sequential mode which specifies scanning order.
	Barcode setting	This defines barcode. This is applicable for complicated multi barcode. (Even in the case that one barcode includes multiple meanings, you can accomplish scanning by only one scan.)

*1 It does not support the component verification of the stick feeder.

■ Standard Specifications

Item	Description
Scan code	 <u>1D code(Barcode):</u> UPC/EAN/JAN, UCC/EAN 128, Code 39, Code 128, etc.
	 <u>2D code:</u> Maxicode, Data Matrix (ECC 200), QR code, etc.
Restrictions for code	Restrictions for code used for Part name, Lot name, Vendor name, and etc. ASCII alphanumeric and signs within 30 characters As for signs, only followings can be used: - + = , . _ @
Display language	English, Chinese, Japanese 1) Applicable for the display screen of the setting terminal on LWS

Standard Configuration


Item	Description	
Wired scanner	Main body of wired scanner	This is a unit for reading barcodes. Operation on two tables is made possible by one scanner. We recommend the main body of scanner to be installed alternately at both sides of front and rear. Please make purchase in accordance with your line configurations. 
	Scanner holder	This is a unit which holds scanner onto the machine.

5.2 Automatic Changeover


This supports changeovers (production data change and rail width change), minimizing the time loss of operation caused by product changes. In accordance with each customer's operation, selection can be made from following two types, "External scanner read type", and "Head read type".

■ System Configuration

External scanner read type



Head read type



Function List

Item		Description
Changeover function	External scanner read type	External scanner is installed on the first conveyor, and the scanner reads 1D/ 2D codes* ¹ on boards, automatically implementing changeovers.
	Head read type * With production data restrictions* ³	2D code* ¹ on boards is read by Head camera on the first NPM-W2, making it possible to implement automatic changeover.
Setting function	Barcode setting	This defines barcode. This is used to specify production data, and two types of method of specifying are available. • <u>Method of specifying character string</u> Method in which data extracted from barcode is character string, which corresponds to production data name on a one-to-one level. • <u>Method of specifying range</u> Method in which data extracted from barcode is numeric value, and its range corresponds to production data name on a one-to-one level.

*1 This option does not include printing function of 1D/ 2D code on PCBs.

*2 This option does not include printing function of 1D/ 2D code on papers.

*3 Board width cannot be adjusted. So, all data of board width must be common.
All data of 2D code coordinate, which is used for changeover, also must be common.
(As for the 2D code coordinate of splittable board, there's no need for the commonality.)


Standard Specifications

Item	Description
Readable code	External scanner read type  <u>1D code (Barcode):</u> CODE39, ITF, Industrial2of5, COOP2of5, NW-7, CODE128, EAN128, CODE93, JAN/EAN/UPC (supporting add-on), TriopticCode39, etc.  <u>2D code:</u> QR code, MicroQR, Data Matrix (ECC200), PDF417, MicroPDF, Maxicode, etc.
	Head read type  <u>2D code:</u> QR code, MicroQR, Data Matrix (ECC200) Max. dimension: 5 mm × 5 mm
Restrictions for code	Restrictions for code used for Board ID and Pattern ID ASCII alphanumeric and signs within 128 characters. As for signs, only followings can be used: - + = , . _ @
Display language	English, Chinese, Japanese (Applicable for display screen of setting terminal on LWS)

■ Standard Configuration

Item	Description
Hardware	External scanner read type • <u>External scanner unit</u> This is not supplied by us and for the purpose of 1D/ 2D code reading. One device is required for each lane in a line. Following is the scanner for which operation was confirmed by us. Please consult us when you use other scanners. Scanner: SR-510, SR-600, SR-600HA, SR-610, SR-750, SR-750HA, SR-1000, SR-2000 (KEYENCE CORPORATION) Communication unit: N-L1 (KEYENCE CORPORATION) ^{*1} ^{*1} The communication unit is required for SR-600, SR-600HA, SR-610. • <u>Conveyor</u> This conveyor is not supplied by us. This is located on the Head of the line. This must be in conformity with following specifications. 1) Availability of board waiting with stopper 2) Equipment of mechanism that can change width automatically or manually with a handle. 3) Availability of SMEMA communication*
	Head read type Head camera is used, so hardware is not needed.
	Planned form read type • <u>Main body of wired scanner</u> This is for reading barcode, and connected to first machine. One device is required for a line. Common use with component verification option (wired) is possible. • <u>Scanner holder</u> This is for placing the scanner on the machine. Common use with component verification option (wired) is possible.
License	A license is required for each machine. Please refer to "14. Regarding Licenses".

* LNB controls scanner through intervention in SMEMA communication.
TCP/IP is used to interconnect LNB and an external scanner, and LNB and a machine.
There is a timing chart of SMEMA communication below.
SMEMA communication between conveyor and machine must be in conformity with this timing chart.




5.3 Feeder Setup Navigator


It is a support tool to navigate efficient setup procedure. The tool factors in the amount of time it takes to perform and complete setup operations when estimating the time required for production and providing the operator with setup instructions. This will visualize and streamline setup operations during setup for a production line.

■ System Configuration

For support station (Component verification type)



For PanaCIM-EE (Material verification)



■ Function List

Item	Description
Production plan creation function	Based on the specified model, production volume and number of workers involved in the setup task, it creates a production plan that factors in the amount of time it takes to perform and complete the setup is created. The estimated time of completion of production can also be confirmed on a per-model basis.
Setup instruction display function	It displays setup tasks necessary for production of the next and following models. It permits you to check the status of the feeders being mounted on the machine in real time and the progress on the ongoing setup task, and also to perform a setup task on the machine in operation. In addition, one and the same view can be displayed in web browser on several different PCs or mobile terminals.

■ Standard Configuration

Item	Description
License	A license is required for each machine. Together with the license, select the options below. <u>Required</u> Support station box (Component verification type) <u>Choice (Select any of the following options)</u> 1) Component verification (License) + Support station: Component verification type (License) 2) PanaCIM-EE ready (License) Please refer to "14. Regarding Licenses".
PC	It is a PC used to display production plans and setup instructions. * Please prepare on your own. Can also be shared with NPM-DGS and support station PCs.

■ System Requirements

• Hardware specifications

Item	Specifications	Class
Main body	IBM PC/AT-compatible machine	Required
CPU	Intel® Core™2 Duo E6700 equivalent or greater	
Mother board	Fully compatible with IBM	
Graphic board	SXGA or higher Desk top region: 1 280 × 1 024 dot or more	
Memory	4 GB or more	
HDD	20 GB or more (NTFS file system)	
Optical drive	4x speed or faster of DVD drive To be used in installation	
Keyboard	English version: 101 keyboard Japanese version: 106 keyboard	Required
Mouse	Supported by your OS as standard	
Monitor	SXGA ready	
Printer	Supported by your OS	Recommended
Network card	100BASE-TX network card	Required
Display terminal	iOS11.0 or later、or、Android™ 4.3 or later Resolution : WUXGA or later	Recommended

• Software specifications

Item	Specifications	Class
OS	<PC> Microsoft® Windows® 11 Pro (64-bit version) Microsoft® Windows® 10 Pro (64-bit version) Microsoft® Windows Server® 2012 (64-bit version)	Required
	< Mobile terminal> iOS Safari : 11.0 and later versions (e.g. : since iOS 11.0) Android Chrome : 56 and later versions (e.g. : since Android™ 4.3)	Recommended
	Support Language	Required
	Framework	
	.Net Framework 4.7.2 or later	
Virus check	Virus Buster™ Program version 12.0 or later	Recommended

- Microsoft, Windows, and Windows Server are registered trademarks or trademarks of Microsoft Corporation in the United States.
- Intel and Intel Core are registered trademarks or trademarks of Intel Corporation in the United States.
- Virus Buster is a registered trademark or trademark of Trend Micro Incorporated.
- iOS is a registered trademark or trademark of Cisco Corporation
- Android is a registered trademark or trademark of Google Inc.


■ Constraint condition

Item	Description
Target feeder	Intelligent tape feeder, thin type single tape feeder, tray feeder *Only can display the setup instructions on tray feeder. Cannot check the status of the feeders in real time.
Target area	In-line setups (Setups or preparations inside the machine) Off-line setups (Feeder cart setups or preparations)
Other	When a product changeover is performed on one lane during the independent mode, both the first machine in line and the other lane in operation need to temporarily stop production.

5.4 Upper Communication

This is an interface which is in cooperation with customer's existing system. As standard interface is prepared, it's possible to intercommunicate necessary information. Depending on the purpose of customer's system, functions of "Event", "Component verification with other vendor's machine", and "Information for component management" can be used.

■ System Configuration



■ Function List

Item	Description	
Standard Interface	Event* ¹	This outputs machine's events in real time. e.g.) When you would like to construct a system which combines machine's events and displays machine's status in real time.
	Component verification with other vendor's machine	This intercommunicates with customer's component verification system. e.g.) When there is other vendor's machine in the floor, and you would like to construct a component verification system that functions in cooperation with the machine by setting our system.
	Information for component management	This outputs following two information regarding components. 1) component remaining information 2) Trace information Combined information of components* ² and boards* ³ is output. e.g.) When you would like to construct a system which controls component remaining in the whole floor by receiving component remaining information that is transmitted after production of every single board in real time.
Setting function	This sets network transmission.	

*1 This is a function that transmits information to the upper system at the timing of the machine's detection of disorders, such as occurrence of component exhaustion.

*2 Component information inputs, which are done by using function of component verification option or "component verification with other vendor's machine" of this option, are required.

*3 Board information inputs, which are done by using function of automatic changeover option, are required.

Standard Specifications

Item	Description	
Communication form	Socket communication form	Sockets are used for this communication. There is no over head caused by hard disc accesses. This communication can be used when the file sharing is prohibited.
	Text communication form	Windows file-sharing function is used for this communication. Technologically, it is easier to construct this form than that of socket communication, because text files, which were input/output to file-sharing area, are used. This communication is also suitable for debugging.
Communication format	XML form	
Communication cache	This makes it possible to receive events of late 3 hours at the time of reconnection after the occurrence of disconnection.	
Upper system connection	One upper system can be connected for one FA PC.	
Display language	English, Chinese, Japanese (Applicable for display screen of setting terminal on LWS)	

Standard Configuration

Item	Description
License	A license is required for each machine. Please refer to "14. Regarding Licenses."

5.5 Component Supply Navigator


This navigator can prevent short time breakdown in the production line and contribute to manpower saving. It optimizes the supply sequence to provide a shortest route without component shortage. The optimized supply sequence will be displayed as a best supply route on wireless scanner or the monitoring PC for each operator. Component Supply Navigator is included in the PanaCIM-EE Gen2 product architecture. For the details, see the PanaCIM-EE Gen2 Specifications.

5.6 Support station

Time loss caused by changeover is drastically reduced by using spare feeder carts or feeders, which you have, and by preparing for next products while the machine continues its operation.

This has two types: one of them only supplies power to feeder carts and feeders, and another one implements component verification in addition to the power supplying.

* Component verification type is required for the optional “Feeder Anywhere” feature.



Function List

Item	Description	
	Power supply type	Component verification type
Feeder cart preparation	This supplies power to feeder carts, enabling preparations for next products while the machine continues its operation.	This supplies power to feeder carts, enabling preparations for next products while the machine continues its operation. This has a navigation function like pointing out positions that require preparation.
Feeder preparation	This supplies power to feeders, enabling preparations for next products while the machine continues its operation.	This supplies power to feeders, enabling preparations for next products while the machine continues its operation. This has a navigation function like pointing out positions that require preparation.
Component verification	Not supported	This verifies components of next products.

* In NPM series, “Change Cart Preparation Unit” in CM series is not available.

■ Standard Configuration

Power supply type

Item	Description
Power supply unit*1 *2 	This supplies power to feeder carts and feeders. The following items are included in this unit. • Power supply unit Rated voltage : Single-phase, AC 100 V ~ 240 V Frequency : 50/ 60 Hz Rated capacity : 90 VA • Power supply cable to feeder • Power supply cable to feeder cart

Component verification type


Item	Description
Support station box*1 *2 	This supplies power to feeder carts and feeders and additionally verifies components. The following items are included in this unit. • Power supply unit Rated voltage : Single-phase, AC 100 V ~ 240 V Frequency : 50/ 60 Hz Rated capacity : 90 VA • Power supply cable to feeder • Power supply cable to feeder cart • Wired scanner • Scanner connecting cable * Select this option when PanaCIM-EE is used for off-line setup (component verification).
License	A license is required for each machine. Please refer to "14. Regarding Licenses." * The license is not required for off-line setup (component verification) using PanaCIM-EE.
Support station PC*3 	This is for verifying components. * This is not supplied by us.

*1 The electric source cable is not prepared by us. Regarding the connecting plug, please use the ones that are suitable for the following standards:

AC plug (IEC 60320 C13: 10 A/ 250 V)

*2 In NPM series, "Change Cart Preparation Unit" in CM series is not available.

*3 Software for the support station PC is included in NPM-W2 system software DVD-ROM.

Item	Description
Feeder setting Jig 	This is a jig dedicated for the purpose of setting feeders. Setting of one tape feeder of 8 mm to 104 mm is possible. (Two 8 mm or 12/ 16mm tape feeders or four thin type tape feeders* can also be set at a time.) * "Attachment for thin type tape feeder" is required to install thin type tape feeders.

■ Component verification type—Standard Specifications

Item	Description
Readable code	 <u>1D code (Barcode):</u> UPC/EAN/JAN, UCC/EAN 123, Code 39, Code 128, etc.  <u>2D code:</u> Maxicode, DataMatrix (ECC200), QR code, etc.
Restrictions for code	Restrictions for code used for Part name, Lot name, Vendor name, and etc. ASCII alphanumeric and signs within 30 characters As for signs, only followings can be used: - + = , . _ @
Display language	English, Chinese, Japanese

■ Component verification type—Support station PC

• Hardware Specifications (Required)

Item	Specification
Main body	IBM PC/AT compatible machine
Processor	1 GHz or faster with 2 or more cores on a compatible 64-bit processor or SoC (System-on-a-chip)
Mother board	IBM-fully-compatible machine
Graphic board	WXGA or higher Desk top region: 1 280 × 768 dot or more
Memory	4 GB or more
Storage	80 GB or more
Optical drive	DVD drive
Keyboard	English version: 101 keyboard Japanese version: 106 keyboard
Mouse	Supported by your OS as standard
Monitor	WXGA-compliant
LAN port	1000/100BASE-TX × 2

• Software Specifications (Required)

Item	Specification
OS	Microsoft® Windows® 11 Pro Microsoft® Windows® 10 Pro (64-bit version)
Support language	English, Chinese, Japanese


- Microsoft, Windows and Windows Vista are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Intel is a registered trademark or trademark of Intel Corporation in the United States.

5.7 APC system

With miniaturization of component size and high density packaging, variations in PCB size or solder printing position might cause misalignment between the positions of solder printing and the positions for components to be placed on a mounting machine, which will be a factor for defective placement or degradation of placement accuracy.

APC (Advanced Process Control) system reduces mounting defects arising from such misalignments of solder printing or part placement.

■ Overall configuration of APC system



■ Circles[O] indicate necessary licenses for APC system ready.

Function	License	Printer	Mounter (you need as many licenses as machines)
APC-FB	Inspection results feedback ready	○*	
APC-FF	APC system ready		○*
APC-MFB	APC-MFB2 system ready		○


* When solder inspection is conducted with SPI of inspection machines from other companies, you need as many "Interface software of the inspection machine from other companies" licenses as machines.
See "5.7.1.1 When you use SPI of inspection machine from other companies" for details.

The existing "APC-MFB system ready" supports to compensate only chip components having a size of ≤ 1005 .
"APC-MFB2 system ready" has expanded the scope of the components to be compensated.
See "5.7.2 APC-MFB" for details.

■ Feedback control (APC-FB) See specifications of printers for details.

Print position correction (Target machine: SP series connected with LNB)

- It analyzes measurement data of solder inspection and offset printing positions (X, Y, θ).




Mask cleaning (Target machine: SP series connected with LNB)

- According to the solder inspection result (blur, oozing, bridging, etc.), mask cleaning is performed.

■ Feed-forward control (APC-FF) See “5.7.1 APC-FF” for details.

Placement position correction (Target machine: NPM series, NPM-X series)


- Places components in the optimal positions based on the measured location of solder paste.
Mounting to appropriate position allows to make good use of self alignment effect in achieving high quality placement.



■ Mounter feedback control (APC-MFB) See “5.7.2 APC-MFB” for details.


Component placement position correction (Target machine: NPM series, NPM-X series)

- Compensate misalignments based on the AOI measurement results to place components.
Appropriately positioned placement provides stable quality after placed.



When APC-MFB is used with APC-FF, placement positions can be controlled and compensated before component inspections. (Target machine: Other companies' MFB-authorized AOI)



- Components are inspected based on compensated placement positions.



5.7.1 APC-FF

APC-FF ability to place components at appropriate positions based on SPI measurement results improves the quality after placed.

■ Basic specification

Items	Description	
Communication method	Ethernet communication	
Supported head	Lightweight 16-nozzle head V3A, V2, 12-nozzle head, Lightweight 8-nozzle head, 3-nozzle head V2, 2D inspection head	
Feed-forward control	Solder	Measure solder position and feed forward the offset amount of X direction (offset dx), Y direction (offset dy), and angle direction (offset dθ).
	Land	Measure land position and feed forward the offset amount of X direction (offset dx), Y direction (offset dy), and angle direction (offset dθ).
	Chip component  Package component 	

You can select SPI solder inspections for feedforward control (APC-FF) from the following options.

- When you use SPI of inspection machine from other companies : See 5.7.1.1 section
- When you use inspection heads : See 5.7.1.2 section

■ Effects

Mounting quality improvement^{*1}

- Bonding strength will be improved through reduction in defects, such as lifted, misaligned and missing, in miniature components (0402 or 0603 chips, etc.).
- Mounting defects arising from variations in the positions of the lands can be reduced. (Flexible or ceramic boards, PCBs to be transported via a carrier, etc.)
- Reduce the occurrence of voids on BGA/CSP to improve bonding reliability.
- The impact during component placement can be reduced so that cracking or chipping tendency of components will be decreased.

Cost reduction^{*1}

- Skipping the placement of components to NG coordinates or patterns will cut the cost associated with the loss of components. (2D inspection head standard feature)
- Land inspections before placement will cut the costs involved in prior PCB inspections or the process for marking NG patterns. (2D inspection head standard feature)

Enhanced productivity^{*1}

- For a PCB having a number of patterns, the PCB recognition time will be extended in proportion to the number of patterns.
Owing to the use of APC system, high precision placement of components can be achieved only by using the standard PCB recognition (AB-point recognition), thereby leading to enhanced productivity.

^{*1} We cannot assure you that these effects will work on all your product placements.

5.7.1.1 When you use SPI of inspection machine from other companies

This section explains basic specifications for the use of SPI of inspection machines from other companies.


■ Basic specification

Items	Descriptions
What to be compensated :	Depends on the functions of inspection machines from other companies
Solder, Component	
Number of components	Depends on the functions of inspection machines from other companies

■ Interface software of the inspection machine from other companies

This is interface software to enable APC system using a measurement data of inspection machine*¹ (solder inspection) from other companies.

This option (License) is required per equipment that receives APC-FF offset data. (In case of below, 3 licenses are required.) Select this option, together with "APC system-ready (License)" for the same number.



*¹ Target inspection machines need to satisfy the requirements of our specifications. For details, please contact us.

*² A dedicated PC needs to be placed between the inspection machine from other company and FA PC (LNB). Please prepare a PC, a HUB and LAN cables (LAN (1)-(4) shown in the figure above) by customers.

■ Inter-machine connection conditions

- SMEMA connection (BA and Ready signals) is essential for inter-machine connection. (NPM turns ON the Ready signal to the upstream machine (inspection machine or conveyor made by other company) after confirming the BA signal from the upstream machine.)
- Up to one conveyor can be placed between other company's inspection machine and NPM. Additionally, the number of PCBs that can wait on the conveyor is not more than one. Barcode operation control is required if you are likely to have more than two PCBs waited on the conveyor. Barcode reading specifications, and conveyor specifications for reading conform to the descriptions in the "Standard Specifications" and "Standard Configuration" paragraph of the "5.2 Automatic Changer" section. For details, please contact us.
- When NPM are connected via a machine, such as other company's inspection machine or conveyor, APC communication will fail to work properly.
- When you change an NPM-X upstream process from single lane to dual lane with a traverser (horizontal moving transfer equipment), you may need to remodel NPM-X about signals between machines. Contact us for the details.
- Connection conditions between machines vary when you also use iLNB or PanaCIM. Contact us for the details.

In case of using interface software of the inspection machine from other companies, please prepare the following hardware and software at customer side.

■ Hardware specifications

• Dedicated PC

Item		Specifications	Class
Main body		IBM PC/AT-compatible machine	Indispensable
	CPU	Intel® Core™2 Duo E6700 equivalent or greater	
	Mother board	Fully compatible with IBM	
	Serial I/O	Fully compatible with IBM	
	Graphic board	SXGA or higher Desk top region: 1 280 × 1 024 dot or more	
	Memory	2 GB or more	
	HDD	20 GB or more of available space (NTFS file system)	
	Optical drive	DVD drive To be used in installation	
Keyboard		English version: 101 keyboard Japanese version: 106 keyboard	Indispensable
Mouse		Supported by your OS as standard	
Monitor		SXGA or higher ready	
Network card		100BASE-T or greater	
Uninterruptible power supply (UPS)		Supported by your OS as standard	Recommended

• HUB and LAN cable

Item		Specifications	Class
HUB	Transfer rate	100BASE-T or greater	Indispensable
	Number of port	4 ports or more	
LAN cable		100BASE-T: UTP Cat 5 or larger (4 pieces)*	

* Please arrange appropriate length of LAN cables according to your installation environment as it varies depending on factory layout.

■ Software specifications

Item		Specifications	Class
OS		Microsoft® Windows® 11 Pro (64-bit version) Microsoft® Windows® 10 Pro (32-bit/ 64-bit version)	Indispensable
	Support language	English, Chinese, Japanese	
	Framework	Microsoft® .Net Framework 2.0, 3.0, or 3.5 shall be installed.	
Virus check		Virus Buster™ Program version 7.0 or later	Recommended

- Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
- Intel and Intel Core are registered trademarks or trademarks of Intel Corporation in the United States.
- Virus Buster is a registered trademark or trademark of Trend Micro Incorporated.

** Remarks **

- The hardware/OS should be prepared and installed by yourself.

5.7.1.2 When you use inspection heads

This section explains basic specifications for the use of inspection heads.


■ Basic specification

Items		Description	
Offset target		2D inspection head A (18 μm)	2D inspection head B (9 μm)
	Solder paste	<u>Chip components:</u> 0.1 × 0.15 mm or more (0603 [0201"] or more) <u>Package components:</u> φ0.15 mm or more	<u>Chip components:</u> 0.08 × 0.12 mm or more (0402 [01005"] or more) <u>Package components:</u> φ0.12 mm or more
	Compo-nents	Chips (0603 [0201"] or more), SOP, QFP (Larger than 0.4 mm pitch), BGA, CSP, aluminum electrolytic capacitors, trimmer potentiometers, trimmers, coils, connectors, network resistor, transistors, diodes, inductors, tantalum capacitors, cylindrical chip	Chips (0402 [01005"] or more), SOP, QFP (Larger than 0.3 mm pitch), BGA, CSP, aluminum electrolytic capacitors, trimmer potentiometers, trimmers, coils, connectors, network resistor, transistors, diodes, inductors, tantalum capacitors, cylindrical chip
Number of offset component		Max. 10 000 points/line (number of measuring solder: Max. 30 000 points/line)	

Component inspection position correction


Direct recognition of land positions where components are placed upon can support deformed PCB enabling components to be placed with high accuracy.

It is effective for flip chip which is placed with flux or solder transfer.



Land position is accurately measured through dedicated processing to seek the center of shape and dimension specified.

- Inspects components in the position based on the component placement position after offset.



* For details, refer to "4.6 Line configurations that includes a machine equipped with an inspection head."

* "APC system ready" licenses are required per equipment.

The applicable machines are the first one installed in line equipped with inspection head to generate APC-FF offset data and the one receives the APC-FF offset data.

* APC-FF ready equipment: NPM series, NPM-X series (mixed line supported)

If a line is made up with other equipment than the above, please contact us.

* Provide a distribution conveyor whose number of PCB stocks is ≤1. Contact us for more details.



* 03015 components are not eligible.

5.7.2 APC-MFB

APC-MFB (Advanced Process Control-Mounter Feed Back) compensates for misalignment based on the results of AOI inspection to stabilize the post-mounting quality.

Divided into categories focusing on nozzles, feeders, components, and mounting positions, the results of AOI inspection are presented as a process capability index. This helps variation management and supports appropriate response when the process varies.

■ Basic specification

Items			Description
	Communication method		Ethernet communication
	Supported head		Lightweight 16-nozzle head V3A, V2, 12-nozzle head, Lightweight 8-nozzle head, 3-nozzle head V2
	AOI		Applicable AOI for “APC-MFB2 system ready” • Please contact us to confirm the applicable makers. (NPM inspection head is excluded) • The AOI should be installed in line. • When APC-MFB is used with APC-FF, placement positions can be controlled and compensated before component inspections, and components are inspected based on the compensated placement positions. 
	System		About the applicable system version of NPM and AOI which support APC-MFB2 system ready, please contact the AOI maker or us.
	Placement mode		• Independent mode / Share mode • Single lane / Dual lane * When using the Automatic Changeover line, Update of MFB offset starts after production model agrees between NPM and AOI.
Components	Remarks		Production with APC-MFB offset is not applicable to NPM placed at the downstream process of AOI from other company because the system cannot receive mounting positions. (Example) Line configuration: Some equipment is not applicable for Production with APC-MFB offset 
	Type	APC-MFB2 Inspection target* APC-MFB Offset target	Chip components, lower electrode components, lead components (electronic components with a lead drawn out from one side are not included) (depend on the specification of AOI) When there are AOI measurement results and component placement uses nozzles, APC-MFB compensates for the placement positions of the targeted components for offset.
Number of offset component			Number of offset components depends on the specification of machines

*Differences in components to be measured under APC-MFB licenses (depend on the specification of AOI)

License	Components to be measured
「APC-MFB system ready」	Chip components having a size of ≤ 1005
「APC-MFB2 system ready」	chip components, lower electrode components, and lead components (electronic components with a lead drawn out from one side are not included)

- Licenses are necessary per equipment.
- “APC-MFB system ready” supports only NPM-D3.
- When you have equipment for “APC-MFB system ready” and have purchased its license, compensation of chip components having a size of ≤ 1005 is supported even if equipment for “APC-MFB2 system ready” for which you have purchased the license exist in a line.
- New purchase is available only for “APC-MFB2 license ready”.

* AOI recognition level and type of components where MFB could be applied

Type of components where MFB could be applied depends on the AOI recognition level of inspection machine manufactures.

AOI recognition level	Type of components where MFB could be applied
Not yet recognized	None(Cannot use MFB)
MFB-recognition	1005 chip components or chip components having size of under 1005
MFB2-recognition	All components (components with leads drawn out from one side, odd-shaped components, components with unmeasurable AOI leading position are not included)

■ Programming specification

This programming specification is for production data of NPM and AOI.

(NPM) : When using DGS, please put the circuit code (like R123) which is used in the AOI into the comments section of placement coordinate setting. Make sure there is no duplicate code in the same pattern.

(AOI) : Make sure the circuit code for component on PCB board is the same code which is set in the DGS.
(Including space, “ - “, etc.)

The numbering rule of pattern is same as NPM.

(Make sure the combination of pattern code and circuit code is the same one between NPM and AOI.)

■ System specification

Item		Description	
Increased line tact time of production (VS normal production)		- Line tact time under 50 s : less than 1.0 s - Line tact time over 50 s : less than 2%	
Functions	Mounting position MFB offset function*	Offset functions for mounter. - An offset function to correct the machine variation of each XY shaft, recognition unit, and nozzle angle. - An selection function to pick-up the components for calculating offset data.	
	Process variation management function	APC-MFB offset monitor display function	(1) Mounting points - Display the Cp/Cpk of each head. - Display the correction factor of each mounting point. (Top 20) (2) Unit - Cp/Cpk of each nozzle or angle. Correction factors - Cp/Cpk of each feeder, Correction factors - Cp/Cpk of each component, Correction factors - Cp/Cpk of each area, Correction factors (3) The correction factor of each nozzle of multi-recognition camera position. (4) The correction factor of XY shaft.
		Process variation warning function	(1) Manage CPk value of each head. (2) Check for Cp value falling of each unit.

* When using the mounting position MFB offset function, the effect of placement accuracy depends on solder conditions, chip shapes, and/or other conditions.


** Remarks **

- When using licenses for “APC-MFB2 system ready”, placement accuracy, applicable PCB size, the number of offset component and etc. are depend on the performance of AOI from other company.

■ Example of system configuration

When using APC-MFB system only

AOI takes misalignment measurements based on Component Placement Design coordinates. Misalignments are compensated through the AOI measurement results.




*1 Contact us for inspection machines (AOI) that support "APC-MFB2 system ready" licenses.


*2 "APC-MFB2 system ready" licenses are necessary per equipment.

When using APC-MFB in APC-FF Line.

AOI takes misalignment measurements based on Component Placement coordinates in light of the misalignments of printing positions. Misalignments are compensated through the AOI measurement results.



Apply APC-MFB offset based on Component Placement coordinates
in light of the misalignments of printing positions



*1 Contact us for inspection machines (AOI) that support “APC-MFB2 system ready” licenses.

*2 Licenses for APC-FF or APC-MFB are necessary per equipment.

- When using APC-FF/ FB functions in solder inspections with SPI from other companies, a dedicated PC (NIP: Interface software of the inspection machine from other companies described in “5.7.1.1”) is required.
- There is no need to prepare NIP if the equipment has our inspection head.

■ Effect

Maintain placement quality*

- Compensation based on AOI measurement results helps maintain the initial accuracy of facilities and provide stable quality after placed.
- Maintenance of placement accuracy reduces lifted electrodes or misalignments of small components.
- Maintenance of placement accuracy contributes to SMT with narrow pitches.
- Placement accuracy management divided into nozzles, feeders, components, and areas using Cp/Cpk helps observe the changes of Cp/Cpk, and a warning is shown when Cp exceeds the control value.
- Showing placement accuracy divided into nozzles, feeders, components, and areas using Cp/Cpk helps identify failures of nozzles, feeders, components, and/or areas.

Reduce cost*

- Maintenance of initial accuracy of facilities reduces failures arising from misalignments and offers loss cost savings and/or repair cost savings.
- Managing the changes of Cp/Cpk of nozzles provides maintenance at appropriate timing suitable for production lines.

* We cannot assure you that these effects will work on all your product placements.

** Remarks **

- APC-MFB offset is a function to feedback the mounting position of mounted parts measured with AOI to mounting machine, and does not guarantee placement accuracy.
- For APC-MFB offset, mounting machine and AOI from other company will do a network communication. It's necessary to establish the network connection of LNB and AOI and change a signal cable for APC-MFB offset when delivering the system.
*The signal cable between mounting machine and AOI uses the Board Available (BA) signal including a board request signal.

5.8 PCB information communication function (standard feature)


The first machine in the line performs mark recognition and then passes mark recognition data or information on to the downstream machines.

The use of the transferred data by the downstream machines can enable a shortening of the tact time.

■ Bad mark communication

Bad marks are recognized by the first machine in line, and then the bad mark recognition data is passed on to the downstream machines.

This enables the downstream machines to shorten the time required to recognize the bad marks.




* For connection with other company inspection machines, see the optional "Other Company Bad Mark Communication".

■ Pattern mark communication

The first machine in the line recognizes pattern marks and then passes correction value data on to the downstream machines.

This allows the downstream machines to recognize only master marks, which helps shorten the PCB recognition time.




* Discussion on an individual basis is necessary when receiving PCB data from machines other than NPM-X series or NPM-series, or when you use together with APC.
For details, please contact us.

5.8.1 When Receiving Bad Marks from Other Company Inspection Machines

■ Other Company Bad Mark Communication (License)

Communicates bad mark data using each PCB's bad mark data written to a LNB's shared folder from your systems, for example other company inspection machines. This reduces bad mark reading time on a stage at the head of a line.

■ System Configuration Example



■ Processing

1. Write each PCB's bad mark data to a LNB's shared folder in the given format.

【Sample】

```
<?xml version="1.0" encoding="UTF-8" ?>
<BoardInformation>
<Element>
<Lane>1</Lane>
<BoardNumber>123</BoardNumber>
<BoardBarcode>BARXXX</BoardBarcode>
<BadMark>010001110010010100010010101010101</BadMark>
</Element>
</BoardInformation>
```

2. Communicates bad mark data using bad mark data associated with PCB barcodes read with a mounter's head camera or an external scanner.

* Deletes bad mark data from oldest once gets accumulated more than 10 bad mark data in an LNB shared folder.

5.9 Automatic recovery function for pickup error

This function recovers the pickup / recognition error automatically in order to continue production without stoppage.

■ Function Summary

Pickup position teaching when pickup error occurs

This function enables the machine to automatically teach the pickup position when an error is detected.
After teaching is complete, machine will continue production.
With this function, line stop times will be reduced and the utilization can be improved.

The re-pickup of pickup error components

The most of large components are not available to automatically teach the pickup position, that the function "Pickup position teaching when pickup error occurs" is not applicable.

This function enables the machine to automatically re-pick up the error components without transferring.
If pickup is complete, machine will continue production.
With this function the pickup error times and line stop times will be reduced, the machine utilization can be improved.
Available components: 12 mm ~ Embossed tape.

1 mm ⇔ 2 mm, 2 mm ⇔ 4 mm Automatic pitch switching




When there are same components whose tape pitch is 1mm, 2mm and 4mm, and tape pitch at component supply is mixed, at the timing of tape switching(for example, at component supply, at splicing or when you cancel an error), it automatically calculates tape pitch in the process of automatic pickup position teaching and changes to the calculated pitch and continues production.

Automatic pitch switching conditions

Items	Description
Component data	With pickup position automatic teaching * There is component size limit.
Tape width	8 mm
Applicable tape	Paper
Supply pitch	1 mm ⇔ 2 mm、2 mm ⇔ 4 mm

5.10 Component inspection before pickup (Polarity)


This function recognizes the surface of a component captured by the head camera before picking it up from the tray or tape feeder, in order to prevent possible misloading through the polarity checks.

Misloading prevention This function detects the orientation of the components by recognizing any of the following features on the components to prevent misproduction.		
Polarity mark	Chamfering	Feature of luminosity
		

If the polarity is right, go on with pickup and mounting. But the polarity is wrong; it will show the picture with a single stop.

■ System Configuration

Recognition images are captured by the machine, and polarities are confirmed by the pre-pickup check server PC. Pre-pickup check PC is to be connected to one line (1 FA PC). (Recommended*¹) Besides, the pre-pickup check server PC can also be served as NPM-DGS client PC.)



*1 When the heads to be checked is 6 or less, up to 2 lines (2 FA PCs) can be connected.
In case of more than 6 heads, required check time may be longer.

■ Function List

Items	Description
Polarity inspection (Misloading prevention)	Inspection method: Select from among "Pattern matching", "Chamfering detection" and "Average luminance". 1) Select "Pattern matching" to recognize the polarity mark. 2) Select "Chamfering detection" to recognize the chamfering. 3) Select "Average luminance" to select any features of luminosity.
Setting when to check	Selectable from among "First component", "All components", and "Specified interval". Feeders capable of detecting the joint of taper components can perform component inspection of the joint position.
Handling components judged as NG	Components judged as NG can be handled by either of the following: 1) If the component is correct, press [OK] to pick it up. 2) If the component is wrong, change it to a correct one, and make check again.
Automatic pickup angle adjustment function	This function automatically corrects the angle in order to continue pickup and placement without stoppage.

■ Basic specifications

Items		Description			
Applicable components		Tray components, Tape feeder components			
Processing time required (including image pickup)* ¹		Approx. 1 s per component (1 FOV) Approx. 2 s (4 FOVs)			
Recognition requirements * ²					
Polarity mark	Mark type* ³	Processed or printed with ink			
	Mark shape				
		Circle	Square	Ring	Frame
Chamfering	Component shape	Must have a lead in four directions respectively and only one corner out of four corners must be chamfered.			
Feature of luminosity	Component shape	Must have one characteristics luminosity area at the position other than the center of the component.			

*¹ Time required may vary depending on the conditions, such as production data.

*² Recognition performance may be degraded if:

1) there is a soil, damage or foreign matter on the surface of the component

2) the working environment of the machine or designed shape of the pocket may affect the captured images

*³ Check result may not be satisfactory if the laser markings are low contrast image.

* Recognition check can be performed in advance by PSFS. Contact us for details.

■ Basic configuration

Item	Specification
Pre-pickup check (Polarity) license	A license is required for each machine.
Pre-pickup check server PC	PC used to run the pre-pickup check server software for polarity recognition. Hardware and software specification comply with those of the NPM-DGS. * Must be prepared by customer. * The pre-pickup check server PC can also be served as NPM-DGS client PC. (Recommended) The pre-pickup check server PC cannot be served as NPM-DGS server PC.


5.11 Pre-pickup Inspection(Char · 2D Recognition)

■ Overview


Recognizes the characters or 2D code on the surface of a component captured by the head camera immediately before picking it up from the tray or tape feeder, in order to prevent possible misloading and to support traceability.

Misloading prevention	Recognizes the part number to detect any wrong number, thus preventing wrong model from being produced.
Traceability support	Recognizes the manufacturing lot number to help ensure traceability.

Character Recognition



2D code Recognition




■ System configuration


Recognition images are captured by the machine, and characters or 2D codes are recognized by the pre-pickup check server PC. Pre-pickup check PC is to be connected to one line (1 FA PC). (Recommended*¹) Besides, the pre-pickup check server PC can also be served as NPM-DGS client PC.)

System configuration example

1. When check server PC is connected to one line



2. When check server PCs are connected to two line



*1 The following conditions should be met.

- Heads to be checked connectable to 1 check PC should be 6 heads or less in total.
- FA PC (LNB) connectable to 1 check server PC should be 2 FA PCs (2 lines) or less in total.

■ Function List

Item	Specification
Component verification (Misloading prevention)	Recognizes the string identifying the part number in the characters or 2D code in the preset area on the surface of the component, and compares it with the preset string to detect any wrong number.
Trace check (Traceability support)	Recognizes the string identifying the manufacturing lot number in the characters or 2D code in the preset area on the surface of the component.*1
Setting when to check	Selectable from among "First component", "All components", and "Specified interval". Feeders capable of detecting the joint of taper components can perform component inspection of the joint position.
Handling components judged as NG	Components judged as NG can be handled by either of the following: 1) If the component is correct, press [OK] to pick it up. 2) If the component is wrong, change it to a correct one, and make check again.

*1 Manufacturing lot numbers can be traced and managed by PanaCIM-EE. Contact us for details.

■ Basic specifications

Item			Description													
Applicable components			Tray components, Tape feeder components													
Verifiable characters			Max. 30 characters													
Traceable characters			Max. 30 characters													
Inspection processing time* ¹ (Component Verification + Trace Check)		1FOV	1.5 s or less													
		4FOV	2.5 s or less													
Recognition requirements* ²																
Characters	Recommended fonts		Sans-serif* ³ * Italic, dotted, and underlined characters are not supported.													
	Applicable characters		Numbers, Upper-case letters, Lower-case letters * Following lower-case letters are not supported: ' i ', ' j ', ' l '													
	Printing conditions	Printing method	Laser marking													
		Size (Width x Height)	≥0.5 mm x 0.8 mm													
		Letter thickness	≥0.1 mm													
		Letter spacing	≥0.1 mm	<table><tr><td>A</td><td>B</td><td>C</td><td>D</td><td>E</td><td>↓</td></tr><tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>↑</td></tr></table> Letter spacing→←	A	B	C	D	E	↓	1	2	3	4	5	↑
		A	B		C	D	E	↓								
1	2	3	4	5	↑											
Line spacing	≥0.1 mm															
2D code		Applicable codes		QR code, Micro QR code, Data Matrix (ECC200)												
Printing method	Printing method	Laser marking														
	Cell Size	≥0.15 mm														

*1 Inspection processing time may vary due to the following situations

- 1) Communication load on network
- 2) Running state of other applications on check server PC

*2 Recognition performance may decrease due to the following reasons:


- 1) Dirt, scratches, or foreign matter on the surface of the component.
- 2) Printing defects such as fading or dropouts
- 3) Captured image affected by the use environment of equipment, pocket shape design, etc.
- 4) Number of characters is fixed and similar letters may be printed on the same position:
(For example, letter "O" and number "0")

*3 Fonts have not been defined clearly since there are many similar fonts, and original fonts by laser marker manufactures also exist.
The proven samples of recognizable fonts are shown below for your reference.



We can evaluate the recognizability of fonts in advance. Contact us for details.

■ Basic configuration

Item	Description
Head camera LED light 2 	LED lighting for the head camera provided with additional LED for recognizing characters or 2D codes.
Tray feeder installation kit	Adjust bolt dedicated for pre-pickup check (Character • 2D recognition) Installation of the tray feeder uses adjust bolt.
Pre-pickup check (character/2D code recognition) license	License is required machine by machine.
Pre-pickup check server PC	PC used to run the pre-pickup check server software for polarity recognition. Hardware and software specification comply with those of the NPM-DGS. * To be prepared by the customer. * Can also be served as NPM-DGS client PC (Recommended). Note that it cannot be used as NPM-DGS server PC.
Image processing software license	License required to use the image processing software for character/2D code recognition. Must be installed on the pre-pickup check server PC. Insert the included USB dongle into the USB port to enable recognition. * Please purchase one license for the major equipment of the line.

5.12 Message board

This function can display different images^{*2} for a certain period of time^{*1} on touch panels that are not in active use. By using the inactive time of touch panels to display training information, work instructions and etc., training and handoff can be conducted smoothly.

*1 Display time can be changed for each equipment by customer.

*2 By downloading the images from LNB, the display content can be changed for each equipment.

■ Function Summary

The number of images

Each machine can display up to 10 different images.

The images can be set during production.

Error messages display first

If an error occurred in message board images displaying, the error messages will be displayed first.

5.13 Head diagnosis

With this function, errors can be prevented in advance, and a stable production can be ensured.

■ Function Summary

Air Leak Check (*3)

Under closed state, this function measures air- flow value when turn ON/OFF the valve.

Flow Sensor Zero Check

Measure the range of flow sensor.

Air Stuff Check

Under open state, this function measures air- flow value when turn ON/OFF the valve.

Z-axis /θ-axis Action Check

Measure the motor torque of Z-axis /θ-axis at high speed and low speed.

*3 Air leak checks require nozzle setting jigs (nozzles).

A nozzle setting jig and its quantities required on air leak checks depend on the types of nozzle heads. See the list below.

3-nozzle jig nozzle is a jig nozzle dedicated for head diagnosis and is the no-barcode nozzle only.


	Required quantity	No barcodes		With barcodes	
		Parts No.	Nozzle No.	Parts No.	Nozzle No.
Lightweight 16 nozzle head V3A, V2	16	N610148258AA	256CS	N610148260AA	256CSN
12 nozzle head	12				
Lightweight 8 nozzle head	8	N610140967AB	256C	N610140968AB	256CN
3 nozzle head V2	3	MTKU002588AA	DIAG	—	—

5.14 Remote operation


Remote operation function allows centralized collection of errors generated in the machines and offers remote-controlled recovery, reducing error recovery time and contributing to efficient capacity utilization and labor-saving. This provides a system where it detects errors when they occur and allows remote-controlled recovery. This centralized recovery system helps reduce “the need for operators to notice errors” and “the travel time to the targeted error machine”, thereby reducing error recovery time.

■ System configuration

Standard configuration



Centralized control



■ Function List

Item	Description
Remote operation function	Remote operation function offers remote-controlled operations to the screens and operation switches. This allows remote-controlled recovery operations of errors generated in the machine to resume productions. The function works only when the machine is in an automatic operation state.
Remote access function	Remote access function offers remote access to the screens. You can get the actual screen that shows how the machines are working and how on-site workers are operating.
Status monitor function	Status monitor function shows present errors that are subject to remote recovery of controlled lines. With this function, you can open the remote panel on which you can get the screen from a status monitor and operate it.
Event list function	Event list function lists the present error events of the controlled lines and shows whether those errors are subject to remote recovery. Present error event information contains when it happened and what it's like. You can open or close the remote panel on which you can get the screen from event lists and operate it.

■ Standard Configuration

Item	Description
License	Licenses are necessary per machine. For more details for licenses, see “14. License” .
PC	This is for remote access. Install remote access client software before use * We ask you to prepare it

■ System requirements

Computers Hardware specifications

Item	Specifications (primary PC)	Specifications (secondary PC)
Unit	IBM PC/AT compatible machine (We recommend primary PC be desktop PC)	
Processor	1 GHz or faster with 2 or more cores on a compatible 64-bit processor or SoC (System-on-a-chip)	
Mother board	Fully compatible with IBM	
Memory	8 GB or more	4 GB or more
Storage	100 GB or more	
Optical drive	DVD drive To be used in installation	
USB port	USB Type-A x 1 or more ports (when you use an option license)	—
Keyboard	English version: 101 keyboard Japanese version: 106 keyboard	
Mouse	Supported by your OS as standard	
Monitor	WXGA Supported, Desktop size : 1 280 x 768 dots or higher	
LAN port	100BASE-TX or faster x 1 port	

Computers Software specifications

Item	Specification	Notes
OS	Microsoft® Windows® 11 Professional Microsoft® Windows® 10 Professional (64 bit version)	Required
Display Language	Japanese, English, Chinese	—
Framework	Microsoft® .Net Framework 4.5.2 or later	—

- Microsoft, Windows and Windows Server are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

* Environmental requirements are based on Microsoft® Windows® 10 Professional.

* When you use anti-virus software or others, do not block the following port ranges.
(59 000 ~ 59 999)

Mobile devices Operation specification(Standards)

Operations specifications on remote control operations with a smartphone or a tablet(Android) are as follows.

Item	Specifications	Notes
OS	Android 9 ~ 11	Recommended
Devices	Resolution : 1 280 x 720 dots or higher (Operation tested devices are as follows) TOUGH BOOK FZ-S1 (Android 10) Galaxy Tab S7 (Android 11)	Some actions using devices other than those on left may vary.

IOS are not supported.

■ Constraints

Machine status		Remote access activation	Constraints and other notes	Notes
When machine is in an automatic operation state		Can activate	Working on machines always has priority.	When remote access is active and at the same time you operate a machine, working on the machine always has priority and is effective. You cannot resume remote access operations until working on the machines is finished. When safety covers were open, remote access operations are disabled until on-site workers resume productions.
	When there are errors			
When machine is NOT in an automatic operation state		Cannot activate	Read only Only on-site workers can operate machines, including start-up of the machines.	Before the start-up of machines, on-site workers must visually check whether the machines are operational.

5.15 Biometric authentication

With biometric authentication, you can connect it with external authentication devices that accept biometrics such as iris recognition or facial authentication and can access to a machine without having to enter a password with a keyboard.

■ Overviews

Authenticate

- Authenticates users with an external authentication device.
- (External authentication management system manages users)

Operation constraints

- Prevents access from unauthorized users.
- With an operator customized tool, you can set limitations by the user.


Trace

- Collects operation logs.

■ System configuration

Biometric authentication function checks who is using the machine with an external authentication management system, and send user information to iLNB.

iLNB changes authority for access based on user information.



■ Standard configuration

Item	Description
Machine software	Switches access authority based on user information identified with an external authentication system.
iLNB	FA PC (iLNB) *LNB needs individual basis supports. A license for E-Link (equipment control) is required. The license is required for each stage of a machine.
Biometric authentication license	Licenses are necessary per machine.
External authentication management system (external authentication device)	You need authentication management system that you can link to our authentication system. For the details, contact us. We do not take any responsibility or liability for personal information management on other company's biometric authentication system.

5.16 Mount complete position recognition

This option contains the following two functions.

Section	Functions
5.16.1	Mount complete position recognition function
5.16.2	Shield case warping inspection function before mounting

5.16.1 Mount complete position recognition function

Mount complete position recognition function measures the brightness of two areas of shielded components with a head camera and detects improper mountings from the brightness.

When detected an improper mounting, machine gets into single stop.

■ Overviews

Detect improper positions

- After all components were mounted, the head camera measures two areas' brightness per one component.
- When detected as a NG component, machine gets into single stop.

Show NG components

- When the function detected as a NG component, it lists NG components and automatically shows the list.

Teaching

- You can adjust the instructions of lamp value, areas, and threshold by the component about recognition points set on each component.

■ Standard specifications

Item	Description
PCB constraints	When PCB needs separate mounting, it does not activate this option.
PCB height constrains after mounting	When PCB has mounted tall components, it does not activate this option because the tall components may be the cause of interference.

■ Standard configuration

Item	Description
Mount complete position recognition option license	Licenses are necessary per machine.

5.16.2 Shield case warping inspection function before mounting

The machine checks shield case warping. When it detects components as warping, the components become disposal. The inspection before mounting prevents improper shield components from being mounted.

■ Overviews

Warping detection

- This function measures the characteristic points of shield cases and detects warped components. NG components become disposal.

Teaching

- Component recognition teaching function also detects warped components. When NG components were detected, it shows an error.



■ Components to be measured

In order to measure the floats or warping of shield cases, at least four heights of characteristic points must be measured.

Here are measurable characteristic points.

*Set a point on the same height surface to a characteristic point.

(Basically, we will receive samples and then decide whether to be able to detect or not after going through consideration and experiments)

Item	Description
Corners (Max 8 corners)	Size must be 2 mm or less and its corner R, roundness, must be maximum 0.8 mm. (e.g.) 
Pair lines * Non-parallel two lines combination (Max.8 pairs)	Size must be maximum 2 mm and its corner R, roundness, must be maximum 0.8 mm. (e.g.) 
Circles (Max 20 circles)	Size must be 2 mm or less.
Lead groups (Max 16 lead groups)	Lead group size must be 2 mm or less.

*When you would like to make sure of shield-warping detectable components, contact us at any time.

■ Standard configuration

Item	Description
Mount complete position recognition option license	Licenses are necessary per machine.
Multi recognition camera Type3	Multi recognition camera Type3 is necessary.

5.17 Tray 1 Pallet 10 Kind

This is a feature that uses tray units to achieve production by putting small volume components packaged in cut embossed tapes onto a pallet. You can put onto a pallet up to 10 kinds of components.

For example, you can use small volume components packaged in cut embossed tapes for trial production and/or small lot production.



(e.g.) Component Layout

■ Feature List




Items	Descriptions
Create Production Data	Uses DGS to create production data that it is up to 10 kinds of components onto 1 pallet.
Edit Production Data	Views/Edits the related layout data on the screen.
Teaching	Teaching about the related tray pickup positions on the screen.
Production	Based on the above production data, production is up to 10 kinds of components onto 1 pallet.
Component Shortage	Deals with component shortage by component type

■ Standard Configuration

Items	Descriptions
License	License is necessary by the machine. For License details, see "14. License".
Tray jig	We ask you to prepare a dedicated tray when you use this option.

■ Tray Jig Design Specification

Tray jig design specification basically conforms to “Tray Conditions” in the “4.3 Feeder Carriage Configuration” section.

Items	Descriptions
Component Layout	As shown below, put tape components parallel to PCB transfer direction on a jig. (We recommend that tray jig end face parallelism be 0.1 mm or smaller) 
Height	① When component height in all the components is equal to or lower than tray jig maximum height t1, the following formula about height difference of t1(max) and component minimum height t2(min) should be satisfied. $t1(\max) - t2(\min) \leq 6 \text{ mm}$  ② When there is a component higher than tray jig maximum height t1, the following formula about height difference of component maximum height t2(max) and component minimum height t2(min) should be satisfied. $t2(\max) - t2(\min) \leq 5 \text{ mm}$ 

■ Restrictions

- When this option is activated, the following features will be deactivated.
 - 1) Use tray supply side
 - 2) Tray outside comp collation
 - 3) Tray stock Auto Change
- This option does not work with Lightweight 16-nozzle head V3A.
- You cannot attach this option in some cases; it depends on your jigs or components.
For details about whether to be able to attach it, contact us.


5.18 LCR checker(Feeder shaped type)

LCR checker (Feeder shape type) measures electrical properties of chip components to prevent improper mounting caused by erroneous picking up of chip components.

■ Standard configuration

LCR checker measures electrical properties of chip components and FA PC checks whether the values are within normal limits. FA PC manages execution logs.

When you use LCR checkers, you need to enter settings with DGS



■ Overviews

Check

- Measures electrical properties of chip components and checks whether the values are within the set range.

Production stop

- When judged as NG, i.e. when electrical properties of chip components are out of the set range, productions will go in to error stop.

■ Standard specifications

Item	Description
Components	L:0.6mm x W:0.3mm x H:0.23mm ~ L:3.2mm x W:1.6mm x H:1.5mm • Square chip components (The conditions must be a state that conducts electricity; i.e. In Dimension "L", chip components have electrodes on both sides and both lateral faces have electrodes)
Measurable parameter range	Resistance(R) : 10 Ω ~ 100 M Ω Capacitors(C) : 10 pF ~ 100 μ F Inductors(L) : 1 μ H ~ 47 μ H * The above is a measurable range that has taken into account the use of LCR checker and variations in measurement accuracy. (For measurable range based solely on LCR checker, see the checker specifications)
Measurement accuracy	Resistance(R) : ± 10 % Capacitors(C): ± 10 % Inductors(L) : ± 10 % * The above accuracy is the maximum measurement accuracy variations when a machine installs and operates LCR checker. (For measurable range based solely on LCR checker, see the checker specifications) * In some cases, depending on electrical properties of components, they may not be eligible for measurement even measurement accuracy is within the values indicated above,
Eligible nozzles	Standard-specification nozzles that match targeted measurement component size * Nozzles for calibration when LCR checker is installed Lightweight 16 nozzle head V3A, 12 nozzle head, : 230CS nozzle Lightweight 8 nozzle head : 230C nozzle 3 nozzle head V2 : 1001 nozzle
Where to install checker	• You can install LCR checker on a place where tables have feeder supply units and tables have component recognition camera. (Installation fills up one slot of supply place)
Placement mode	• Share mode • Independent mode * When LCR checker is installed on one table of a 2-table beam machine, components supplied on the table not installing LCR checker are not eligible for LCR checking.

Standard configuration

Item	Description
LCR checker (Feeder shaped type) 	LCR checker (Feeder shaped type) is a tool that measures electrical properties of chip components.
LCR checker license	Licenses are necessary per machine.

5.19 Tray Pickup Positions Offset (Standard Specification)

Recognizes the place where trays are during production and revises pickup positions based on the recognized positions to prevent pickup errors.

■ What Is Recognized?

Head camera checks the following items to revise pickup positions.

Tray Corner Recognition	Scans diagonal 2 corners of a tray and revises pickup position.
Mark Recognition	Scans the specified 2 marks of a tray and revises pickup position.

■ Compatible Components

It applies to tray components, such as interposer components and long, narrow connector components.

*Does not apply to tape components.

*Does not apply to soft material trays that warping occurs when securing pallets .

■ Tray Data Setting



As to the following data, input accurate design data.


- Tray size (X, Y)
- Tray height
- 1st pickup
- Last Pickup
- Mark coordinates X*, Y*

*When it scans marks on a tray to revise.

■ Field of View

Here is an overview of the field of view that camera can image.

Where to Scan	Field of View Setting Example at Tray Corner Recognition
「Top Right/ Bottom Left」	 Field of View (Size: 7 mm × 7 mm) When it cannot fit on 1 field of view because of recognition are size, it sets more than one field of view automatically. Recognition Area At tray corner recognition, field of view captured is 4 places.
「Top Left/ Bottom Right」	



6. Other Standard Functions


6.1 Programming Functions

Data are created on NPM-DGS, the data creating system. The production data created on NPM-DGS will be downloaded to the machine via FA PC. Some data, however, can be modified on the machine. The data modified on the machine and what was taught will be retained and reusable.

* The hardware for NPM-DGS should be prepared by yourself. (NPM-DGS should be purchased separately.)

Regarding the license in NPM-DGS and in the option of NPM-DGS, a license is required for each machine, so you need to purchase license as many as the number of the machine you have.

For details about NPM-DGS, please refer to "NPM-DGS Specification."



6.2 Signal Tower

Color of signal tower and lighting standard


Standard: Horizontal mounting 1 514 mm from floor (Blue or Red) Vertical mounting is also possible. The height is 1 629 mm above the floor. 1 629 mm from floor (Blue or Red)	Signal Color	Classification	Lighting Standard
	Red	Emergency stop error	• Trouble in shafts of motors, etc. • Drop in air pressure • Trouble in PCB supports • Head trouble • Tape trouble ,and etc.
	Yellow	Single stop error	• Pickup error • Placement error • PCB transfer error • Component run out • Nozzle change error ,and etc.
	Green	In operation	Electric source ON (e.g., in automatic operation) (This, however, is off while red or yellow is blinking.)
	Blue or Red	Blue is lighted up on the machine that becomes bottleneck –the machine that requires longest cycle– among the machines coupled. Red is lighted up when the emergency stop switch is pushed.	

* Lighting specifications are programmable.

7. PCB Design Standard

7.1 PCB Specifications

■ Single conveyor specification




Item	Specifications
PCB dimensions	50 × 50 mm ~ 750 × 550 mm * Two PCBs can be clamped when PCB length is up to 350 mm.
Placement and inspection area	50 × 44 mm ~ 750 × 544 mm * For more information on the dispensing area, see "4.4 Dispensing area limitations."
PCB thickness	0.3 mm ~ 8.0 mm
PCB mass	3.0 kg or less* ¹
Permissible PCB warpage	Max. 0.5 mm PCB section Max. 0.5 mm
Conditions of PCB before placement	Lightweight 16-nozzle head V3A: 6.5 mm 12-nozzle head: 6.5 mm Lightweight 8-nozzle head: 12 mm 3-nozzle head V2: 30 mm Dispensing head: 28 mm Area where any components should not be present Support pin*² (Please leave 2 mm or more between this and back side components.)

*¹ When mass of PCB (including carrier mass) exceeds 3.0 kg, please consult us separately.

*² When an "automatic replacement of the support pins" is used, the support pin shape and pin configuration conditions are differ. For details, please refer to "9. Option: Automatic replacement of the support pins."

* For ceramic PCBs, please consult us.

■ Dual conveyor specification



Numerical value in (): For single lane mode



Item	Specifications
PCB dimensions	Dual lane mode : 50 × 50 mm ~ 750 × 260 mm Single lane mode* ¹ : 50 × 50 mm ~ 750 × 510 mm * Two PCBs can be clamped when PCB length is up to 350 mm. (The two PCBs clamping is not done when share mode is selected in dual lane mode.)
Placement and inspection area	Dual lane mode : 50 × 44 mm ~ 750 × 254 mm Single lane mode* ¹ : 50 × 44 mm ~ 750 × 504 mm * For more information on the dispensing area, see “4.4 Dispensing area limitations.”
PCB thickness	0.3 mm ~ 8.0 mm
PCB mass	3.0 kg or less* ²
Permissible PCB warpage	Max. 0.5 mm PCB section Max. 0.5 mm
Conditions of PCB before placement	Lightweight 16-nozzle head V3A: 6.5 mm 12-nozzle head: 6.5 mm Lightweight 8-nozzle head: 12 mm 3-nozzle head V2: 30 mm Dispensing head: 28 mm Area where any components should not be present Support pin*³ (Please leave 2 mm or more between this and back side components.)

*¹ When production is implemented in a single lane mode, the optional PCB support block that supports single lane mode is needed.

*² When mass of PCB (including carrier mass) exceeds 3.0 kg, please consult us separately.

*³ When an “automatic replacement of the support pins” is used, the support pin shape and pin configuration conditions are differ.
For details, please refer to “9. Option: Automatic replacement of the support pins.”


* For ceramic PCBs, please consult us.

Item	Specifications												
PCB notch condition	PCB notch dimensions should meet the following two conditions.												
Condition A	PCB notch dimensions should meet the following conditions.  <table border="1"> <thead> <tr> <th>L</th><th>L1</th></tr> </thead> <tbody> <tr> <td>$50 \text{ mm} \leq L \leq 350 \text{ mm}$</td><td>Less than $L/4$</td></tr> <tr> <td>$350 \text{ mm} < L \leq 750 \text{ mm}$</td><td>Whichever is smaller, $L/4$ or 100 mm.</td></tr> </tbody> </table> <table border="1"> <thead> <tr> <th>W</th><th>W1</th></tr> </thead> <tbody> <tr> <td>$50 \text{ mm} \leq W \leq 260 \text{ mm}$</td><td>Whichever is smaller, $W/3$ or 30 mm.</td></tr> <tr> <td>$260 \text{ mm} < W \leq 550 \text{ mm}$</td><td>Please consult us.</td></tr> </tbody> </table> * The above is when PCB thickness is 1.6 mm and over. When PCB thickness is thinner than 1.6 mm, contact us.	L	L1	$50 \text{ mm} \leq L \leq 350 \text{ mm}$	Less than $L/4$	$350 \text{ mm} < L \leq 750 \text{ mm}$	Whichever is smaller, $L/4$ or 100 mm.	W	W1	$50 \text{ mm} \leq W \leq 260 \text{ mm}$	Whichever is smaller, $W/3$ or 30 mm.	$260 \text{ mm} < W \leq 550 \text{ mm}$	Please consult us.
L	L1												
$50 \text{ mm} \leq L \leq 350 \text{ mm}$	Less than $L/4$												
$350 \text{ mm} < L \leq 750 \text{ mm}$	Whichever is smaller, $L/4$ or 100 mm.												
W	W1												
$50 \text{ mm} \leq W \leq 260 \text{ mm}$	Whichever is smaller, $W/3$ or 30 mm.												
$260 \text{ mm} < W \leq 550 \text{ mm}$	Please consult us.												
Condition B	There should be no cutout (including slit) in  of the drawing below.  * The drawing presented above is based on the front reference. For the back reference, the reference rail will be located at the back.												
Condition for component protruding from the edge face of PCB	Please consult us.												


7.2 Recognition Mark

PCB needs two PCB recognition marks at its opposite corners.

■ PCB Recognition Mark Specifications

Standard Mark Shapes and Dimensions	Standard Mark Shapes	Dimensions
	○	φ0.5 mm ~ φ1.6 mm
	△ (Equilateral triangle)	Length of one side: 0.5 mm ~ 1.6 mm
	□	Length and width: 0.5 mm ~ 1.6 mm
	+	Length and width: 0.5 mm ~ 1.6 mm (Line width: 0.3 mm or more)
	Length and width means the dimensions of the quadrangle circumscribing the mark.	
Mark Materials and Circuit Pattern	Because PCB recognition correction is based on the positional relationship between the marks and the circuit pattern (conductor pattern), the marks must be made in the same process and of the same materials as those of the circuit pattern from the viewpoint of correction accuracy.	
Image Conditions of Mark Materials and PCB Base	Because, basically, mark recognition process is carried out based on the intensity difference of reflected light, a fixed contrast is required between the mark materials and the PCB base. This difference varies significantly depending on the plating condition, oxidation condition, surface height, unevenness, degree of mirroring, coating, or disturbance light; therefore, the assessment of the marks is required beforehand.	
Mark Dimensions and Background	Noninterference area of larger than a certain dimension is required outside of the mark.  Noninterference area $a \geq 0.2 \text{ mm or more}$ Not all the marks are black.	

7.3 PCB waiting condition


PCB length: L	Description
$50 \text{ mm} \leq L$ $\leq 220 \text{ mm}^{*1}$	 Placement position^{*2} Waiting PCB Placement position^{*2} A piece of PCB can wait in both the upstream and downstream (total of two pieces).

*1 If the PCB length exceeds 220 mm, please contact us.

*2 When doing the independent mounting in dual lane mode.

In the alternate mounting mode, the upstream mounting position will be PCB's waiting position.

8. Standard Machine Configuration

Item	Description	Quantity
Main body		1 set
Accessories	System disk • Machine system, Recognition system, and LNB system (DVD-ROM) • Machine parameter SD card • Install system SD card • Password-changing SD card	1 set each
	Manual Parts List Control wiring diagram	1 set/Line

9. Options

Options are classified as follows.

Category	Description
Factory	These options need to be supported when the machine is being manufactured before shipment.
On-site	These options can be added after the machine has been delivered. However, a construction work is required on the spot.
Customer	These options can be added after the machine has been delivered. A construction work on the spot is not required.

Category	Table	Whole machine
	Can be supported for each table.	Supported as a whole of machine.

* Depending on user's machine specification, the manufacturing No., etc., some options may not fit the above classification.
For details, please consult us before purchasing the machine.

Please select options that answer your purposes.



No.	Purpose / Feature	Option name	Category
A	1 To select required options.	• FA PC • HUB	On-site -
		• Single conveyor • Dual conveyor	Factory Whole machine
		• Upstream extension conveyor (L=300 mm) • Downstream extension conveyor (L=300 mm)	On-site -
	2 To select a component recognition unit suitable for the intended use.	• Multi-recognition camera: Type 1/ 2/ 3 • Side lighting	On-site Table
	3 To set the PCB transfer height at 930 mm/ 950 mm above the floor.	• Support for 930 mm transfer line	Factory -
		• Support for 950 mm transfer line	




No.	Purpose / Feature	Option name	Category	
B	1 To select the nozzle in accordance with the production pattern.	• Nozzle • Storage nozzle case	Customer	-
	2 To select the tape feeder in accordance with the production pattern.	• Intelligent tape feeder	Customer	-
	3 To use thin type tape feeder.	• 4 mm thin type single tape feeder • 8 mm thin type single tape feeder • Attachment for thin type tape feeder • Power connector for thin type tape feeder • Handle for 4 mm thin type tape feeder • Reel holder for 4 mm thin type tape feeder	Customer	-
	4 To eliminate the tape splicing work. To reduce the feeder setup time.	• 8 mm thin type auto load feeder • Auto load feeder common attachment	Customer	-
	5 To select the stick feeder in accordance with the production pattern.	• Single stick feeder • Guide block (For Single stick feeder) • 3-lot stick feeder • Guide block (For 3-lot stick feeder)	Customer	-
	6 To select the stackable stick feeder in accordance with the production pattern.	• Stackable stick feeder (S) • S, M, L size pusher for S type • Stackable stick feeder (L) • S, M, L, LL, LLL size pusher for L type	Customer	-
		• Air Supply Unit for Feeder	On-site	Table
	7 To manage and store tape feeders.	• Tape feeder stand	Customer	-
	8 To manage and store stackable stick feeder. To prepare in advance.	• Feeder stand • Power and air supply unit (For stand)	Customer	-
	9 To prepare for the replacement of a support pin.	• PCB support block • Support pin setting jig • Additional support pins	Customer	-
	10 To replace the support pins automatically.	• Automatic replacement of support pins	On-site	Whole machine
		• Nozzle for support pin changeover • Support pin (For automatic replacement)	Customer	-
	11 To prepare feeders in advance and change them collectively.	• Feeder cart	Customer	-
	12 To place tray-feeding components.	• Single tray feeder • Twin tray feeder	Factory	-
		• Additional tray magazine • Additional tray pallet • Additional components-ejection tray • Pallet for vacuum-molded-tray	Customer	-
	13 To improve the workability of tape splicing.	• Splicing cart	Customer	-
	14 To mount thin embossed tape components (Feeding holes become deformed when tape thickness is equivalent to 0.2mm or thinner)	• 8 mm double feeder (Thin embossed tape ready)	Customer	-

No.	Purpose / Feature	Option name	Category	
C	1	• Spare placement head • Spare nozzle changer	Customer	Table
		• Spare multi-recognition camera: Type 1/ 2/ 3 • Spare side lighting	On-site	Table
	2	• Height sensor	On-site	Table
		• Height sensor teaching jig	Customer	-
	3	• Independent changeover supporting unit	Factory	Table
	4	• ±0.025 mm placement support • 03015 placement support	Factory	Table
	5	• NG-components ejection conveyor	Customer	Table
	6	• No Head attachment • Safety cover	Customer	-
	7	• Head stand (For two Heads)	Customer	-
	8	• Support station	On-site	-
		• Feeder setting jig • Attachment for thin type tape feeder • Power connector for thin type tape feeder	Customer	-
	9	• PanaCIM-EE ready (License)	On-site	-
	10	• iLNB ready (License)	On-site	-
	11	• Automatic changeover (License)	On-site	-
	12	• Component verification (License)	On-site	-
		• Wired scanner	Factory	Table
		• Scanner holder	On-site	Whole machine
	13	• Feeder Setup Navigator (License)	On-site	-
	14	• Upper communication (License)	Customer	-
	15	• Component verification (License) • Support station: Component verification type	On-site	-
	16	• Spare 2D inspection head • Inspection head support unit	On-site	Table
		• Safety cover	Customer	Table
	17	• APC system ready (License)	Customer	-
	18	• Interface software of the inspection machine from other companies (License) • APC system ready (License)	On-site	-
			Customer	-
	19	• APC-MFB2 system ready (License)	Customer	-
	20	• Spare dispensing head	Customer	Table
		• Dispensing Nozzle	Customer	-
		• Spare dummy dispensing unit • Spare wiping station • Safety cover	Customer	Table
		• Jig kit for accuracy verification • Spare screw unit	Customer	-
	21	• Multi-functional transfer unit • Coating thickness gauge	Customer	-
		• Air supply unit for the feeder	On-site	Table
	22	• Remote operation (License)	On-site	
	23	• Biometrical authentication (License)	On-site	-
	24	• Lightweight 16-nozzle head constant mount load control (License)	On-site	-
	25	• Lightweight 16-nozzle head transfer (License)	On-site	-
	26	• Load checker	Factory	-
	27	• Pre-pickup Inspection (Char/2D) (License)	Factory	-
	28	• Multi-recognition camera PIP lighting	Factory	-
	29	• AOI info display function (License)	On-site	-


No.	Purpose / Feature	Option name	Category	
C	30 To see whether electrical properties of components is within a predefined range before they are going to be mounted	•LCR Checker(Feeder shaped type) (License) •LCR Checker(Built-in type)	On-site	-
	31 To do simple test for checking shield component conditions after mounting.	•Mount complete position recognition (License)	Customer	-
	32 To do simple test for checking shield component conditions before mounting.	•Mount complete position recognition (License)	Customer	-
	33 To connect the factory-side plumbing to equipment to enable primary air connecting	• Primary air hose unit	Customer	-
	34 To use large reels	• Separator for feeder cart	Customer	-
	35 To use small volume components packaged in the cut tapes and do mounting for production trial and small lot production	•Tray 1 Pallet 10 Kind (License)	Customer	
	36 To increase mount points and patterns	•Extend Mount points (50 000 points, 8 000 patterns) (License)	Customer	
	37 To extend the height scope of mounting components	•Tall Component mount (License)	Customer	
	38 To mount large heavy components	•Large heavy component mount (License)	Customer	
	39 To communicate bad marks with other company machines	•Other Company Bad Mark Communication (License)	Customer	
	40 To perform polarity test of tray components and tape feeder components right before pickup.	•Pre-pickup test (polarity) (License)	Customer	
	41 Automatic recovery when pickup error or recognition error occurs and to continue production	• Pickup error automatic recovery (License)	Customer	
	42 To display a chosen image when you haven't used touch panel for a certain period.	• Message board (License)	Customer	
	43 Visual control of placement head conditions and to prevent troubles.	• Head Diagnosis (License)	Customer	




No.	Purpose / Feature	Option name	Category	
D	1 To keep the machine condition in regular maintenance.	• Greasing set • Maintenance jig • Nozzle holder cleaning jig	Customer	-
	2 To calibrate as needed.	• Jig kit for accuracy verification • Standard calibration jig kit • Jig kit for adjusting the main body • Plane calibration jig	Customer	-
	3 Required for exchanging/removing the Head.	• Unit exchanging tool	Customer	-
	4 To maintain the nozzle head automatically.	• Head maintenance unit • Air supply connection kit • Side filter • Bottom filter • Additional nozzle holder pallet	Customer	
	5 To splice the parts tape automatically	• Automatic tape splicing unit • Splicing tape • Battery box (Including connection cable) • Charge Terminal • Rubbish box • Tape cutting jig	Customer	
		• Battery • Battery Charger	Customer	
	6 To maintain the tape feeder automatically	• Feeder maintenance unit • Master jig • Attachment for thin type single feeder • Thin type single feeder master jig • Auto load feeder jig tapes	Customer	-

A-1	Selection of required options
On-site FA PC HUB	
- Always required for the NPM-W2 line. (a type/line) - For more information, please refer to "4.5 Line configuration."	
Factory	☐ Whole machine
Single conveyor	
This is a single lane conveyor that transfers PCBs and fixes them at each stop position. * PCB support block and support pin is not attached.	
Factory	☐ Whole machine
Dual conveyor	
- This is a dual lane conveyor that transfers PCBs and fixes them at each stop position. - In dual conveyor specification, you can exchange PCBs at one lane while continuing component placement at another lane, eliminating the PCB exchange time, resulting in enhanced productivity. - You can produce one product type PCBs using both lanes and also produce two different product types PCBs using two lanes for the different production from one another. * PCB support block and support pin is not attached.	
On-site Upstream extension conveyor (L=300 mm): Single lane Upstream extension conveyor (L=300 mm): Dual lane	
- Please be sure to select it for the first equipment of the NPM-W2 to ensure the safety of the transfer opening. - The PCB of 220 mm or more in length is allowed to standby. (Max. L 510 mm) - If the extension conveyor is installed between the NPM-W2s, the PCB of max. 750 mm in length is allowed to standby.	
On-site Downstream extension conveyor (L=300 mm): Single lane Downstream extension conveyor (L=300 mm): Dual lane	
- Please be sure to select it for the last equipment of the NPM-W2 to ensure the safety of the transfer opening. - The PCB of 220 mm or more in length is allowed to standby. (Max. L 510 mm)	

A-2	To select a component recognition unit suitable for the intended use.
On-site ☐ Table ☐	Multi-recognition camera: Type 1 
	• The position in picking up the chip and the angle deviation are corrected. • Please be sure to select it for the table where the placement head is selected. • Please refer to "4.7 Recognition Unit Configuration" for details.
On-site ☐ Table ☐	Multi-recognition camera: Type 2 (Type 1 + Component thickness measurement) 
	• A component thickness measurement function will be added to "Type 1." • This provides component thickness measurement (added to chip data entry and reflected in placement height), component's standing/tilted standing is detected, flip of Tr/ Di is detected, and nozzle tip is checked. • This supports each Placement head. • Please refer to "4.7 Recognition Unit Configuration" for details.
On-site ☐ Table ☐	Multi-recognition camera: Type 3 (Type 2 + 3D-measurement function) 
	• A 3D-measurement function will be added to "Type 2." • Detects coplanarity(flatness) and XY-direction positions of all the leads in QFP/SOP, and presence or absence of all the balls, and partially broken balls in its shape in BGA/CSP and other packages. • This supports each Placement head. (Multi-recognition camera Type3 comes with side lighting) • Please refer to "4.7 Recognition Unit Configuration" for details.
On-site ☐ Table ☐	Side lighting 
	• This is required for bump recognition of the BGA/ CSP. (Exclusive to multi-recognition camera) • Multi-recognition camera Type3 comes with side lighting.

* Multi-recognition camera is exclusive to NPM-W2S/W2, NPM-D3A/ D3 and NPM-TT2.

A-3	To set the PCB transfer height at 930 mm/ 950 mm above the floor.
Factory	Support for 930 mm transfer line (Adjustable range: 920 mm ~ 950 mm) Support for 950 mm transfer line (Adjustable range: 940 mm ~ 970 mm) The standard height of the PCB transfer line is 900 mm to 920 mm above the floor.
B-1	To select the nozzle in accordance with the production pattern.
Customer	Nozzle - Please refer to "4.2 Nozzle Configuration" for details. - Wrong nozzle setup can be detected by nozzle No. verification with 2D code for the nozzles which include "N" in their nozzle No. - For information about the special nozzles, please contact us. - The nozzles are compatible with CM602, CM402/ DT401 series, CM232, CM212, CM101, NPM series, and NPM-X series.
Customer	Storage nozzle case  - This case, which is made of plastic, is manageable because it can be checked for its contents from outside. - The one for 16-/ 12-nozzle head, for 8-nozzle head (Less than nozzle diameter $\phi 5$ mm) can accommodate 50 nozzles. - The one for 8-nozzle head, for 3-/ 2-nozzle head (Nozzle diameter $\phi 5$ mm or more) can accommodate 21 nozzles. - The nozzle case is compatible with AM100, CM602, CM402/ DT401 series, CM232, CM212, CM101, NPM series, and NPM-X series.
B-2	To select the tape feeder in accordance with the production pattern.
Customer	Intelligent tape feeder - Please refer to "4.4 Feeder Carriage Configuration" for details. - The tape feeder is compatible with AM100, CM602, CM402/ DT401 series, CM232, CM212, CM101, NPM series, and NPM-X series.

B-3	To use thin type tape feeder.
Customer	4 mm thin type single tape feeder (No detection sensor) 8 mm thin type single tape feeder
	• Please refer to “4.4 Feeder Carriage Configuration” for details. • Not available for CM602, CM402/ DT401 series, CM232, CM212, and CM101. * As for the inspection of a thin type tape feeder by IFCU, "Master attachment for thin type tape feeder (option)" is required.
Customer	Attachment for thin type tape feeder 
	• One piece is required per slot when you attach a thin type tape feeder. Two thin type tape feeders can be attached to each slot. • This is required even when you use a “Feeder setting jig” in offline setting. * A dedicated attachment for 4mm/ 8mm thin type tape feeder. (This attachment cannot be used on auto load feeder.)
Customer	Power connector for thin type tape feeder 
	• Required to directly supply electricity to thin type tape feeders (at the time of preparation, etc.). • Used by connecting to the power cable for feeders, which comes with feeder carts (or 13-slot feeder base). It can also be connected to the feeder power cable of the support station. • When power to thin type tape feeders is supplied through “Attachment for thin type tape feeders”, this option is not required. (Use a standard type power cable for feeders.)
Customer	Handle for 4 mm thin type tape feeder Reel holder for 4 mm thin type tape feeder 
	• <u>Handle for 4 mm thin type tape feeder</u> This handle is attached to tape feeder. To improve the usability of setting and carrying. • <u>Reel holder for 4 mm thin type tape feeder</u> This reel holder is integrated in tape feeder. One reel can be set in.

B-4

To eliminate the tape splicing work.
To reduce the feeder setup time.

Customer**8 mm thin type auto load feeder**


- This is a thin type feeder materialized automatic component tape setup.
The off-line setup time can be drastically reduced by the simple work of inserting a tape, then pressing the “ Send ” button. (Approx. 30s/reel ⇒Approx. 15s/reel)
- This auto load feeder can also use a short cut tape (longer than 120mm).
- The ‘Tape guide’ is different in each size. (Same feeder body)
Depending on the component size, please select from the following types.

Type	Target components	Remarks
Type S	0402R/C	• It is possible to purchase the tape guide only. • The service life of cover tape peeling blade: about 3 000 h Equivalent to 1500 times of peeling * Not available for emboss tape. * If need the tape guide for 2012 or 3216, please contact us.
Type A	0603R/C	
Type B	1005R/C	
Type C	1608R/C	


- Please refer to “4.4 Feeder Carriage Configuration” for details.
- Not available for CM602, CM402/ DT401 Series, CM232, CM212, CM101.

* If you want use IFCU to check auto load feeder, please contact us for details.

* When the auto load feeder is used, a reel holder for setting the reel to be used up and a newly supplied reel is required.
Please consult us separately.

Customer**Auto load feeder common attachment**

- One piece is required per slot when you attach an auto load feeder.
Two auto load feeders can be attached to each slot.
 - This is required even when you use a “Feeder setting jig” in offline setting.
- * This attachment can also be used on 4 mm/ 8 mm thin type tape feeder.


B-5	To select the stick feeder in accordance with the production pattern.
Customer	Single stick feeder • Please refer to “4.4 Feeder Carriage Configuration” for details. • Supporting only Lightweight 8-nozzle head and 3-nozzle head V2. • Single stick feeder cannot be used in CM602, CM402/ DT401 series, CM232, CM212, CM101.
Customer	3-lot stick feeder • Please refer to “4.4 Feeder Carriage Configuration” for details. • Supporting only Lightweight 8-nozzle head and 3-nozzle head V2. • It is compatible with AM100, CM602, CM402/ DT401 series, CM232, CM212, CM101, NPM series, and NPM-X series.
Customer	Guide block (For Single stick feeder, 3-lot stick feeder) * Guide block is used when components are difficult to be picked up by the machine in the feeding method with the tip-cut sticks because the transfer state of components and the components posture at the pick-up position are not good depending on the component/stick shape, etc.
B-6	To select the stackable stick feeder in accordance with the production pattern
Customer	Stackable Stick feeder Stackable stick feeder (S) S, M, L size pusher for S type Stackable stick feeder (L) S, M, L, LL, LLL size pusher for L type
	• Please refer to “4.4 Feeder Carriage Configuration” for details
On-site	☐ Table
	Air Supply Unit for Feeder
	• Air Supply Unit for Feeder is necessary when using stackable stick feeders. (13-slot feeder base comes with “Air supply unit for the feeder”.)
B-7	To manage and store tape feeders.
Customer	Tape feeder stand 
	• This is a stand for intelligent tape feeders. • For the 8 mm double tape feeder, for example, up to 90 ones can be stocked. * Please contact us for stocks of thin type tape feeders. (Enables to stock thin type tape feeders if it is installed to “Thin type feeder attachment.”)

B-8

To manage and store stackable stick feeders. To conduct advance preparation

Customer

Feeder stand



- This is a stand for stackable stick feeders.
- For stackable stick feeder (S), up to 15 pcs can be stocked. For stackable stick feeder (L), up to 7 pcs can be stocked.
- This is used when to pull the stackable stick feeder off a machine and when to move the stackable stick feeder.
- When there are intelligent tape feeders only, it is available to use stand for intelligent feeders.

Customer

Power and air supply unit (For stand)

- By adding power and air supply unit to the feeder stand, power and air can be supplied to the feeders and offline feeder movement is possible.
- Items below are included.

1. Power supply unit

Item	Specification
Rated voltage	Single phase, AC 100 V ~ 240 V
Frequency	50/ 60 Hz
Rated capacity	90VA

2. Power supply cable for feeder**3. Power supply cable****4. Air connector**

* Please prepare power supply source, cable, air supply source and air hose by yourself.

B-9	To change the positions of PCB support pins externally in order to reduce the changeover time.
Customer	PCB support block (For single conveyor) PCB support block (For dual conveyor)
	- PCB support blocks (4) and support pins (20) are included. - It can be additionally purchased by the block. - The support pin is not included if additionally purchased. Please select "Additional support pin" as needed. - To set up the positions of support pins for new PCB externally, please select "Support pin setting jig" separately. - Common with NPM-W * This is not used with "Automatic replacement of support pins."
Customer	PCB support block that supports single lane mode (For dual conveyor)
	2 blocks are required in the single lane production mode. - It is used in combination with the support blocks for dual conveyor. (See the following figure) - It can be additionally purchased by the block. - No support pin is included. Please select "Additional support pin" as needed. - To set up the positions of support pins for new PCB externally, please select "Support pin setting jig (for Dual conveyor)" separately. - Common with NPM-W * This is not used with "Automatic replacement of support pins."
Customer	Support pin setting jig (For single conveyor) Support pin setting jig (For dual conveyor)
	- To prepare the support pins externally, please select the "PCB support block" separately. - Common with NPM-W
Customer	Additional support pins
	- Please select when needed in addition. (20 pieces are included in 1 set.) - For single/dual use. - It is common with NPM-X series, NPM series, AM100 and NPM(Dual Lane Specification).

B-10

To replace the support pins automatically.

On-site

Whole machine


Automatic replacement of support pins

A function to automatically set up the support pin using the placement head.

Up to 40 support pins can be automatically configured per a piece of PCB. (Standard support pins cannot be used.)

For process-plus-placement head (or no head-plus-placement head) specifications, the placement head on one side copes with pin configurations in the front and rear lanes.

Support pin configuration data is created by NPM-DGS. You can check pin configuration on the PC screen.




Accessory	Description	Remarks
PCB support block (For automatic replacement): Select either one according to the conveyor specifications.		Common with NPM-W
For single conveyor	1 set (four blocks)	
For dual conveyor	1 set (two blocks each of Front/Rear)	
Dedicated nozzle changer	1 pair (one each of Front /Rear)	Common with NPM-X, NPM series

Selection option	Description	Remarks
Support pin (For automatic replacement)		Common with NPM-X, NPM series, AM100
Nozzle for support pin changeover	100 nozzle: For 16-/ 12-/ 8-nozzle head 1100 nozzle: For 3-nozzle head	Common with NPM-X, NPM series

The nozzle for support pin changeover is stored in the dedicated nozzle changer.


Each one of #100 nozzles and #1100 nozzles can be stored in the dedicated nozzle changer.

Dedicated nozzle changer

See the next page for the constraint condition when support pins are automatically replaced.

Customer

Support pin (For automatic replacement)




- Up to 40 pieces can be configured per a piece of PCB. (For PCBs whose size is L= 350 mm or less: up to 20 pieces)
(Dual conveyor specifications: Max. 80 pieces with front lane and rear lane)

Customer

Nozzle for support pin changeover



100 nozzle
(For 16-/ 12-/ 8-nozzle head)



1100 nozzle
(For 3-nozzle head)

- Please select according to head configuration. (One nozzle is used for each placement head.)





B-10


To replace the support pins automatically.

The following constraint conditions are required when support pins are automatically replaced.

Constraint condition


(Unit: mm)

Item	Description
Minimum PCB size capable to set up pins	Single conveyor specifications: L 50 × W 90 mm Dual conveyor specifications: L 50 × W 70 mm
Pin configuration pitch	16 mm or more (X, Y direction)
Pin configuration area (Left-to right flow)*1	• <u>Single conveyor specifications</u>  • <u>Dual conveyor specifications</u> For dual lane mode  For single lane mode  : Pin (center) configurable area*2 *1 If PCB flow is from right to left, the above dimensions are symmetrically situated. *2 Visible outline is included in the pin (center) configurable area.
Pin arrangement condition	 Please configure support pins to the location where the dimensions shown on the left can be secured. Keep away from slit on a PCB when pins are configured.


B-11	To prepare feeders in advance and change them collectively.
Customer	Feeder cart (30-slot) 
• The floor slope in the feeder cart installation area needs to be 6 mm or less in the right/left direction and 11 mm or less in the forward/backward direction. If the floor slope is beyond the above limit, the feeder cart cannot be taken in and out. • Common with NPM- W	

B-12

To place tray-feeding components.

Factory

Max. 20 products

Single tray feeder
with 13-slot feeder base

Max. 40 products


Twin tray feeder

Standard accessory	Single tray feeder	Twin tray feeder
Tray magazine (15 mm pitch × 10 stages)	2 pcs.	4 pcs.
Tray pallet	21 pcs.	42 pcs.
Components-ejection tray	1 pc.	2 pcs.

* The single tray feeder is common to the tray feeder for the NPM-W, NPM-D3A/ D3/ D2/ D, NPM-TT, NPM and AM100.
When connecting the tray feeder for the existing NPM-D (or NPM), modification of tray feeder wiring may be required.
Please ask us for details. (Custom specification)

* Twin tray feeder is common with NPM-W.

- Not connectable if the main unit is to the feeder cart specifications.
- 13-slot feeder base is included with the single tray feeder.
(with an air supply unit for feeder)



13-slot feeder base

4 mm tape
8 mm tapeMax. 26: Thin type tape feeder
Max. 26: Duple/ Thin type tape feeder (Small reel)12/ 16 mm tape
24/ 32 mm tape
44/ 56 mm tape
72 mm tape
88 mm tape
104 mm tapeMax. 13
Max. 6
Max. 4
Max. 3
Max. 2
Max. 2Stick
NG-components ejection conveyor
Multi-functional transfer unitMax. 3
1
1**Customer**

Additional tray magazine (15 mm pitch × 10 stages)

Additional tray pallet

Additional components-ejection tray

- Please select this option when needed additionally.

Customer


Pallet for vacuum-molded-tray


Pallet for vacuum-molded-tray (Magnet fixed type)

- Please select this option when using vacuum-molded trays.




[Applicable tray dimensions]



L × W = Max. 230 × 318 mm

15 mm or less
(Magnet fixed type: 10 mm or less)

B-13	To improve the workability of tape splicing.
Customer	
Splicing cart	
	This cart improves the workability of tape splicing. (For Intelligent tape feeder)

B-14	To mount thin embossed tape components (Feeding holes become deformed when tape thickness is equivalent to 0.2mm or thinner)
Customer	
8 mm double feeder (Thin embossed tape ready)	
	- At embossed tapes that is ultra-thin and weak tape strength, sprockets to feed tapes could deform feeding holes. - Changes to smoother sprocket surface at thin embossed tape feeder, and that increases the contact area with carrier tapes to reduce the deformation of feeding holes. - For the details, see "Intelligent Tape Feeder" in the "4.4 Feeder Carriage Configuration" section.

C-1	To replace the Head.
Customer	Table
 Spare Lightweight 16-nozzle head V3A*  Spare 12-nozzle head  Spare Lightweight 8-nozzle head  Spare 3-nozzle head V2  Head case	
- Head case comes together with spare head. - It should be replaced for each table. Different Heads can be installed to the front and rear tables. - Since nozzle changer and side lighting do not come together, please select them separately as options. - It is for NPM series and NPM-X series only. * You cannot use Lightweight 16-nozzle head V3A with NPM-WXS, NPM-W2S/ W, NPM-TT2/ TT, NPM-D3/ D2/ D, NPM. * You cannot use 12-nozzle head with NPM-DX, WX/ WXS, NPM-TT2/ TT. - In Individual Specification, you can use it with NPM-D3A. For the details, contact us. * You cannot use Lightweight 8-nozzle head with NPM-W, NPM-TT, NPM-D2/ D, NPM. * You cannot use 3-nozzle head V2 with NPM-DX, NPM-D3A/ D3/ D2/ D, NPM . * In an emergency, is possible to use the conventional 16-nozzle head. (4 point fixation type only) In that case, placement tact time and accuracy are the same as NPM-W (70 000 CPH, ± 0.04 mm (Cpk≥ 1)).	
Customer	Table
 Spare nozzle changer (For Lightweight 16-nozzle head V3A) (For 12-nozzle head) You can also use the existing 16/ 12-nozzle head nozzle changer  Spare nozzle changer (For Lightweight 8-nozzle head) You can also use the existing 8-nozzle head nozzle changer  Spare nozzle changer (For 3-nozzle head V2) You can also use the existing 3-nozzle head nozzle changer  Spare nozzle changer (For Lightweight 16-nozzle head V3A) (For 12-nozzle head) Nozzle changer Expansion type You can also use the existing 16/ 12-nozzle head nozzle changer  Spare nozzle changer (For Lightweight 8-nozzle head) Nozzle changer Expansion type You can also use the existing 8-nozzle head nozzle changer  Spare nozzle changer (For 3-nozzle head V2) Shield nozzle ready You can also use the existing 3-nozzle head nozzle changer	
- It is for NPM series and NPM-X series only. * You cannot use Lightweight 16-nozzle head V3A nozzle changer with NPM-TT2/ TT. * You cannot use Lightweight 16-nozzle head V3A nozzle changer(Expansion type) with NPM-DX, NPM-D3A/ D3/ D2/ D, NPM-TT2/ TT, NPM. * You cannot use Lightweight 8-nozzle head nozzle changer(Expansion type) with NPM-DX, NPM-D3A/ D3/ D2/ D, NPM. * You cannot use 3-nozzle head V2 nozzle changer with NPM-DX, NPM-D3A/ D3/ D2/ D, NPM.	
On-site	Table
Spare multi-recognition camera: Type 1 Spare multi-recognition camera: Type 2 Spare multi-recognition camera: Type 3 (With side lighting)	
On-site	Table
Spare side lighting	
This is required for bump recognition of the BGA/ CSP. (Exclusive to multi-recognition camera)	

C-2	To correct the PCB height (Warp) and improve placement/dispensing quality.
On-site	Table
Height sensor	
- The height sensor supports the placement/the dispensing heads. The sensor functions change depending on whether it supports the placement head or the dispensing head. (The functions cannot be used together) <PCB warpage correction (Placement head)> - Controls the placement height of a PCB by measuring the height (warp) of the whole PCB. (The measurement is after PCB recognition) Measurement time: 3.0 s (750 × 510 mm in an optimal condition, with 9-point measurement) - Select the height sensor for the first NPM-W2 in line. Select only the front side for single conveyor specifications and, both the front and rear side, for dual conveyor specifications. The head configuration except for [placement head + placement head], PCB warpage correction does not function. - Measurement data is passed to the downstream NPM-W2. * For any PCB whose warp geometry changes each time it is clamped, please consult us separately. <Local PCB height correction (Dispensing head)> - The PCB height (warpage) adjacent to the drawing position (non-contact) is measured in order to correct and optimize the nozzle height. (The measurement is before dispensing) Measurement time: 0.5 s (30 × 30 mm in an optimal condition, with 4-point measurement) - Nozzle height correction during dot dispense is also enabled. (local range) - Select the height sensor for the dispensing head mount beam. - No data passing is allowed. - Please refer to "4.7 Recognition Unit Configuration" for details.	
Customer	
Height sensor teaching jig	
- It calibrates linearity and offset of the height sensor. - It is necessary if you purchase the height sensor for the first time. - It is common with NPM series, NPM-X series, AM100.	
C-3	To exchange the feeder carts in the independent changeover.
Factory	Table
Independent changeover supporting unit: Front side Independent changeover supporting unit: Rear side	
- It is option for the dual conveyor specification. - Feeder cart can be changed in the Independent changeover. Please select for the stage which uses a feeder cart. (It cannot select the rear side only.) * The safety cover cannot be attached, when you select this option for the table. * The feeder carts are required when installed in the dispensing head table. * These cannot be installed in the inspection head table.	

C-4**Improve Lightweight 16-nozzle head function****Factory**

Table

±0.025 mm placement support

- It improves placement accuracy. (± 0.025 mm ($Cpk \geq 1$): Under below conditions)
- Make ± 0.025 mm placement-specific parameter settings.
- Possible to simultaneously select "03015 placement support", but the placement accuracy is ± 0.03 mm ($Cpk \geq 1$).

<Placement condition>

Target head	Lightweight 16-nozzle head V3A, V2
Production mode	High production mode: OFF
Applicable components	Jig chips (1005)
Placement angle	0°, 90°, 180°, 270° only
Recognition	Placement angle recognition

Factory

Table

03015 placement support


- 03015 placement is possible. (± 0.03 mm ($Cpk \geq 1$): Under below conditions)
- Make 03015-specific parameter settings.
- For 03015 chip placement, "276CS (or 276CSN) nozzle" and 4mm thin type tape feeder (4W1P) is required.
- 03015R is out of 2D inspection.

<Placement condition>

Target head	Lightweight 16-nozzle head V3A
Production mode	High production mode: OFF
Applicable components	03015R (By Panasonic)
Placement angle	0°, 90°, 180°, 270° only
Recognition	Placement angle recognition


C-5**To align and eject the NG components onto the conveyor.****Customer**

Table


NG-components ejection conveyor


- Applicable component dimensions
Max. W 42 × L 60 mm
T = 1 mm ~ 16 mm


- Component shape
 - ① No space exceeding 0.3 mm on its underside on a horizontal surface
 - ② No extremely unstable shape, e.g. small underside compared with its height




- This is used for ejecting recognition NG components.
- Usable only for 8-nozzle head and 3-nozzle head V2.
- This option will occupy four feeder setting slots.
- It is possible to install for the 13-slot feeder base.
- This cannot be installed on tables for which the Twin tray feeder is selected.
- It is for NPM series and NPM-X series only.




C-6	To implement production with a Head/Heads removed.
Customer	
No Head attachment	
	• This is an attachment that is required to implement production with one side Head in where one Head is removed due to maintenance, etc. (Normally, the machine cannot operate with the Head removed.) • When the attachment setting is done for both sides (front and rear), the machine can operate with PCBs only passing through the machine.
Customer	
Safety cover: Front side	
Safety cover: Rear side (Feeder cart specification)	
	• Please be sure to select the safety cover. (Not required when Feeder cart is attached.) • This is exclusively for NPM-W2. * The safety cover cannot be attached when the independent changeover support unit is installed in the table. Please mount the feeder cart.
C-7	To manage and store the removed Heads.
Customer	
Head stand (For two heads)	
	• This is used to store the removed heads after exchanging. • One stand can store two heads. • This is exclusively for NPM series and NPM-X series.

C-8	To reduce time for changeovers.
On-site	Support station (Power supply type) Support station box (Component verification type) - By using the spare feeder carts and feeders, which you have, you can prepare for next products while the machine continues its operation. - This has two types: one of them only supplies electric source to feeder carts and feeders, and another one implements component verification in addition to the electric source supplying. - To use PanaCIM-EE for off-line setup, "Support station box (Component verification type)" is required. - Please refer to "5.5 Support Station" for details. * In NPM series, "Change Cart Preparation Unit" in CM series is not available.
On-site	Support station: Component verification type (License) This is required for the use of "Support station box (Component verification type)." * The license is not required for off-line setup (component verification) using PanaCIM-EE. * This does not support stackable stick feeder.
Customer	Feeder setting jig - The feeder setting jig is used as a feeder holder to set components on the feeder and to verify components. "Attachment for thin type tape feeder" is required to install thin type tape feeders.
Customer	Attachment for thin type tape feeder
Customer	Power connector for thin type tape feeder  - Required to directly supply electricity to thin type tape feeders (at the time of preparation, etc.). Used by connecting to the power cable for feeders, which comes with the support station. - When power to thin type tape feeders is supplied through "Attachment for thin type tape feeders", this option is not required. (Use a standard type power cable for feeders.)
C-9	Wishes to use all sorts of function modules of PanaCIM-EE.
On-site	PanaCIM-EE ready (License) - Please select this option when connecting to PanaCIM-EE. - It supports each functional module of PanaCIM-EE. - It includes "Component verification (License)" and "Upper communication (License)." - Please refer to "PanaCIM-EE Specification" booklet for details.
C-10	Wishes to use all sorts of function modules of iLNB.
On-site	iLNB ready (License) - Please select this option when connecting to iLNB. - It supports each functional module of iLNB. - It includes "Upper communication (License)". - Please refer to "iLNB Specification" booklet for details.

C-11	To implement changeover efficiently.
On-site	
Automatic changeover (License)	
- This supports changeovers (production data change and rail width change), minimizing the time loss of operation caused by product changes. In accordance with each customer's operation, selection can be made from following three types, "External scanner read type", "Head read type", and "Planned form read type". - Please refer to "5.2 Automatic Changeover" for details.	
C-12	To prevent setting error at the time of component change.
On-site	
Component verification (License)	
- This prevents components from being put wrongly. If wrong components are put, interlock function of the machine operates to create the mode automatically where production cannot be continued. It is possible to customize order of barcode scanning and/or barcode definition, according to customers' operation. - We have wired scanner type and wireless scanner type(PanaCIM-EE Gen2 Capability). - It is not available to select with "PanaCIM-EE ready (License)" at the same time. (It is included in "PanaCIM-EE ready (License).") - Please refer to "5.1 Component Verification" for details.	
Factory	Table
Wired scanner	
- Required when "Component verification (wired scanner type)" is selected. - Operation on two tables is made possible by one scanner.	
	
On-site	Whole machine
Scanner holder	
Holders, which are for fixing wired scanners, are equipped at the front and rear of the machine.	
C-13	To streamline setup operations during a changeover.
On-site	
Feeder Setup Navigator (License)	
- It is a support tool to navigate efficient setup procedure. The tool factors in the amount of time it takes to perform and complete a setup when estimating the time required for production and providing the operator with setup instructions. - Together with this license, select the following options. <u>Required</u> Support station box (Component verification type) <u>Choice (Select any of the following)</u> - Component verification (License) + Support station: Component verification type (License) - PanaCIM-EE ready (License) - Please refer to "5.3 Feeder Setup Navigator" for details.	
C-14	To use existing system effectively.
Customer	
Upper communication (License)	
- This is an open interface which is in cooperation with customer's existing system. As standard interface is prepared, it's possible to intercommunicate necessary information. Depending on the purpose of customer's system, functions of "Event", "Component verification with other vendor's machine", and "Information for component management" can be used. - It is not available to select with "PanaCIM-EE ready (License)" at the same time. (It is included in "PanaCIM-EE ready (License).") - It is not available to select with "iLNB ready (License)" at the same time. (It is included in "iLNB ready (License).") - Please refer to "5.4 Upper Communication" for details.	

C-15	To make use of the location-independent tape feeder function.
- The tape feeder can be located flexibly within the same table. - You can locate components alternately and the feeder for the next product at an empty slot. * Using the "Support station box (Component verification type)", you need to write data to tape feeders in advance. "Component verification (license)" is also needed.	
On-site	Component verification (License)
On-site	Support station box (Component verification type) Support station: Component verification type (License)
It is necessary to write information to the memory of tape feeders.	
C-16	To change to inspection head (to execute solder or component inspection)
On-site	Table
Spare 2D inspection head A (Resolution: 18 μm) Spare 2D inspection head B (Resolution: 9 μm)	
On-site	Table
Inspection head support unit (Inspection BOX and calibration jig)	
Customer	Table
Safety cover: Front side	
* Exclusive to NPM-W2	
 The diagram illustrates the components and installation of the inspection head support unit. On the left, a main view of the unit shows three callouts: 'Head' (a vertical black component), 'Safety cover' (a black rectangular plate), and 'Inspection BOX' (a black box). On the right, a detailed view of the unit's internal components shows the 'Calibration jig' (a green and blue component) and the 'Head case' (a blue box). Arrows indicate the placement of these components within the unit.	
- Regarding resolution of the 2D inspection Head, there are two types, 18 μm and 9 μm. - One inspection head cannot handle solder inspection and component inspection at the same time. - Inspection head support unit (Inspection box and Calibration jig) are necessary for each inspection head installed stage. (Inspection head A/ B can be commonly used.) - Please be sure to select the safety cover. - Head case is accompanied to spare 2D inspection head.	

C-17	To improve placement quality by controlling process through process measurement data of inspection head (solder inspection).
Customer	
APC system ready (License)	
- APC system can help improve placement quality by feed forwarding solder measurement data of inspection head to placement head which enables component placement at the optimum and highly accurate positions. - With component inspection, misalignment can be inspected against controlled reference position of placement. - This option is required for each of the following equipment: 1) First NPM-W2 in line which has 2D inspection head installed. 2) NPM-W2 which receives APC-FF offset data. - Please refer to "5.7 APC system" for details. * APC system-ready equipment: NPM X / NPM series (mixed line supported) If line is made up with other equipment than the above, please contact us. * 03015 components are not eligible.	
C-18	To enable APC system using SPI
On-site	
Interface software of the inspection machine from other companies (License)	
- This is interface software to enable APC system using a measurement data of inspection machine (solder inspection) from other companies. - This option is required per NPM-W2 that receives APC-FF offset data. - Select this option, together with "APC system-ready (License)" for the same number. - Please refer to "5.7.1.1 When you use SPI of inspection machine from other companies" for details. * Target inspection machines need to satisfy the requirements of our specifications. For details, please contact us. * A dedicated PC needs to be placed between the inspection machine from other company and FA PC (LNB). Please prepare a PC, a HUB and LAN cables by customers. * 03015 components are not eligible.	
Customer	
APC system ready (License)	
- This is required when using "Interface software (License) of inspection machine from other companies". - This option is required per NPM-W2 that receives APC-FF offset data.	
C-19	To maintain placement quality by using the AOI measurement data of mounting process.
Customer	
APC-MFB2 system ready (License)	
- APC-MFB, based on the results of AOI, compensates for the discrepancy between component mounting coordinates and the actual mounting position to maintain the accuracy of an initial mounting to achieve stable mounting quality. - Divided into categories focusing on nozzles, feeders, components, and mounting positions, the results of AOI inspection is presented as a process capability index. This is helpful for process variation management and appropriate response when the process varies. - This option is required per NPM-W2 that receives APC-MFB offset data. - This option supports NPM X/ NPM series. - Please refer to "5.7.2 APC-MFB system" for details.	

C-20	To change to dispensing head.
Customer	Table
	Spare dispensing head
Customer	
	Dispense nozzle
	- For information about the dispense nozzle types, please refer to “4.3 Dispense Nozzle Configuration.” - For information about the special nozzles, please contact us. - This is exclusively for NPM-W2/ W, NPM-D3A/ D3/ D2/ D and NPM.
Customer	Table
	Spare dummy dispensing unit Spare wiping station
	You may need to exchange the bracket when install the wiping station in the existing NPM-W*. Please contact us for details. * Applicable: NPM-W with the serial No. 1C7V0517 or earlier
Customer	Table
	Safety cover: Front side Safety cover: Rear side (Feeder cart specification)
	* This is exclusively for NPM-W2
Customer	
	Jig kit for accuracy verification
	- It is a set of the calibration nozzle and the PCB for accuracy verification. - It is necessary in purchasing the first machine.
Customer	
	Spare screw unit
	
	- Two pieces are accompanied to dispensing head. Please select when needed additionally. - It allows you to continue production even while cleaning a screw unit.
 Head  Safety cover*  Wiping station  Dummy dispensing unit  Head case 	
	- Please be sure to select the safety cover. (Not required when Feeder cart is attached.) - Head case is accompanied to spare dispensing head. * The safety cover cannot be attached when the independent changeover support unit is installed in the table. Please mount the feeder cart.


C-21

To perform transfer.

Customer**Multi-functional transfer unit****1. Outline**

The multi-functional transfer unit is a device to form the coating of transfer materials in the process, such as PoP top package mounting, requiring transfer of flux etc.


The transfer process will be done when a component picked up by the placement machine is pressed against the coating formed by this unit.

**2. Features**

The squeegee gap is programmable for each chip data. This makes it available to finely select the coating thickness to be transferred according to the size of bumps. (Programmable squeegee gap)

This unit can be installed on the feeder cart and 13-slot feeder base in the same way as that of the intelligent tape feeder.

The feeder address numbers 23 to 30 (8 slots) are occupied.

**3. Specifications**

Item	Specifications
Electric source	DC 24 V (to be supplied from main body)
Outside dimension	W 165 × D 676 × H 285 mm
Mass	21 kg (including 1 kg of a transfer table)
Environmental condition	Temperature: 20 °C ~ 30 °C (coating-formable temperature*) Humidity: 25 %RH ~ 75 %RH (No condensation)
Exportation/Storage conditions	Temperature: -20 °C ~ 60 °C Humidity: 75 %RH or below (No condensation)

* If the temperature range of target transfer materials is narrower than the above range, the former range should be followed.

4. Availability of transfers based on the feeding method of applicable components

	Applicable head		
	Lightweight 16-nozzle head V3A*1	Lightweight 8-nozzle head	3-nozzle head V2
Feeding method	Taping	Taping and tray*2	
Component dimension	2 × 2 mm ~ 8.5 × 8.5 mm (6 × 6 mm ~ 8.5 × 8.5 mm With conditions added)	~ 20 × 20 mm	~ L40 × W30 mm
Applicable component	BGA, CSP		

*1 Lightweight 16-nozzle head transfer (License) is necessary.

*2 Tray components are only in the Single Tray Feeder Specification.

5. Automatic supply of transfer materials

The multi-functional transfer unit has a function to supply transfer materials automatically.

This function is used by specifying the supply frequency parameter. The amount of one supply can be adjusted by specifying the parameter of the discharging time from syringe.

We recommend "Automatic supply" as a supply method of the transfer materials. ("Automatic supply" makes the amount of use of the transfer material a minimum.) To use this function, the optional air supply unit needs to be installed on the feeder cart on which the multi-functional transfer unit is installed. (For 13-slot feeder base, the air supply unit for a feeder is included.)

To use this function, the materials should be set in the multi-functional transfer unit while being encapsulated in the MUSASHI-ENGINEERING-manufactured $\phi 26$ mm syringe (PSY-30E, PSY-50E, PSY-70E, etc.) or its equivalent*. The customer needs to specify that when purchasing from a materials manufacturer, or to prepare the syringe by yourself and refill it.

* Equivalent: The one that can be used in combination with the MUSASHI-ENGINEERING-manufactured adapter tube AT50-E.
The one that can be used in combination with the MUSASHI-ENGINEERING-manufactured joint J-R-3.


6. Programmable squeegee gap

The multi-functional transfer unit determines the coating thickness of transfer materials by controlling the gap (space) between the transfer table forming the coating of transfer materials and the squeegee smoothing them.

This space is called a squeegee gap, and programmable for each chip. The setting range is as follows.

Squeegee gap setting range: 0.015 mm to 0.35 mm

The thickness of the coating to be actually formed varies depending on transfer materials; however, it is generally 50 % to 70 % of the squeegee gap.



Coating-formable materials verified

- By Panasonic MSP521 Flux
- By Indium TACFlux023 (Flux)
- By Senju Metal Industry M705-TVA03.9-F (Solder paste for transfer)

* These materials should not be viewed as our recommendation.

The multi-functional transfer unit does not guarantee to form the coating of every transfer material. It may not be able to form the coating of even the coating-formable materials verified above, depending on their storage condition, replacement frequency, and so on.

7. Transfer materials

As for the usage of transfer materials, the specifications and instruction manuals provided from their respective manufacturers should be followed. And also, it is necessary to obtain the chemical substances safety data sheets (MSDS) of the transfer materials, and follow their descriptions.

8. Transportation and carry

The mass of the multi-functional transfer unit is 21 kg.

As to the transportation and carry, the precautions described in the instruction manuals should be followed.

* This option is compatible with AM100, CM602, CM101, NPM series, and NPM-X series.

Customer

Coating thickness gauge (0 μ m to 250 μ m, in 10 μ m increments)

Coating thickness gauge (0 μ m to 500 μ m, in 20 μ m increments)

- This is the gauge for measuring the thickness of the coating formed by the multi-functional transfer unit.
- Please select the one with the appropriate measurement range.
- Recommended manufacturer and type

Manufacturer	Type (identical)
Sanko Electronic Laboratory Co., Ltd. (in Japan)	234R/IV: 0 μ m - 250 μ m (10 μ m)
ERICHSEN (outside Japan)	234R/V: 0 μ m - 500 μ m (20 μ m)

* This option is compatible with AM100, CM602, CM101, NPM series, and NPM-X series.

On-site

Table

Air supply unit for the feeder

- It is necessary when using the automated transfer material supply function. (For 13-slot feeder base, the "Air supply unit for the feeder" is included.)

C-22	To enable remote operation
On-site	
Remote operation (License)	
- Remote operation function allows centralized collection of errors generated in the machines and offers remote-controlled recovery, reducing error recovery time and contributing to efficient capacity utilization and labor-saving. - This provides a system where it detects errors when they occur and allows remote-controlled recover. This centralized recovery system helps reduce “the need for operators to notice errors” and “the travel time to the targeted error machine, thereby reducing error recovery time. - For details, see “5.13 Remote operation”.	

C-23	To login to a machine using biometric information
On-site	
Biometric authentication(License)	
- Biometric authentication uses biometric information and enables login to a machine. (Helps improve security; preventing to someone from stealing passwords and preventing passwords to be shared) - For details, see “5.14 Biometric authentication”.	

C-24

To keep the placement push-in load of Lightweight 16-nozzle head constant

On-site

Lightweight 16-nozzle head constant mount load control (License)

1. Overview

This function keeps the placement push-in load of Lightweight 16-nozzle head V3A constant.

2. Features

Keeps the push in the load constant by controlling the motor current of the Z axis.

This provides the stable mounting without over-pushing the board even when the board has upward warp.

3. Specifications

Item	Specification
Placement load (N)	≤ 1.0 N
Productivity	This function does not decrease the productivity
Setting method	Setting for each table is possible.

4. Reference information

This function controls the push in load.

Use "Placement 2-head Down" in the standard function together when you want to control the contact load of the board.

C-25

To enable bonding involving paste transfer with Lightweight 16-nozzle head

On-site

Lightweight 16-nozzle head transfer (License)

1. Overview

Enables transfer mounting with Lightweight 16-nozzle head.

2. Features

Enhances transfer mounting productivity

3. Specifications

Item	Specification
Applicable components	Component Size : □2 mm~□6 mm (When it is Lightweight 16-nozzle head V3A, it is □8.5 mm) (□6 mm ~ □8.5 mm with conditions added) Thickness: Max. 3 mm (When you use a short nozzle(101GS, 101GSN, 102GS, 102GSN), it is 6 mm at the maximum)
Required condition	The top surface of component picked up by the nozzle must be flat and larger than the pickup nozzle. * However, some restrictions are placed by the transfer process condition.

C-26	To measure the push-in load or impact load during placement and display the results on the monitor of the machine or on the LNB																											
Factory																												
Load checker																												
1. Overview This function measures the “push-in load” of the placement head and displays the results on the monitor of the machine or on the LNB. 2. Definition of loads Impact load: The load that occurs momentarily when the nozzle touches the load cell during placement. Push-in load: The load that occurs when the nozzle is pushed onto the load cell by 0.3 mm. 3. Main features <table border="1"> <thead> <tr> <th>Item</th><th>Specification</th></tr> </thead> <tbody> <tr> <td>Push-in load measurement</td><td>Measures the push-in load of the placement head nozzle by the load checker during maintenance or production, and displays the results on the screen of the machine or on the LNB. * Push-in load measurement: Placement 100% and Place gap 0.3 mm * Measured load is expressed as the deviation from the standard value.</td></tr> <tr> <td rowspan="2">Measured push-in load judgment</td><td>(1) Load Warning Range Displays a warning message if the measured load exceeds the preset range. Measurement range: $\pm 0 \sim 3,000\%$ (Default: $\pm 40\%$)</td></tr> <tr> <td>(2) Load NG Range Displays “NG” if the measured load exceeds the preset range. The axis detected as NG will be set as “Bad nozzle” automatically. Measurement range: $\pm 0 \sim 3,000\%$ (Default: $\pm 60\%$) * Set a value greater than “Load Warning Range”.</td></tr> <tr> <td>Stop production if push-in load is NG</td><td>Stops production if “NG” is detected in the loads measured during production.</td></tr> <tr> <td>Measure push-in load storage</td><td>Stores the push-in loads measured during maintenance or production to be stored in the LNB for 30 days so that they may be checked as necessary.</td></tr> <tr> <td>Applicable heads</td><td>Lightweight 16-nozzle head V3A, V2, 12-nozzle head, Lightweight 8-nozzle head * Multifunctional head are not supported.</td></tr> <tr> <td>Requirements of applicable nozzles</td><td>- Nozzle tip size: $\leq 4.0 \times 4.0$ mm (Tx, Ty in nozzle library) - Total nozzle length: 13.8 mm (TUPH in nozzle library) * Nozzles with non-flat end is not supported. (Special nozzle, bad nozzle, etc.)</td></tr> <tr> <td>Load display</td><td>Represents the measured push-in load as the deviation from the standard value in percent. Least increments: 0.1%</td></tr> <tr> <td>Push-in load Measurement count</td><td>Sets how many times push-in load is to be measured per nozzle axis. 1 ~ 9 times per nozzle * Default: 3 times</td></tr> <tr> <td>Load measuring interval by board count</td><td>Sets the interval of push-in load measurement during production in terms of board count. 0 ~ 9,999 pcs. * Default: 0</td></tr> <tr> <td>Push-in load measurement accuracy</td><td>$\leq \pm 0.2$ N (Common to all heads)</td></tr> <tr> <td>Load checker calibration time</td><td>≤ 15 s per head (Common to all heads)</td></tr> <tr> <td>Push-in load measurement time</td><td>Lightweight 16-nozzle head V3A, V2: ≤ 40 s 12-nozzle head: ≤ 30 s Lightweight 8-nozzle head: ≤ 20 s</td></tr> </tbody> </table>		Item	Specification	Push-in load measurement	Measures the push-in load of the placement head nozzle by the load checker during maintenance or production, and displays the results on the screen of the machine or on the LNB. * Push-in load measurement: Placement 100% and Place gap 0.3 mm * Measured load is expressed as the deviation from the standard value.	Measured push-in load judgment	(1) Load Warning Range Displays a warning message if the measured load exceeds the preset range. Measurement range: $\pm 0 \sim 3,000\%$ (Default: $\pm 40\%$)	(2) Load NG Range Displays “NG” if the measured load exceeds the preset range. The axis detected as NG will be set as “Bad nozzle” automatically. Measurement range: $\pm 0 \sim 3,000\%$ (Default: $\pm 60\%$) * Set a value greater than “Load Warning Range”.	Stop production if push-in load is NG	Stops production if “NG” is detected in the loads measured during production.	Measure push-in load storage	Stores the push-in loads measured during maintenance or production to be stored in the LNB for 30 days so that they may be checked as necessary.	Applicable heads	Lightweight 16-nozzle head V3A, V2, 12-nozzle head, Lightweight 8-nozzle head * Multifunctional head are not supported.	Requirements of applicable nozzles	- Nozzle tip size: $\leq 4.0 \times 4.0$ mm (Tx, Ty in nozzle library) - Total nozzle length: 13.8 mm (TUPH in nozzle library) * Nozzles with non-flat end is not supported. (Special nozzle, bad nozzle, etc.)	Load display	Represents the measured push-in load as the deviation from the standard value in percent. Least increments: 0.1%	Push-in load Measurement count	Sets how many times push-in load is to be measured per nozzle axis. 1 ~ 9 times per nozzle * Default: 3 times	Load measuring interval by board count	Sets the interval of push-in load measurement during production in terms of board count. 0 ~ 9,999 pcs. * Default: 0	Push-in load measurement accuracy	$\leq \pm 0.2$ N (Common to all heads)	Load checker calibration time	≤ 15 s per head (Common to all heads)	Push-in load measurement time	Lightweight 16-nozzle head V3A, V2: ≤ 40 s 12-nozzle head: ≤ 30 s Lightweight 8-nozzle head: ≤ 20 s
Item	Specification																											
Push-in load measurement	Measures the push-in load of the placement head nozzle by the load checker during maintenance or production, and displays the results on the screen of the machine or on the LNB. * Push-in load measurement: Placement 100% and Place gap 0.3 mm * Measured load is expressed as the deviation from the standard value.																											
Measured push-in load judgment	(1) Load Warning Range Displays a warning message if the measured load exceeds the preset range. Measurement range: $\pm 0 \sim 3,000\%$ (Default: $\pm 40\%$)																											
	(2) Load NG Range Displays “NG” if the measured load exceeds the preset range. The axis detected as NG will be set as “Bad nozzle” automatically. Measurement range: $\pm 0 \sim 3,000\%$ (Default: $\pm 60\%$) * Set a value greater than “Load Warning Range”.																											
Stop production if push-in load is NG	Stops production if “NG” is detected in the loads measured during production.																											
Measure push-in load storage	Stores the push-in loads measured during maintenance or production to be stored in the LNB for 30 days so that they may be checked as necessary.																											
Applicable heads	Lightweight 16-nozzle head V3A, V2, 12-nozzle head, Lightweight 8-nozzle head * Multifunctional head are not supported.																											
Requirements of applicable nozzles	- Nozzle tip size: $\leq 4.0 \times 4.0$ mm (Tx, Ty in nozzle library) - Total nozzle length: 13.8 mm (TUPH in nozzle library) * Nozzles with non-flat end is not supported. (Special nozzle, bad nozzle, etc.)																											
Load display	Represents the measured push-in load as the deviation from the standard value in percent. Least increments: 0.1%																											
Push-in load Measurement count	Sets how many times push-in load is to be measured per nozzle axis. 1 ~ 9 times per nozzle * Default: 3 times																											
Load measuring interval by board count	Sets the interval of push-in load measurement during production in terms of board count. 0 ~ 9,999 pcs. * Default: 0																											
Push-in load measurement accuracy	$\leq \pm 0.2$ N (Common to all heads)																											
Load checker calibration time	≤ 15 s per head (Common to all heads)																											
Push-in load measurement time	Lightweight 16-nozzle head V3A, V2: ≤ 40 s 12-nozzle head: ≤ 30 s Lightweight 8-nozzle head: ≤ 20 s																											

C-27	To recognize the characters or 2D codes on the surface of a component before picking it up from tape feeder
Factory	
Pre-pickup Inspection (Char/2D) (License)	
• Right before pickup of tray components and tape feeder components, character recognition or 2D recognition of component surface, captured with head camera, prevents setting wrong (incorrect components) and maintains traceability. * You need to change head camera lighting to an optional lighting(Low Angle Lighting2). * You need to change tray feeder to the one with anti-vibration rubber adjust bolt. • For the details, see "5.11 pre-pickup inspection (Char/2D)".	

C-28

To recognize the lead pins of the leaded components to be inserted

Factory

Multi-recognition camera PIP lighting

1. Overview






Multi-recognition camera PIP lighting is intended to be used for recognizing only the lead pins of the leaded components to be inserted.

Multi-recognition camera PIP lighting is for 3-nozzle head V2.

2. Main functions

Item	Specification
PIP lighting	Used to extract/recognize only the inserted leads by concentrating the light.
Side lighting	Used when recognizing the solder balls on BGA / CSP (equivalent to existing side lighting).

3. Basic specifications

Item	Description
Component conditions	Overall dimensions
	Depend on the placement head used.
	Lead pitch
	$\geq 0.5 \text{ mm}$
	Lead sizes
	$\geq 0.2 \times 0.65 \text{ mm}$
	No. of leads/ group
Difference in lead length	Lead group: Max. 32 groups per component No. of leads: Max. 255 leads per group
	$\leq \pm 0.5 \text{ mm}$ (Example)
	In-spec.: $\leq 0.5 \text{ mm}$
	Off-spec.: $> 0.5 \text{ mm}$
	 $\leq 0.5 \text{ mm}$
	 $> 0.5 \text{ mm}$
Lead protrusion	$\geq 2.0 \text{ mm}$ (Example)
	In-spec.: $\geq 2.0 \text{ mm}$
	Off-spec.: $< 2.0 \text{ mm}$
	 $\geq 2 \text{ mm}$
Lead tip	 $< 2 \text{ mm}$
	 Must be higher than bottom of body
Lead material	Must have an inclined part (chamfered).
	Metallic

NOTE

Dedicated jig is required for luminosity calibration.

Part name: Luminosity calibration jig for PIP lighting unit



C-29

To reduce the time required for checking the positions judged as NG by AOI

On-site

AOI info display function (License)

1. Overview


This function provides automatic two-way information display between the AOI and mounters (NPM). It automatically identifies the NG positions so as to save labor.

- * Effect 1: Reduce the time required after NG judgment by AOI until feeder positions are identified.
- * Effect 2: Allows the feeder positions to be identified even by operators with less NPM/DGS skills.

2. System Configuration

AOI exchanges information with the mounters (NPM) through communication via the LNB.

System configuration example


**3. Main functions**

Item	Specification
Displaying NPM information on AOI	Displays the information on the NG component feeder position information automatically on the AOI screen if inspection NG has occurred. Display example: Machine No., Feeder address, Nozzle No. * Displayed information differs with the inspection machine manufacturer.
Displaying AOI information on NPM	Notifies the AOI information with the inspection image to the NPM that mounted the component concerned through the operation via the AOI screen. At this time, a warning message is displayed on the NPM, and information can be checked while continuing production.

C-30	To see whether electrical properties of components is within a predefined range before they are going to be mounted															
On-site																
LCR checker (Feeder shaped type) (License)																
• For details, refer to "5.17 LCR checker (Feeder shape type).																
On-site																
LCR checker (Built-in type)																
																
1. Common specifications between Feeder-shaped type LCR checker and Built-in type LCR checker • Checks electrical properties of chip components and judges whether they are within the specified limits. • When judged as NG components, productions will go in to error stop to prevent error mounting. • This function detects and prevent erroneous picking up of chip components that shape recognition cannot detect; the shape of chip components is the same but are different. (effective to reduce error mounting due to improper chip components being set on feeders)																
2. Comparing main points between Feeder-shaped type LCR checker and Built-in type LCR checker																
<table><tr><th>Items</th><th>Feeder-shaped type LCR checker</th><th>Built-in type LCR checker</th></tr><tr><td>Component size</td><td>0603 ~ 3216 , thickness is up to 1.5 mm</td><td>0402 ~ □6.0 mm, thickness is up to 5.0 mm</td></tr><tr><td>Type and property range</td><td>Resistance : 10 Ω ~ 100 MΩ Condenser : 10 pF ~ 100 μF Inductor : 1 μH ~ 47 μH</td><td>Resistance : 0 Ω ~ 100 MΩ Condenser : 1 pF ~ 100 μF Inductor : 4.7 nH ~ 1 mH Diode : 0 V ~ 3.4 V * Polarity evaluation only</td></tr><tr><td>Occupied slots(Feeder cart)</td><td>1 slot</td><td>None</td></tr><tr><td>License</td><td>Need</td><td>No Need</td></tr></table>		Items	Feeder-shaped type LCR checker	Built-in type LCR checker	Component size	0603 ~ 3216 , thickness is up to 1.5 mm	0402 ~ □6.0 mm, thickness is up to 5.0 mm	Type and property range	Resistance : 10 Ω ~ 100 MΩ Condenser : 10 pF ~ 100 μF Inductor : 1 μH ~ 47 μH	Resistance : 0 Ω ~ 100 MΩ Condenser : 1 pF ~ 100 μF Inductor : 4.7 nH ~ 1 mH Diode : 0 V ~ 3.4 V * Polarity evaluation only	Occupied slots(Feeder cart)	1 slot	None	License	Need	No Need
Items	Feeder-shaped type LCR checker	Built-in type LCR checker														
Component size	0603 ~ 3216 , thickness is up to 1.5 mm	0402 ~ □6.0 mm, thickness is up to 5.0 mm														
Type and property range	Resistance : 10 Ω ~ 100 MΩ Condenser : 10 pF ~ 100 μF Inductor : 1 μH ~ 47 μH	Resistance : 0 Ω ~ 100 MΩ Condenser : 1 pF ~ 100 μF Inductor : 4.7 nH ~ 1 mH Diode : 0 V ~ 3.4 V * Polarity evaluation only														
Occupied slots(Feeder cart)	1 slot	None														
License	Need	No Need														
• For details, refer to"4.8 LCR Checker (Built-in type)".																

C-31	To do simple test for checking shield component conditions after mounting
Customer	
	Mount complete position recognition (License)
	- Measures the brightness of two areas of shielded components with a head camera and detect improper mountings from brightness. When detected an improper mounting, machine gets into single stop state. (Detection of improperly mounted shield components before reflow process reduces repair time) - For details, see "5.15.1 Mount complete position recognition function".

C-32	To do simple test for checking shield component conditions before mounting
Customer	
	Mount complete position recognition (License)
	- Checks shield case warping with the machine. When detected components as warping, the components become disposal. (Prevent improper shield components from being mounted) - For details, see "5.15.2 Shield case warping inspection function before mounting".

C-33	To connect the factory-side plumbing to equipment to enable primary air connecting
Customer	Primary air hose unit 
	Primary air hose unit is used for primary air connecting where factory-side plumbing is connected to equipment.
C-34	To use large reels
Customer	Separator for feeder cart 
	Separator for feeder cart is used when supplying taping components for large reels.
C-35	To use small volume components packaged in the cut tapes and do mounting for production trial and small lot production
Customer	Tray 1 Pallet 10 Kind (License) - You can place onto a pallet up to 10 kinds of feeder supply components packaged in cut tapes and do production. - For the details, see "5.17 Tray 1 Pallet 10 Kind".

C-36

To increase mounting points and patterns

Customer

Extend Mount Points (50 000 points, 8 000 patterns) (License)

1. Overview

This is a chargeable license to increase the maximum mounting points by model.
(Common to Line/Machine, 2 lane total)

* (The maximum) Mounting point includes patterns and marks.

Now

Models	Mounting points	Patterns	Marks
NPM-W2	10 000	1 000	1 000
NPM-TT2	10 000	1 000	1 000
NPM-D3A	10 000	1 000	1 000
DGS	10 000	1 000	1 000

In the standard specification, there is no system to stop automatic operation due to an error even when production data is over 10 000. When the chargeable license is not activated, however, a warning will be shown when production is started with production data over 20 000.

When Option Activated

Models	Mounting points	Patterns	Marks
NPM-W2	50 000	8 000	8 000
NPM-TT2	50 000	8 000	8 000
NPM-D3A	50 000	8 000	8 000
DGS	100 000	8 000	8 000

In the chargeable license specification, we do not guarantee performance, however, there is no production data limit even when production data is over 50 000.

2. Restrictions

- (1) The following processing may be affected, e.g., Screen response gets slow and screen switching gets slow, Automatic operations do not run smoothly.

* It is not unusual condition. It is because of machine internal processing. Since there are many production data, it takes time to extract and manipulate data.

- Production data loading
- Trace data uploading
- Cycle time
- Teaching, Operations
- Switching to the production data edit screen, Saving, etc.

- (2) It is limited to LNB PC Model No. E27B and after.

C-37

To extend the height scope of mounting components

Customer**Tall Component Mount (License)****1. Overview**

Achieves component mounting up to the maximum height as below.

Mode	Max component height
Now	30 mm (component height)
When Option Activated	Up to 48 mm (maximum transfer height)


Achieves mounting of tall components by changing head movement routes when tall components are mounted to prevent interference between the mounted components and vacuumed components, and interference between the mounted components and a head camera.

2. Applicable Components

It is limited to components that meet the following conditions.

$$30 < Th \leq 48 - Tb - Tk$$

M/C Frame (Cover)



Hc : Max. transfer height
 Th : Mountable component height
 Tb : PCB thickness
 Tk : Carrier height

3. Restrictions

- (1) Head to be able to mount tall components is 3-nozzle head V2.
- (2) Machine to be able to mount tall components is the machine at the very end of a connection line.
- (3) Make sure that there is no mechanical interference at the transfer opening and that sensor at the transfer opening is at high enough so that it is not blocked out.
- (4) It is limited to components delivered from trays.
- (5) Specifications about transfer lanes are as follows.
 - Single Lane, or Tray supplying lane at single lane mode
 - Tray supplying lane at dual lane independent mode.
 - Tall component supplying lane at dual lane share mode and the opposite lane
(You cannot attach beams at both sides)
- (6) Tall component mount is after component mounting that are not tall.
- (7) When tall component is being mounted, aging offset does not work.
- (8) Split mounting does not work.
- (9) At tall component mount, 1 turn is 1 pickup and 1 mounting.
- (10) Tall components will be put back in the tray that it was picked up from.
- (11) Mounting does not work at 2nd Mount Position.
- (12) You cannot continue production when you finished production after tall component was mounted.
- (13) Tray stock Auto Change does not work.
- (14) LCR checker does not work.
- (15) When picked up with a nozzle whose total length is longer than 22.5 mm, the maximum component height gets lower by the length going beyond.
 ([e.g.] When nozzle length is 25.5 mm, the maximum component height gets 3 mm lower)

C-38

To mount large heavy components

Customer**Large Heavy Component Mount(License)****1. Overview**



Enables mounting of large heavy components (over □90 mm ~ □135 mm).

2. Applicable Components①

Items	Specifications	
Component Mass	Max. 300 g (Max.320 g including nozzle) * When 6617/ 6617N nozzle is used. Component mass, whether pickup is OK or not, depends on some elements, such as how large the surface area is for pick-up. Some components cannot be picked up because of its shape.	
Pick-up Surface Appearance	Component surface near the center of gravity is flat for stable pick-up, Not having bump or hole, Surface area is enough for pick-up.	
Components	Over □90 mm ~ □135 mm	
Maximum Component Thickness	When component diagonal outer dimension is 152.1 mm or shorter	30 mm at the maximum (Nozzle No. is 3451/3451N)* ¹ * When nozzle No. is 6617/6617N, it is 27 mm at the maximum* ¹
	When component diagonal outer dimension is longer than 152.1 mm	13 mm at the maximum. (The maximum outer dimension is □135 mm)

*1 When you choose "Tall Component mount" (option), it is "Mount component + PCB thickness + Carrier thickness ≤ 48mm".

Nozzle Outline Dimensions

Nozzle No.	3451 / 3451N	6617 / 6617N
Model ID	MTKU001354AB MTKU003487AA(with 2D code)	MTKU0055174AA MTKU005446AA(with 2D code)
Shape (Unit: mm)		
Notes	With NBR pad Nozzle length : 22.5 mm (+ Pad allowance : 0.3 mm)	With NBR pad Nozzle length : 25.5 mm (+ Pad allowance : 0.5 mm)

* 3451/ 3451N nozzles are limited to ones with small inertia(moment of inertia).


Component mass is Max.80 g (Max. : 110 g nozzle included), for your reference.

* Whether components are compatible is judged finally from vacuum experiment since it is affected by various elements such as whether there is a vacuum leak, component size, component mass, and center of gravity.

Inertia6617/ 6617N nozzle Max. $9.1 \times 10^{-4} \text{ kg} \cdot \text{m}^2$ 3451/ 3451N nozzle Max. $1.0 \times 10^{-4} \text{ kg} \cdot \text{m}^2$

(Determined from the following formula)

$$J = M \times (L^2 + W^2) \times 10^{-9} / 12 [\text{kg} \cdot \text{m}^2]$$

* Provided that it is with square components and θ is 10%.

C-38

To mount large heavy component

Customer

Large Heavy Component Mount(License)

3. Applicable Components②


Mountable BGA conditions are as follows.

* Basically, in BGA mounting, we will receive samples and then decide whether it is mountable after going through consideration and experiments.

	Items	Specifiaications
Dimensions	Outer Dimension	Over □90 mm ~ □135 mm
	Component thickness	0.3 mm ~ 30 mm (Nozzle No.3451/3451N)* ¹ *When nozzle No. is 6617/6617N, it is 27 mm at the maximum* When diagonal component outer dimension is longer than 152.1 mm, it is 13 mm at the maximum.
	Ball pitch	0.3 mm ~ 1.5 mm
	Ball Diameter	φ0.15 mm ~ φ0.9 mm
Notes	Ball shape	Spherical or Columnar
	Ball Material	High-temperature solders, Eutectic solders
	Balls	Lattice Layout : 2 x 2 ~ 64x 64 balls (Row x Column) (Staggered Layout : 2 x 2 ~ 32x 32 balls (Row x Column) * Ball pitch should be uniform. Non-Lattice Layout : 2 ~ 15 000 balls
	Ball surface appearance	Not having cloudy appearance by oxidation on the ball surface. (We will check oxidation degree and decide whether recognition is OK after going through experiments)
	Feeding type	Tray or Tape, Face-down feeding (with balls facing down)
	Others	We will decide whether it is mountable after sample assessment.


*1 When you choose "Tall Component mount" (option), it is "Mount component+PCB thickness+Carrier thickness≤48mm".

4. Conditions

Items	Specifications
Applicable head	3-nozzle head V2
Appropriate nozzle position	Pos2 (NP2)
Recognition	3-division recognition ($Cx \leq 135$ mm and $Cy \leq 135$ mm) * 3-division recognition requires a separate calibration. To do calibration, "Multi recognition camera 3D jig" is necessary.
Applicable nozzle changer	Nozzle changer unit (Shield nozzle for 3-nozzle head : when using two L size) * It is necessary when you use 6617/ 6617N nozzles. 

C-39	To communicate bad mark data with other company machines
Customer	
Bad Mark Communication from other company machines(License)	
1. Overview Transfers bad mark data using bad mark data in each PCB written on a LNB's shared folder from your systems, for example other company inspection machines. This reduces bad mark reading time on a stage at the head of a line. Each machine using bad mark communication needs this option. * See "5.8.1 When Receiving Bad Marks from Other Company Inspection Machines" for the details. 2. Restrictions (1) You cannot use with APC system ready or interface software of other company inspection machines(option). (2) You cannot use with the following iLNB features when PCB barcodes are read with a mounter head camera (ア) Automatic changeover of iLNB's PCB ID reading method (イ) Features needing to read PCB IDs with an iLNB ① (Gate check, Different model check, PCB ID notification to upper systems) (3) Barcodes must be printed on an upper surface of a PCB. (4) You need to add barcode data(positions and size) as production data. (5) 2D codes that can read PCB barcodes are as follows. 1. Compatible with standards(Data Matrix, GR codes, Micro QR codes) 2. Max size : □5 mm 3. Max data : 128 (alphanumeric characters) (6) Use your system and write bad mark data in each PCB to a LNB's shared folder in the given format (7) You cannot use LNB automatic changeover of other company machines and bad mark communication from other company machines at the same time. (8) PCB ID barcodes need reading at the head of a line. ① There are cases in which you may have to add an external scanner or other devices. * (3)(4)(5) are applicable when PCB barcodes are read with a mounter head camera.	

C-40	To perform polarity test of tray components and tape feeder components right before pickup.
Factory	
	Pre-pickup inspection (Polarity) (License)
	- Before picking up tray components and tape feeder, head camera captures component images and performs polarity tests to prevent setting wrong. - When test result shows polarity direction is correct, components are picked up and mounted. - When polarity direction is not correct, the image is shown, and it will be in single stop. - For the details, see "5.10 Pre-pickup inspection (Polarity)".
C-41	Automatic recovery when pickup error or recognition error occurs and to continue production
Customer	
	Pickup error automatic recovery (License)
	- It is automatic position teaching when pickup error or recognition error occurs. When teaching is done successfully, production does not stop. It continues running the production. That reduces number of equipment downtime and enhances operating rate. - For the details, see "5.9 Pickup error automatic recovery".
C-42	To display a chosen image when you haven't used touch panel for a certain period.
Customer	
	Message board (License)
	- If you are not going to operate a touch panel for a certain period of time, you can display a user-selected screen on it. - When you make better use of vacant monitors and display screens such as an operator training or shift information on them, you could train and give instructions to operators while working on producing. - See "5.12 Message Board" for the details.
C-43	Visual control of placement head conditions and to prevent troubles.
Customer	
	Head diagnosis (License)
	- Diagnosis of placement heads prevents the occurrence of problems and assures stable operation. - See "5.13 Head Diagnosis" for the details.

D-1	To keep the machine condition in regular maintenance.				
Option name	Usage	Description	Remarks		
Customer Greasing set	Greasing the specified parts of machine	Grease gun Nozzle 	Common with NPM series, NPM-X series, AM100, CM602, CM402, CM401, CM400, DT401, DT400, CM232, CM212 and CM101.		
Customer Maintenance jig	Regular maintenance	Grease for Heads (Contained in a syringe) Nozzle cleaning jig (Pin gauge) Cleaning brush	Common with NPM series, NPM-X series and AM100.		
• These are used for the periodical application of grease and cleaning in machine maintenance, etc. • They are necessary in purchasing the first machine.					
Option name	Purpose	Descriptions	Remarks		
Customer Maintenance jig (For Lightweight 16-nozzle head V3A)	Regular maintenance (This is for regular cleaning)	Brush for cleaning chart marks off	NPM series, NPM-X series		
	This is for attaching blocks for chart marks (This is for attaching things in the calibration work)	Torque wrench Bit			
• This is necessary in purchasing the first machine.					
Customer Nozzle holder cleaning jig: For 16-nozzle head* ¹ Nozzle holder cleaning jig: For 12-/ 8-nozzle head* ²					
• A set of nozzle holder cleaning jigs is required per line. Please select according to head configuration. *¹ It is for NPM series, NPM-X series only. *² Common with nozzle holder cleaning jig for NPM series, NPM-X series 12/ 8 nozzle head and the one for CM series 12/ LS 8 nozzle head. (You cannot use with general-purpose head(8-nozzle))					
 Cleaning for inner nozzle holder Cleaning for outer Z-axis shaft					
Nozzle holder cleaning jig	Applicable head			Diameter of hole and shaft	
	NPM series NPM-X series	CM602-L	CM101-D		CM232-M
For 16-nozzle head	Lightweight 16V3A/ Lightweight 16V2/ 16				φ2 mm
For 12-/ 8-nozzle head	12/ Lightweight 8/ 8	12/ LS 8	12/ LS 8	12	φ3 mm

D-2	To calibrate as needed.				
• Placement head jig kits for various adjustments. • Common with NPM series and NPM-X series except for plane calibration jig.					
Option name	Usage	Description	Recommended set		
			Recommended	Calibration after Head exchange	All calibration
Customer (1) Jig kit for accuracy verification	For teaching placement position of chip component and for verifying accuracy	Placement position teaching jig (Glass PCB, Jig chip parts)	(1)	(1) + (2)	(1) + (2) + (3) + (4)
	For teaching placement position of QFP placement and for verifying accuracy	Jig parts, Jig parts supplier, Jig parts supply pallet, Nozzle for each Head (153AS × 2, 153 × 2, 184 × 2, 1001 × 2, 1003 × 2)			
Customer (2) Jig kit for standard calibration	For calibration in changing Heads	Jig station, Jig parts	/	/	
	For pickup position calibration	Pickup position height teaching jig			
Customer (3) Jig kit for adjusting the main body	For placement height calibration	Placement height jig (not used with NPM-W2)			
	For line-camera-related calibration	Line camera jig			
	For placement load calibration	Placement load measuring jig			
Customer (4) Plane calibration jig	For plane calibration	Common with NPM-W, AM100			

The following nozzles are separately needed for placement position teaching. (requisite minimum number)

	For jig chip (1005) calibration (required)		For 0402R calibration (recommended)*2	
16-nozzle head	230CS (or 230CSN) nozzle	16 pcs./ head	256CS (or 256CSN) nozzle	16 pcs./ head
12-nozzle head		12 pcs./ head		12 pcs./ head
8-nozzle head	230C (or 230CN) nozzle	8 pcs./ head	256C (or 256CN) nozzle	8 pcs./ head
3-nozzle head	1001 (or 1001N) nozzle*1	3 pcs./ head	/	

*1 1001 nozzles (2 pcs.) are included with (1) jig kit for accuracy verification.

*2 For 0402 chip placement, tape feeder for 0402 or thin type tape feeder is required.

• The following carry case is included in each jig kit.



Case for jig kit for accuracy verification



Case for standard calibration jig kit



Case for jig kit for adjusting the main body



Case for jig kit for adjusting the main body

D-3	Required for exchanging/removing the Head.		
Option name		Usage	Description
Customer Unit exchanging tool		Replacement or removal of head unit	Torque wrench Long bit
It is for NPM series and NPM-X series only.			

D-4

To maintain the nozzle head automatically.

Customer

Head maintenance unit

1. Summary

Attachment / Detachment of nozzle holder & cleaning and inspection of spline shaft can be done automatically by this unit.

Not only reducing man-hours, but also eliminating inconsistent manual maintenance, the consistency of mounting quality can be controlled.

This unit is Installed on feeder cart of NPM Series and NPM-X Series, or 13-slot feeder base. (Use the 8-slot right edge)

* When target head is 8-nozzle head, you need to select the Side lighting option.

2. Specifications

Item	Specification
Mountable Model	NPM series, NPM-X series *1
Target Head	Lightweight16-nozzle head V3A/ 12-nozzle head/ Lightweight 8-nozzle head
Function	①Nozzle holder attachment / detachment*2 ②Nozzle holder shaft cleaning ③Nozzle holder shaft bending inspection ④Nozzle holder sliding inspection
Operation Mode	- Full inspection mode - Function selection mode (Individual execution ① ~ ④)
Operation Time	Lightweight 16-nozzle head V3A (Full inspection model): About 10 min. / 1 head
External Dimensions	W 166 × D 640 × H 240 mm
Weight	About 9 kg
Electric Source	DC 24 V (Supply form main body)
Pneumatic Source	Supply form main body*3
Environment	Temperature: 10 °C ~ 35 °C (No condensation)
Accessory	- Nozzle holder pallet × 1 - Side filter for 16-nozzle head × 30 - Side filter for 12-/ 8-nozzle head × 30 - Bottom filter × 30

*1 When Install the head maintenance unit on an existing line, may need to update the software of equipment, NPM-DGS(Data generation system), LNB(Line Network Box) and so on. Please consult us separately for details.

*2 Nozzle holder cleaning cannot be performed.

If the nozzle holder of 12/8 nozzle head is N610067607AD or before, will be available by exchange to N610067607AE or later.


*3 When using this unit on a "30-slot feeder car" or "13-slot feeder base",

The "Air supply connection kit(option)" is required.

Main unit




Head maintenance unit



Nozzle holder pallet

Cleaning unit

12/8 nozzle head
Side filter16-nozzle head
Side filter

Bottom filter

D-4

To maintain the nozzle head automatically.


Customer

Head maintenance unit

3. Important Points

- When recovery from an error during operation, must make a visual confirmation before continuing the operation.
- Old type head maintenance unit does not work with Lightweight 16-nozzle head V3 or V3A.
How to tell the difference between old and new is to see a Model No. printed on a nameplate label on the detachable grip side.

	Old N610154798AA	New N610154798AB
Lightweight 16-nozzle head V3A	×	○
Lightweight 16-nozzle head V3	×	○
Lightweight 16-nozzle head V2	○	○
Lightweight 16-nozzle head	○	○
16-nozzle head	○	○

**On-site**

Air supply connection kit

- This air supply connection kit is used for feeder cart.
- Please refer to the following information and select the kit for each cart.
- When using this unit on the feeder cart without an "Air supply unit for feeder"

Item name	Item No.	Remodeling target
Air supply connection kit (For 30 slot feeder cart)	N610167970AA	30 slot feeder cart

- This option is used for feeder cart remodeling.
- The removability of air supply section can be improved after remodeling by this option.

- When using this unit on the feeder cart with an "Air supply unit for feeder"

Item name	Item No.	Remodeling target
Air supply connection kit (With the air supply unit for feeder : 30 slot)	MTKA001661AA	30 slot feeder cart
Air supply connection kit (For 13-slot feeder base)	N610167971AA	13-slot feeder base

- This option is used for the remodeling of feeder cart and feeder base.
- When using this unit on the feeder cart and feeder base which with an "Air supply unit for feeder", will need this option to remodel.

* The "Air supply unit for feeder" is a supply port to supply air from a feeder cart or feeder base to stamp unit and etc..

Customer

Additional cleaning filter

- ① Side filter : for 16-nozzle head (100 pcs./1 set)
- ② Side filter : for 12-/ 8-nozzle head (100 pcs./1 set)
- ③ Bottom filter (100 pcs./1 set)

- Side filter is used for side cleaning of spline shaft.
(Each filter can be used to clean 2 heads.)
- Bottom filter is used for tip cleaning of spline shaft.
(Each filter can be used to clean 4 heads.)

Customer

Additional nozzle holder pallet

- It is a palette for the nozzle holder storage.
By setting up the clean nozzle holders, you can exchange them by a palette.

D-5

To splice the parts tape automatically

Customer

Automatic tape splicing unit (Model ID : ATSU Model No: NM-EJW7A)

1. Summary

This unit can splice 8 mm tape automatically.

By eliminating inconsistent manual splicing, this can avoid the low pick up rate and can suppress cuts or out of line of splicing areas. As a result, the operation efficiency can be enhanced.

2. Specifications

Item	Specification
Applicable tape	8 mm Paper/ Embossed *1
Splicing tape	Common to Paper/ Embossed (This unit only)
Empty pockets of splice junction	• 8mm × 4P(Paper/Embossed)= 4pocket *2 • 8mm × 2P(Paper/Embossed)= 8~9 pockets
Operation Time	• Paper tape/ Embossed tape About 10 sec
External Dimensions	W 500 × D 500 × H 1 160 mm
Weight	Approx. 45 kg (Without battery)
Electric Source	DC12 V (Lead-acid battery) Continuous working time: About 16~20hours (With 2 batteries) *3
Environment	Temperature: 10 °C ~ 35 °C (No condensation)
Accessory	• Splicing tape (500 pcs./reel) × 1 pc. • Battery box × 2 pcs. (Including 2 connection cables) • Charging terminal × 2 pcs. • Rubbish box × 1 pcs. • Tape cutting jig × 1 pc
Main body operation (Setting)	Splicing part Recommended setting available

*1) 8 mm × 1P (Paper) : Prior confirmation will be needed.

*2) Empty pockets in 8mm × 4P can become zero by changing pretreatment conditions


*3) This is estimated time in the situation where 28Ah deep cycle battery is used. Working time may vary depending on battery's capacity.



Automatic tape splicing unit



Paper tape complete example



Embossed tape complete example



Splicing tape

3. Important Points

- Exclusive splicing tape required. (Can purchase the splicing tape from the maker directly)
- We recommend to treat the [parts tape cut blade] and the [splicing tape cut blade] as service parts. Our servicemen will do the replacement work.

Customer

Splicing tape (500 pcs./reel)
 Battery box (Including connection cable)
 Charging terminal
 Rubbish box
 Tape cutting jig

D-5

To splice the parts tape automatically

Customer**Battery · Charger****1. Summary**

Battery and charger are prepared by customers.
Specifications are as the table below.

2. Battery specification

Item	Specification
Type	Lead-acid battery
Nominal Voltage	DC 12V
Nominal Capacity	More than 20 Ah (Recommended capacity is 25Ah or more) *1 *2
External Dimensions	W 185 mm or less × D 125 mm or less × H 175 mm or less
Weight	Below 10 kg
Battery Type	Deep cycle battery (For EV)
Cycle Durability (Charge1 time/Discharge1 time)	More than 300 cycles*1
Terminal Shape	Screw (M5) *3
Others	Maintenance free*1

*1 Recommendation, not necessary.


*2 Time to run on one time charge becomes shorter though it runs on 12Ah capacity battery.

*3 The terminal shape of connection cable on Battery box is M5 Ring Terminal. Please make sure the battery is available.

3. Charger specification

Item	Specification
Specification	Adapted to the battery above. Maximum current should be 10A or less when using charging terminal.*4
Others	With protective functions (Reverse-connection protection, Overcharge protection)

*4 Do not use the charging terminal when maximum current is more than 10A, causing the damage of the cable.

4. Constitution (Battery charging)

D-6	To maintain the tape feeder automatically.					
Customer						
Feeder maintenance unit (Model ID : IFMU Model No. : NM-EJW8A)						
1. Overview						
This unit is able to maintain the intelligent feeder and to calibrate the pickup position automatically. You can do the inspections are the same as our shipment inspections for quality control.						
2. Specifications						
Item		Specifications				
Applicable feeder		8 mm W~ 72 mm (including deep groove) * 8 mm single tape feeder, 88 mm tape feeder, 104 mm tape feeder, 8mm double tape feeder and 12/16 mm tape feeder manufactured before 2004 are not included.				
Function	Feeder	Tape width(mm)				
	Item	8W	12/ 16	24/32	44/ 56	72
	Motor torque inspection*1	○	○	○	○	○
	Accuracy measurement of tape feeding (X · Y)*2	○	○	○	○	○
	Height detection of tape hold cover*3	○	—	—	—	—
	Clear the maintenance calculation*4	○	○	○	○	○
	Inspection results storage*5	○	○	○	○	○
	Adjustment support of pickup position in X direction*6	○	○	○	○	○
	Switch & I/O inspection*7	○	○	○	○	○
	Feeder firmware update*8	○	○	○	○	○
Number of attachable feeder	Up to 10 tape feeders (It is possible to attach different types.) 8 mmW : 10 feeders 12/ 16 mm : 10 feeders 44/ 54mm : 3 feeders 24/ 32mm : 5 feeders 72mm : 2 feeders					
Operating time	Up to 60 sec / tape feeder					
Dimensions	W 769±5mm × D720±5mm × H 1 407±5 mm(without feeder & safety cover)					
Mass	Approx. 155 kg (without feeder)					
Electric Source	Single-phase, AC 100 V ~ 240 V 50/ 60 Hz * The power cable (Inlet type) should be prepared by customer. * Please use the power plug which measure up to the specification of "AC plug (IEC 60320 C13: 10 A/ 250 V)".					
Pneumatic Source	Supply air pressure	0.5 MPa ~ 0.8 MPa				
	Supply air amount	15 L/min (A.N.R.)				
	Please install moisture and oil separators on the compressor to ensure the supply of cleaned, dried and compressed air.					
Environment	Temperature: 10 °C ~ 35 °C(No condensation)					

*1 A function to determine the quality by confirming motor torque.

*2 A function to measure accuracy verification of sprocket pin (X,Y), and register the offset of start point.

*3 A function to detect the height of tape hold cover.

*4 A function to clear the maintenance calculation.

*5 A function to store the comprehensive judgment and detailed results in feeder memory or PC hard disk.

*6 A function to support the adjustment of pickup position in X direction.
It is a manual adjustment by using the tool.

*7 A function to inspect the sensor, operating switch, LED, etc..
Sensor & Operating switch are manual inspection.
The NG results will be stored in feeder memory or PC hard disk.

*8 A function to update the feeder firmware.

3. Notice

• Please use the master jig (option) to adjust the offset of starting point regularly.



D-6	To maintain the tape feeder automatically.
Customer	
Master jig	
To customers who are going to buy the IFMU (Feeder maintenance unit) : This unit requires a master jig for calibration (a regular offset adjustment of start point). • The Item No. of master jig is MTKA008066AA. • If you have an IFCU (Intelligent Feeder Check Unit), only need to buy a remodeling kit (MTKA007514AA). (The case when you are using a master jig which Item No. is N610005354AA or N610005354AB)	

D-6

To maintain the tape feeder automatically

Customer


Attachment for thin type single feeder

Required for thin type single feeder and ALF.

1. Specifications

Item	Specifications					
Applicable feeder	When selecting thin type single tape feeder options : 8/4 mm thin type single tape feeder, ALF(Auto Load Feeder)					
Number of attachable feeder	For thin type single tape feeders, up to 8 / (16) feeders *When installing 1 / (2) pcs of attachment * It is possible to attach different types.					
Function	Feeder		Tape width (mm)			
	Item	8mm Thin type	4mm Thin type	ALF		
	Motor torque inspection* ¹	○	○	○		
	Accuracy measurement of tape feeding(X,Y)* ²	○	○	○		
	Height detection of tape hold cover* ³	○	○	○		
	Clear the maintenance calculation* ⁴	○	○	○		
	Inspection results storage* ⁵	○	○	○		
	Adjustment support of pickup position in X direction* ⁶	○	○	○		
	Switch & I/O inspection* ⁷	○	○	○* ⁸		
	Feeder firmware update * ⁹	○	○	○		
*1 A function to determine the quality by confirming motor torque. When feeder is thin type single tape feeder, quality determination by current is performed. *2 A function to measure accuracy verification of sprocket pin (X,Y), and register the offset of starting point. *3 A function to detect the height of tape hold cover. *4 A function to clear the maintenance calculation. *5 A function to store the comprehensive judgment and detailed results in feeder memory or PC hard disk. *6 A function to support the adjustment of pickup position in X direction. It is a manual adjustment by using the tool *7 A function to inspect the sensor, operating switch, LED, etc.. Sensor & Operating switch are manual inspection. The NG results will be stored in feeder memory or PC hard disk. *8 ALF inspection uses two rolls of jig tapes *9 A function to update the feeder firmware.						
Operating time	Up to 60 sec / tape feeder(8 mm thin type single tape feeder, ALF) Up to 90 sec / tape feeder(4 mm thin type single tape feeder)					

- If you have unsupported IFMU (Feeder Maintenance Unit) which does not support thin type single feeder, remodeling to support thin type single feeder and ALF is required. Please contact us.



D-6	To maintain the tape feeder automatically
Customer	Master jig for thin type single feeder
	Jig to calibrate attachment for thin type single feeder (a regular offset adjustment of start point). Item No. of master jig (with case) for thin type single feeder (8 mm thin type, 4 mm thin type, and ALF) is MTKA015403AA. 
Customer	Auto load feeder jig tapes
	This is a jig used only for switch monitoring of auto load feeder and Input/Output status inspection. Product number is MTKP016406AA and this is sold in a set of two jig tapes. * In order to perform switch monitoring of auto load feeder and/or Input/Output status inspection, you will need "Attachments for thin type single feeders" 

D-6

To maintain the tape feeder automatically.

Customer

When using the Feeder maintenance unit (IFMU), the following hardwares & softwares should be prepared by customer.

1. The following items should be prepared by customer.

The following items should be prepared by customer.

Item	Specifications	Quantity																				
PC	IBM PC/AT-compatible machine (including monitor, keyboard, mouse)	1 set																				
Cable	RS232C cable(crossover cable) • Connector : Dsub-9 Pin • Connector screw : #4-40 Inch • Connector pin layout (refer to the figure below) <table><tr><td>Pin No.</td><td>Signal</td></tr><tr><td>1</td><td>Not used</td></tr><tr><td>2</td><td>RXD</td></tr><tr><td>3</td><td>TXD</td></tr><tr><td>4</td><td>Not used</td></tr><tr><td>5</td><td>GND</td></tr><tr><td>6</td><td>Not used</td></tr><tr><td>7</td><td>RTS</td></tr><tr><td>8</td><td>CTS</td></tr><tr><td>9</td><td>Not used</td></tr></table>	Pin No.	Signal	1	Not used	2	RXD	3	TXD	4	Not used	5	GND	6	Not used	7	RTS	8	CTS	9	Not used	1 pc.
Pin No.	Signal																					
1	Not used																					
2	RXD																					
3	TXD																					
4	Not used																					
5	GND																					
6	Not used																					
7	RTS																					
8	CTS																					
9	Not used																					
Conversion cable	USB-RS232C conversion cable *Required when there is no RS232C port on the PC.	1 pc.																				
Power cable	Inlet type	1 pc.																				

2. PC(Hardware/OS)Requirements

Item	Specifications
Main body	IBM PC/AT-compatible machine(A desktop PC is strongly recommended)
CPU	Intel® Core™2 Duo 2.4GHz equivalent or greater
Graphic board	SXGA or higher 1280 × 1024 or more
Memory	2GB or more
HDD	80 GB or more
Optical drive	DVD-ROM
Keyboard	English version: 101 keyboard Japanese version: 106 keyboard
Mouse	Supported by your OS as standard
Monitor	SXGA ready
Network card	1000BASE-T × 1 Port or more (PCI Express network card is recommended) Jumbo Packet (Jumbo Frame) supported *1000BASE-T × 2 Port or more when connecting PanaCIM
RS232C Port	1 Port or more *RS232C card is recommended. When there are no RS232C cards, please prepare an USB-RS232C conversion cable.
OS	Microsoft® Windows® 10 Pro (64-bit)

10. Paint Color

■ Standard color


White W-13 (G50)

* The paint color cannot be designated.

11. Safety Devices

NPM-W2 has the following safety devices for the safety use of machine.

When an emergency stop switch is pressed or the cover is opened while the machine is operating, the operation is forcibly stopped.




** Remarks **

- Please check enough the separate instruction manuals and the warning instructions of equipment to operate the machine properly, regardless of it being in operation or in stop, for the purpose of safety uses.

12. Electric / Pneumatic

12.1 Electric Source Unit

- The power source should be connected with four-conductor cable ranging from 3.5 mm² to 5.5 mm², by using the exclusive tool.
- The cable should be clamped in two points as the lower-left figure shows.
 1. Outside diameter dimensions of the cable: $\phi 13.5$ mm ~ $\phi 18.0$ mm
 2. Be sure to secure the cable with the cable clamps so that it will not be moved by being pulled (100 N) or turned.



■ Precautions in terminal block connection



Terminal connecting pin (Recommended)

Manufacturer: Phoenix Contact

Type: 3.5 mm² ~ 4.0 mm² AI 4-12 GY

5.5 mm² ~ 6.0 mm² AI 6-12 YE

1. Insert the sleeve terminal with its uneven surface parallel to the terminal block.
2. Make sure that the sleeve terminal is fully inserted.
3. Use a tool like that shown below.




4. If the sleeve terminal is not used, fully check for the conductors spread out and the inserted state.

** Remarks **

- Please prepare the electric source cable by yourself.

12.2 Pneumatic Source Unit






13. Dimensions

(Unit: mm)

■ When connecting feeder carts

Single conveyor specification

Dual conveyor specification





** Remarks **



- The above Illustrations do not strictly agree with the actual machine in a reduced scale, etc. When examining the line configuration, dimensions, etc., please ask for the materials for them.
- If passing ducts etc. under this machine, please secure 40 mm or more space between them.

(Unit: mm)

■ When connecting single tray feeder




■ When connecting twin tray feeder




(Unit: mm)

■ When connecting to feeder cart (Including stackable stick feeder)

Single conveyor specification



Dual conveyor specification




* When exchanging the feeder, the space required is as the following.

- When removing feeders from the side, a space of 400mm as in the figure above is required
- In order to remove a feeder in a middle position with feeders at both sides, space of total feeder length (max. 1 600mm) is required.


(Unit: mm)

■ When connecting to single tray feeder (Including stackable stick feeder)

Single conveyor specification



Dual conveyor specification



* When exchanging the feeder, the space required is as the following.



- When removing feeders from the side, a space of 400mm as in the figure above is required
- In order to remove a feeder in a middle position with feeders at both sides, space of total feeder length (max. 1 600mm) is required

(Unit: mm)

■ When connecting to twin tray feeder (Including stackable stick feeder)

Single conveyor specification

Dual conveyor specification




* When exchanging the feeder, the space required is as the following.

- When removing feeders from the side, a space of 400mm as in the figure above is required
- In order to remove a feeder in a middle position with feeders at both sides, space of total feeder length (max. 1 600mm) is required


(Unit: mm)

■ Adjust Bolt Diagram

Single conveyor specification




Dual conveyor specification




(Unit: mm)

Single tray feeder



* The tray feeding height of 896 mm is a standard value when the PCB transport height of NPM-W2 is 900 mm.
The adjustable range: $896^{+65}_{-16.5}$ mm


Twin tray feeder




* The tray feeding height of 838 mm is a standard value when the PCB transport height of NPM-W2 is 900 mm.
The adjustable range: $838^{+65}_{-16.5}$ mm

When exchanging the feeder cart, this is a necessary minimum space.
Before installing the machine, please be sure to secure the following space.

(Unit: mm)



This is the minimum space to be required in installing the twin tray feeder.
Since the tray feeder may be detached in maintenance, please be sure to secure the following space.



- The dimensions in () are used for the single tray feeder.

** Remarks **

- The floor slope in the feeder cart installation area needs to be 6 mm or less in the right/left direction and 11 mm or less in the forward/backward direction. If the floor slope is beyond the above limit, the feeder cart cannot be taken in and out.

14. Regarding Licenses


In order to operate the following software (options), you are required to purchase licenses for respective software.

- PanaCIM-EE ready*
- iLNB ready*
- Component Verification*
- Automatic changeover*
- Feeder Setup Navigator*
- Upper Communication*
- APC system ready
- Interface software of the inspection machine from other companies
- APC-MFB2 System ready
- Support station box (Component verification type)*
- Automatic recovery function for pickup error
- Component inspection before pickup (Polarity)
- Message board
- Head diagnosis
- Remote operation *
- Biometric authentication
- Mount complete position recognition
- LCR checker(Feeder shape type)
- Lightweight 16-nozzle head constant mount load control
- Lightweight 16-nozzle head transfer
- Pre-pickup Inspection(Char/2D)
- AOI info display function
- Extend Mount points
- Other Company Bad Mark Communication
- Large heavy component mount
- Tall Component mount
- Tray 1 Pallet 10 Kind

A license is required for each machine that is intended for the operation.

*The choices of software must be identical among all machines in a line.

Regarding the case in where machines with or without software licenses mixed up in a line, we cannot assure the operation in the whole line.



IMPORTANT—

In order to use above software, you are required to agree to the “Terms and conditions regarding the use of software” on the following page.

Please be sure to look through it.

Terms and conditions regarding the use of software

1. **License Grant.** Upon your payment of the applicable license fee, Panasonic Connect Co., Ltd. ("Licensor") grants only to you a personal, non-transferable and nonexclusive right and license (without the right to sublicense) to use the software ("Software") designed for Panasonic's electronic component placement and insertion systems ("Systems") in accordance with these Terms and Conditions of Use. You may use the Software on an appropriate computer for up to the quantity of manufacturing cells for which you paid a license fee, limited to use in connection with your operation of the Systems, either singly or as part of a manufacturing cell utilizing other brands of manufacturing equipment.
2. **License Limitations.** You may not copy or reproduce the Software or related documentation for any purpose, except that you may make one (1) copy of the Software for backup purposes only in support of your use of the Software in connection with your operation of the Systems. You may not modify, alter, transfer, or prepare any derivative works of the Software or related documentation, or any copy thereof, in whole or in part, without the prior written consent of the Licensor. You may not reverse assemble, reverse compile, or mechanically or electronically trace the Software or related documentation, or any copy thereof, in whole or in part. You may not sell, lease, sublicense, distribute, transfer or assign to any third party the Software or related documentation, or any copy thereof and/or this Software license, in whole or in part.
3. **Non-assignable and Non-sub-licensable.** You shall, with regard to the Software, related documentation and the algorithms, concepts, designs and ideas represented by or incorporated in the Software and related documentation, except the right of use granted in **1. License Grant** above, not obtain any ownership, copyright, right to use of copyrighted works, patent, right to use of patents or other rights in or to the Software, nor may you remove any copyright, trademark, or other notice or product identification from the Software. You must reproduce and include in its entirety any such copyright, notice or product identification, identical or similar to the one included on the Software, on any copy of the Software or related documentation.
4. **Confidentiality.** The Software and the data, documentation, materials and any other information contained in or relating to the Software are Licensor's confidential information. You shall not disclose, distribute or otherwise make the Licensor's confidential information available to any third party without the prior written consent of the Licensor.
5. **Limited Warranty.** The Licensor warrants to you only that the Software will be free from defects under normal use for a period of thirty (30) days from the date of delivery thereof to you (as evidenced by your purchase receipt for the Software); provided, however, that the Licensor's entire liability, and your exclusive remedy under this warranty shall be limited to the replacement of any defective media which is returned to the Licensor, together with a copy of your purchase receipt, within the applicable warranty period. Additionally, in no case shall the Licensor offer or be held liable for the following warranties:
 - (1) The performance or results you may obtain by using the Software;
 - (2) Any defects in the media on which the Software is furnished resulting from your storage thereof;
 - (3) Any defects caused by operation of the media otherwise than as, or in environmental conditions other than those, specified by the Licensor;
 - (4) Any defects caused by accident, misuse, neglect, abuse, mishandling, misapplication, modification, alternation, acts of God, or improper installation or maintenance; or
 - (5) Any defects arising out of modification or attempted modification of the Software by you.
 The express warranty set forth herein in lieu of all other warranties, express, implied or statutory, including, without limitation, non-infringement of third-party rights, the implied warranties of merchantability and fitness for a particular purpose.
6. **Limitation of Liability.** In no event shall the Licensor and Licensor's affiliated companies (including distributors being involved in the sales, etc. of the Software; hereinafter the same) be liable for any damages, including, without limitation, any special, indirect, incidental, consequential, exemplary or punitive damages (including, but not limited to, damages for loss of profits, business, data or information; loss of use of the Software, Systems or any associated equipment; cost of any substitute equipment, facilities or services; or for any claims by any third party) arising out of or in any way related to the use of or inability to use the Software, even if the Licensor and/or its affiliated companies have been advised of, or are aware of, the possibility of such damages.
7. **License Term.** This software license shall, unless otherwise specified by the Licensor or its affiliated companies, be valid without any time limit. You may terminate this license at any time, without refund of any license fee or portion thereof, paid to the Licensor, by returning to the Licensor, at your expense, the Software and related documentation together with all copies thereof in any form. The Licensor and/or its affiliated companies have the right to terminate this software license without notice to you if you fail to comply with any term or condition contained herein (upon any termination, the Licensor shall not refund any license fee, or part thereof, paid to the Licensor). Upon any such termination, you agree to destroy or return to the Licensor, at your own expense, the Software and related documentation together with all copies thereof in any form.
8. **Miscellaneous.** These Terms and Conditions of Use, and other items relating to this license will be governed by the laws of Japan, without regard to conflict of law provisions. You agree that these Terms and Conditions of Use is the complete and exclusive statement of the agreement between you and the Licensor or its affiliated companies, which supersedes any proposal, or prior agreement, oral or written, and any other communications between you and the Licensor or its affiliated companies relating to the subject matter of these Terms and Conditions of Use and this license. Should any part of these Terms and Conditions of Use be declared void or unenforceable by any court of competent jurisdiction, such declaration shall have no effect on the remaining parts thereof.

Important Notes

1. Performance assurance of the Product is subject to the condition that the Product is used in accordance with specifications, specification manuals, and operating instructions provided by us. We do not guarantee performance if the Product is used in any way other than those described in such documents.
 - (a) Never use the Product near any noise generation sources such as welding machines, which will result in malfunctions.
 - (b) Do not unnecessarily turn off the power switch, servo switch, or air during operation; it will run without being controlled, which will result in damage.
 - (c) Before teaching operations or conducting manual operations in a servo free state, make sure there is no interference in the unit, which will result in damage.
 - (d) The covers of the main body, loader/unloader, tray feeder, and the other covers may be cylinder-locked.
Do not attempt to forcibly open the covers, which will result in damage to the covers and/or cylinders.
 - (e) Do not take apart or alter the equipment and its units, as it may influence product safety and/or its quality.
 - (f) Data modifications must only be undertaken by professionally trained and approved personnel. Modifications by unqualified personnel may be a cause of input error, which will result in malfunctions.
 - (g) Do not block any of exhaust openings and intakes. Excessive temperature in the control box is a cause of abnormal functioning.
 - (h) Do not turn off the servo switch during operation, as it may result in control failure.
Always set the Product to a temporarily paused state (e.g. single stop or cycle stop) or operation stop state before the Product is turned off.
 - (i) Be attentive to water quality when using spraying devices and/or humidifiers. In an environment where ultrasonic humidifiers are used, for example, mineral components such as calcium or magnesium, and components such as silica, carbonate, or iron, are released to the air. Such airborne particles stick to the equipment, resulting in the malfunction of sliding parts and/or optical components.
 - (j) Do not use the Product in an atmosphere where gasified low molecular weight siloxane exists.
Low molecular siloxane, released by exposed silicone-based materials (e.g. silicone adhesives, silicone oils, or silicone powders), sticks to the electric contact parts and/or optical components, and will result in contact failure and/or malfunction.
 - (k) Do not use the Product in corrosive gas environments (e.g. nitric acid, hydrogen sulfide, or ammonia), halogen gas environments, or any environment where conductive foreign substances may enter.
Electrodes and/or metal parts of electric components will corrode, and will become a cause of the malfunction of electronic circuits and/or malfunctions.
2. We shall not be held liable for the following failures and damages.
 - (a) Failure and/or damage caused by wrong use or improper repair, adjustment or modification
 - (b) Incidental damage (e.g. loss of profits or the interruption of business) arising from the use of or inability to use the Product
 - (c) Failure and/or damage caused by relocation or transportation of the Product, the dropping of the Product itself or by objects falling on the Product after purchase
 - (d) Failure and/or damage caused by fire, earthquake, flood, thunderbolt, other natural or man-made disasters, pollution damage, salt damage, gas damage (e.g. corrosive gas or halogen gas), abnormal voltage, or the use of power sources besides those specified (e.g. voltage or frequency)
 - (e) Failure and/or damage caused by carriers during delivery via vehicle, ship, or other modes of transport.
 - (f) Damage arising from failure to observe the instructions/cautions of the operating instructions provided with the Product.
 - (g) Any failure caused by hacking, unauthorized access, attacks upon the Product or connected networks and from other similar threats
3.
 - (a) We shall not be held liable for any damage caused by any dispute alleging or claiming the infringement of intellectual property rights and other rights arising in connection with manufacturing inspections or other processes performed during the use of the Products, including any allegation or claim that any items manufactured and/or inspected using the Products is infringing intellectual property rights or other rights of any third party.
 - (b) We shall not be held liable for any allegation or claim of infringement which has been settled or which judgment has been reached without our express written consent.
4. We shall in no event be held liable for any indirect or consequential damages, or for loss of profit that may arise in connection with the Products or their use.
5. The user shall be responsible for determining the necessary structural reinforcement or modifications to the building in which the Products will be installed and for the completion of such measures, all at its own cost and expense, prior to the date of delivery of the Products.

Some of our products fall under the export control items (or technologies) established in the Foreign Exchange and Foreign Trade Act. When exporting (or providing technologies overseas), please check its legal restrictions and be sure to take necessary procedures such as to obtain the export permission.

Panasonic Connect Co., Ltd.

4-1-62 Minoshima, Hakata-ku, Fukuoka City, Fukuoka, 812-8531, Japan